```
Vivado Project Options:
   Target Device                    : xc7vx485t-ffg1157
   Speed Grade                      : -1
   HDL                              : verilog
   Synthesis Tool                   : VIVADO

If any of the above options are incorrect,   please click

MIG Output Options:
   Module Name                      : mig
   No of Controllers                : 1
   Selected Compatible Device(s)    : --

FPGA Options:
   System Clock Type                : No Buffer
   Reference Clock Type             : No Buffer
   Debug Port                       : OFF
   Internal Vref                    : disabled
   IO Power Reduction               : ON
   XADC instantiation in MIG        : Enabled

Extended FPGA Options:
   DCI for DQ,DQS/DQS#,DM           : enabled
   Internal Termination (HR Banks) : 50 Ohms




/*****************************************************/
/*                  Controller 0                     */
/*****************************************************/
Controller Options :
   Memory                           : DDR3_SDRAM
   Interface                        : AXI
   Design Clock Frequency           : 1250 ps (800.00 MHz)
   Phy to Controller Clock Ratio : 4:1
   Input Clock Period               : 4999 ps
   CLKFBOUT_MULT (PLL)              : 8
```

```
   DIVCLK_DIVIDE (PLL)             : 1
   VCC_AUX IO                      : 2.0V
   Memory Type                     : Components
   Memory Part                     : MT41J64M16XX-125G
   Equivalent Part(s)              : --
   Data Width                      : 32
   ECC                             : Disabled
   Data Mask                       : enabled
   ORDERING                        : Normal

AXI Parameters :
   Data Width                      : 256
   Arbitration Scheme              : RD_PRI_REG
   Narrow Burst Support            : 1
   ID Width                        : 4

Memory Options:
   Burst Length (MR0[1:0])           : 8 - Fixed
   Read Burst Type (MR0[3])          : Sequential
   CAS Latency (MR0[6:4])            : 11
   Output Drive Strength (MR1[5,1]) : RZQ/7
   Controller CS option              : Enable
   Rtt_NOM - ODT (MR1[9,6,2])        : RZQ/4
   Rtt_WR - Dynamic ODT (MR2[10:9]) : Dynamic ODT off
   Memory Address Mapping            : BANK_ROW_COLUMN


Bank Selections:
        Bank: 38
                Byte Group T0:  Address/Ctrl-0
                Byte Group T1:  Address/Ctrl-1
                Byte Group T2:  Address/Ctrl-2
        Bank: 39
                Byte Group T0:  DQ[0-7]
                Byte Group T1:  DQ[8-15]
                Byte Group T2:  DQ[16-23]
                Byte Group T3:  DQ[24-31]

System_Control:
        SignalName: sys_rst
```

```
        PadLocation: No connect  Bank: Select Bank
SignalName: init_calib_complete
        PadLocation: No connect  Bank: Select Bank
SignalName: tg_compare_error
        PadLocation: No connect  Bank: Select Bank
```