

Table Of Contents

Table Of Contents ..... 1

How Do I Disable Unnecessary Services? ..... 2

    References: ..... 2

[Home](#) > [Faq](#) > [Mac os x](#)

## Mac OS X Disable Unnecessary Services

Posted by [Vivek Gite](#) <[vivek@nixcraft.com](mailto:vivek@nixcraft.com)>

How do I disable unnecessary services under Mac OS X to secure my Mac OS X based desktop / server / laptop?



Mac OS X use the following directories to start various services (quoting from the man page):

1. **/System/Library/LaunchDaemons/** - System-wide daemons provided by Mac OS X
2. **/System/Library/LaunchAgents/** - Per-user agents provided by Mac OS X.
3. **~/Library/LaunchAgents/** - Per-user agents provided by the user.
4. **/Library/LaunchAgents/** - Per-user agents provided by the administrator.
5. **/Library/LaunchDaemons/** - System-wide daemons provided by the administrator.

launchd manages processes, both for the system as a whole and for individual users using .plist files. Open the terminal and type the following commands to view directory files:

```
cd /System/Library/LaunchDaemons/  
ls -l  
ls -l | less
```

OR

```
cd /System/Library/LaunchAgents/  
ls -l  
ls -l | less
```

## How Do I Disable Unnecessary Services?

You need to use the launchctl command as follows:

```
sudo launchctl unload -w /path/to/.plist/file  
sudo launchctl unload -w /System/Library/LaunchDaemons/file.plist
```

In this example, you are disabling the Bonjour service, enter:

```
sudo launchctl unload -w /System/Library/LaunchDaemons/com.apple.mDNSResponder.plist  
sudo launchctl unload -w /System/Library/LaunchDaemons/com.apple.mDNSResponderHelper.plist
```



### References:

- [launchctl\(1\)](#) <sup>[2]</sup> man page.

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our [daily email](#) newsletter or [weekly newsletter](#) to make sure you don't miss a single tip/tricks. Alternatively, subscribe via [RSS/XML](#) feed.

URLs in this post:

[1] Image: <http://www.cyberciti.biz/faq/category/mac-os-x/>

[2] launchctl(1):

<http://developer.apple.com/Mac/library/documentation/Darwin/Reference/ManPages/man1/launchctl.1.html>

---

Copyright © 2006-2010 [nixCraft](http://www.cyberciti.biz/tips/copyright). All rights reserved. This print / pdf version is for personal non-commercial use only. More details <http://www.cyberciti.biz/tips/copyright>.