

Table Of Contents

Table Of Contents	1
-------------------------	---

[Home](#) > [Faq](#) > [Linux](#)

Linux / UNIX killing a process and restarting the same

Posted by [Vivek Gite](#) <vivek@nixcraft.com>

Q. How do I kill a process called inetd or foo and restart the same so that configuration file get updated?

A. Both UNIX and Linux supports POSIX reliable signals and POSIX real-time signals. Each signal has a current disposition, which determines how the process behaves when it is delivered the signal.



[1]

Generally following command is used

kill -1 process-pid

First get pid of inetd:

```
ps -e | grep inetd
```

Now force read inetd.conf:

```
kill -1 xinetd-pid
```

You can also use pkill command used to send signals. The pkill command allows the use of extended regular expression patterns and other matching criteria.

pkill -HUP process-name

Make syslog reread its configuration file

```
# pkill -HUP syslogd
```

Make xinetd reread its configuration file

```
# pkill -HUP inetd
```

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our [daily email](#) newsletter or [weekly newsletter](#) to make sure you don't miss a single tip/tricks. Alternatively, subscribe via [RSS/XML](#) feed.

Article printed from Frequently Asked Questions About Linux / UNIX: <http://www.cyberciti.biz/faq/>

URL to article: <http://www.cyberciti.biz/faq/howto-linux-unix-killing-restarting-the-process/>

URLs in this post:

[1] Image: <http://www.cyberciti.biz/faq/faq/category/unix/>