# **Table Of Contents**

Table Of Contents	. 1
Step # 1: Delete old ssh host keys	
Step # 2: Reconfigure OpenSSH Server	
Step # 3: Update all ssh client(s) known_hosts files	. 2

nixCraft: Linux Tips, Hacks, Tutorials, And Ideas In Blog Format <a href="http://www.cyberciti.biz/">http://www.cyberciti.biz/</a>

Home > Faq > Debian / Ubuntu

#### **Ubuntu / Debian Linux Regenerate OpenSSH Host Keys**

Posted by Vivek Gite <vivek@nixcraft.com>

This entry is part 1 of 2 in the series openssh [1]

openssh [1]

- Ubuntu / Debian Linux Regenerate OpenSSH Host Keys
- Run SSH In The background After Running a GUI Linux Application [2]

Q. How do I regenerate OpenSSH sshd server host keys stored in /etc/ssh/ssh\_host\_\* files? Can I safely regenerate ssh host keys using remote ssh session as my existing ssh connections shouldn't be interrupted?



A. To regenerate keys you need to delete old files and reconfigure openssh-server. It is also safe to run following commands **over remote ssh session**. Your **existing session shouldn't be interrupted**.

### Step # 1: Delete old ssh host keys

Login as the root and type the following command:

```
# /bin/rm /etc/ssh/ssh_host_*
```

## Step # 2: Reconfigure OpenSSH Server

Now create a new set of keys, enter:

```
# dpkg-reconfigure openssh-server
```

#### Sample output:

```
Creating SSH2 RSA key; this may take some time ...
Creating SSH2 DSA key; this may take some time ...
Restarting OpenBSD Secure Shell server: sshd.
```

## Step # 3: Update all ssh client(s) known\_hosts files

Finally, you need to update ~/.ssh/known\_hosts files, otherwise everyone will see an error message:

Either remove  $\underline{\text{host fingerprint}}$  [4] or update the file using vi text editor.

Series Navigation

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our <u>daily email</u> newsletter or <u>weekly newsletter</u> to make sure you don't miss a single tip/tricks. Alternatively, subscribe via <u>RSS/XML</u> feed.

Article printed from Frequently Asked Questions About Linux / UNIX: http://www.cyberciti.biz/faq/

URL to article: http://www.cyberciti.biz/faq/howto-regenerate-openssh-host-keys/

URLs in this post:

- [1] openssh: http://www.cyberciti.biz/faq/series/openssh/
- [2] Run SSH In The background After Running a GUI Linux Application: http://www.cyberciti.biz/faq/run-ssh-gui-background-for-unix-x11/
- [3] Image: http://www.cyberciti.biz/faq/faq/category/debian-ubuntu/
- [4] host fingerprint: http://www.cyberciti.biz/faq/warning-remote-host-identification-has-changed-error-and-solution/

Copyright © 2006-2010 <u>nixCraft</u>. All rights reserved. This print / pdf version is for personal non-commercial use only. More details <a href="http://www.cyberciti.biz/tips/copyright">http://www.cyberciti.biz/tips/copyright</a>.