Table Of Contents	1/2
Table Of Contents	
Table Of Contents	1

Table Of Contents 2/2

nixCraft: Linux Tips, Hacks, Tutorials, And Ideas In Blog Format http://www.cyberciti.biz/

Home > Faq > AIX

sed Insert a Newline Into the RHS of a Substitution

Posted by Vivek Gite <vivek@nixcraft.com>

Q. How do I insert a newline into the RHS of a substitution using sed under Linux / UNIX like operating systems? My line pattern is as follows:

This is a test. This is another input.

I'd like to insert a newline after dot (.).

A. Simple use sed command as follows:



[1]

```
echo 'This is a test. This is another input.' | sed -e 's/\./&\n/'
```

You need to substitute dot and simply insert newline (\n) to replace with it. If you are using older sed version try:

```
echo 'This is a test. This is another input.' |sed 's/\./& \
> /'
```

Sample output:

```
This is a test.
This is another input.
```

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our <u>daily email</u> newsletter or <u>weekly newsletter</u> to make sure you don't miss a single tip/tricks. Alternatively, subscribe via <u>RSS/XML</u> feed.

Article printed from Frequently Asked Questions About Linux / UNIX: http://www.cyberciti.biz/faq/

URL to article: http://www.cyberciti.biz/faq/sed-insert-newline-into-rhs-substitution/

URLs in this post:

[1] Image: http://www.cyberciti.biz/faq/category/bash-shell/

Copyright © 2006-2010 <u>nixCraft</u>. All rights reserved. This print / pdf version is for personal non-commercial use only. More details http://www.cyberciti.biz/tips/copyright.