

Table Of Contents

Table Of Contents .....	1
-------------------------	---

[Home](#) > [Faq](#) > [Linux](#)

## Linux change the runlevel for a server without rebooting

Posted by [Vivek Gite](#) <[vivek@nixcraft.com](mailto:vivek@nixcraft.com)>

Q. How do I change the runlevel for a Linux server without rebooting my server? I am using Gentoo Linux.

A. Almost all Linux distribution use init program to change runlevel. init is the parent of all processes. Its primary role is to create processes from a script stored in the file `/etc/inittab`. This file usually has entries which cause init to spawn gettys on each line that users can log in. It also controls autonomous processes required by any particular system.



[1]

To change runlevel from 3 to 1 you need to type command as follows:

```
# init 1
```

OR

```
$ sudo init 1
```

Where 1 is runlevel number, other possible runlevel values are:

- => 0 - Shutdown server
- => 1 - Take server to single-user mode
- => 2 - Start X Window (used by Debian)
- => 3 - Full multi-user text mode
- => 5 - Start X Window
- => 6 - Reboot server

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our [daily email](#) newsletter or [weekly newsletter](#) to make sure you don't miss a single tip/tricks. Alternatively, subscribe via [RSS/XML](#) feed.

Article printed from Frequently Asked Questions About Linux / UNIX: <http://www.cyberciti.biz/faq/>

URL to article: <http://www.cyberciti.biz/faq/change-the-runlevel-for-a-linux-server/>

URLs in this post:

[1] Image: <http://www.cyberciti.biz/faq/category/x-server/>