Table Of Contents	1/2
Table Of Contents	
Table Of Contents	1

Table Of Contents 2/2

nixCraft: Linux Tips, Hacks, Tutorials, And Ideas In Blog Format http://www.cyberciti.biz/

Home > Faq > BASH Shell

How do I save or redirect stdout and stderr into different files?

Posted by Vivek Gite <vivek@nixcraft.com>

Q. I need to run a program called oraMon.pl. However this program is run from cron job. It report error to stderr and normal output to stdout. How do I save stdout, stderr and both into 3 separate log files?

A. It is not that hard if you know howto redirect stderr, stdout and small command called tee.



[1]

- => fd0 is stdin
- => fd1 is stdout
- => fd2 is stderr

There are two formats for redirecting standard output and standard error:

&>word

and

>&word

For example anything written to fd2 to the same place as output to fd1, you will use: 2>&1

tee command read from standard input and write to standard output and file.

So to send stderr to /tmp/errors.log, stdout to /tmp/output.log and both to /tmp/final.log, type as follows:

```
((/path/to/oraMon.pl 2>&1 1>&3 | tee /tmp/errors.log) 3>&1 1>&2 | tee /tmp/output.log) > /tmp/final.log 2>&1
```

Read bash man page and tee command for more information.

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our <u>daily email</u> newsletter or <u>weekly newsletter</u> to make sure you don't miss a single tip/tricks. Alternatively, subscribe via <u>RSS/XML</u> feed.

Article printed from Frequently Asked Questions About Linux / UNIX: http://www.cyberciti.biz/faq/

URL to article: http://www.cyberciti.biz/faq/saving-stdout-stderr-into-separate-files/

URLs in this post:

[1] Image: http://www.cyberciti.biz/faq/faq/category/bash-shell/

Copyright © 2006-2010 <u>nixCraft</u>. All rights reserved. This print / pdf version is for personal non-commercial use only. More details http://www.cyberciti.biz/tips/copyright.