Table Of Contents

Table Of Contents	1
How do I define bash array?	2
How do I reference any element in bash array?	
How do I find out bash shell array length?	
Putting it all together	

[1]

nixCraft: Linux Tips, Hacks, Tutorials, And Ideas In Blog Format http://www.cyberciti.biz/

Home > Faq > BASH Shell

How To Find BASH Shell Array Length (number of elements)

Posted by Vivek Gite <vivek@nixcraft.com>

Q. How do I define array in a bash shell script? How do I find out bash array length (number of elements) while running a script using for shell loop?

A. Bash provides one-dimensional array variables. Any variable may be used as an array; the declare builtin will explicitly declare an array. There is no maximum limit on the size of an array, nor any requirement that members be indexed or assigned contiguously.



How do I define bash array?

Array can be defined using following syntax:

```
ArrayName=("element 1" "element 2" "element 3")
```

Define array called distro with 3 elements, enter:

```
distro=("redhat" "debian" "gentoo")
```

How do I reference any element in bash array?

Any element of an array may be referenced using following syntax:

```
${ArrayName[subscript]}
```

To print redhat i.e first element enter:

```
echo ${distro[0]}
echo ${distro[2]} # will print gentoo
```

How do I find out bash shell array length?

You can easily find out bash shell array length using following syntax:

```
${#ArrayName[@]}
```

To print distro array length enter:

```
echo ${#distro[@]}
```

Sample output:

```
3
```

If subscript is @ or *, the word expands to all members of name. By prefixing # to variable you will find length of an array (i.e number of elements).

Putting it all together

A sample shell script to print array called NAMESERVERS:

```
#!/bin/bash
# define array
```

```
# name server names FQDN
NAMESERVERS=("ns1.nixcraft.net." "ns2.nixcraft.net." "ns3.nixcraft.net.")

# get length of an array
tLen=${#NAMESERVERS[@]}

# use for loop read all nameservers
for (( i=0; i<${tLen}; i++ ));
do
    echo ${NAMESERVERS[$i]}
done</pre>
```

Sample output:

```
ns1.nixcraft.net.
ns2.nixcraft.net.
ns3.nixcraft.net.
```

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our <u>daily email</u> newsletter or <u>weekly newsletter</u> to make sure you don't miss a single tip/tricks. Alternatively, subscribe via <u>RSS/XML</u> feed.

Article printed from Frequently Asked Questions About Linux / UNIX: http://www.cyberciti.biz/faq/

URL to article: http://www.cyberciti.biz/faq/finding-bash-shell-array-length-elements/

URLs in this post:

[1] Image: http://www.cyberciti.biz/faq/faq/category/bash-shell/

Copyright © 2006-2010 <u>nixCraft</u>. All rights reserved. This print / pdf version is for personal non-commercial use only. More details http://www.cyberciti.biz/tips/copyright.