

Table Of Contents

Table Of Contents ..... 1

Display Current Hashing Algorithm ..... 2

Configure Linux Server To Use The SHA-512 ..... 2

[Home](#) > [Faq](#) > [CentOS](#)

## Linux Upgrade Password Hashing Algorithm to SHA-512

Posted by [Vivek Gite](#) <[vivek@nixcraft.com](mailto:vivek@nixcraft.com)>

The default algorithm for storing password hashes in [/etc/shadow](#) <sup>[2]</sup> is MD5. I was told to use SHA-512 hashing algorithm. How do I set password hashing using the SHA-256 and SHA-512 under CentOS or Redhat Enterprise Linux 5.4?

You need to use authconfig command to setup SHA-256/512 hashing. This command provides a simple method of configuring /etc/sysconfig/network to handle NIS, as well as /etc/passwd and /etc/shadow, the files used for shadow password support. Basic LDAP, Kerberos 5, and SMB (authentication) client configuration is also provided.



[1]

## Display Current Hashing Algorithm

Type the following command:

```
# authconfig --test | grep hashing
```

Sample outputs:

```
password hashing algorithm is md5
```

## Configure Linux Server To Use The SHA-512

To configure the Linux system to use the SHA-512 algorithm, enter:

```
# authconfig --passalgo=sha512 --update
```

Note users need to change their passwords in order to generate hashes using SHA-512. You can force users to [change their password](#) <sup>[3]</sup> on next login:

```
# chage -d 0 userName
```

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our [daily email](#) newsletter or [weekly newsletter](#) to make sure you don't miss a single tip/tricks. Alternatively, subscribe via [RSS/XML](#) feed.

Article printed from Frequently Asked Questions About Linux / UNIX: <http://www.cyberciti.biz/faq/>

URL to article: <http://www.cyberciti.biz/faq/rhel-centos-fedora-linux-upgrading-password-hashing/>

URLs in this post:

[1] Image: <http://www.cyberciti.biz/faq/category/linux/>

[2] /etc/shadow: <http://www.cyberciti.biz/faq/understanding-etcshadow-file/>

[3] change their password: <http://www.cyberciti.biz/faq/rhel-debian-force-users-to-change-passwords/>