Table Of Contents	1/3
Table Of Contents	
Table Of Contents	1

Table Of Contents 2/3

nixCraft: Linux Tips, Hacks, Tutorials, And Ideas In Blog Format <a href="http://www.cyberciti.biz/">http://www.cyberciti.biz/</a>

#### Home > Faq > Debian / Ubuntu

# How to bind a range of IP's in Debian / Ubuntu Linux

Posted by Vivek Gite <vivek@nixcraft.com>

Q. I've recently installed Debian Linux 4.0 on my server and Ubuntu Linux 7.04 on Laptop. I would love to have a multiple IP address that I can use for verity of purposes. I would like to bind 4 IP's to the 'eth0' device or NIC. How do I do that?



A.. Let us assume that your eth0 IP address is 192.168.1.1. You need to create alias or binding using eth0:0, eth0:1...eth0:N devices. You need to add range of IP's in /etc/network/interfaces config file under Debian/Ubuntu Linux. First make a backup of existing file:

```
# cp /etc/network/interfaces /root/working.interfaces
```

#### Now open file using vi text editor:

```
#vi /etc/network/interfaces
```

#### OR

```
$ sudo vi /etc/network/interfaces
```

#### Modify as follows:

```
auto eth0
auto eth0:0
auto eth0:1
iface eth0 inet static
address 192.168.1.1
netmask 255.255.255.248
gateway 192.168.1.254
iface eth0:0 inet static
address 192.168.1.2
netmask 255.255.255.248
gateway 192.168.1.254
iface eth0:1 inet static
address 192.168.1.3
netmask 255.255.255.248
gateway 192.168.1.254
# add rest of alias / binds below
```

### Save and close the file.

## Now restart networking, enter:

```
# /etc/init.d/networking restart
```

#### OR

```
$ sudo /etc/init.d/networking restart
```

Updated for accuracy.

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and

Table Of Contents 3/3

tricks? Subscribe to our <u>daily email</u> newsletter or <u>weekly newsletter</u> to make sure you don't miss a single tip/tricks. Alternatively, subscribe via <u>RSS/XML</u> feed.

Article printed from Frequently Asked Questions About Linux / UNIX: http://www.cyberciti.biz/faq/

URL to article: http://www.cyberciti.biz/faq/bind-alias-range-of-ip-address-in-linux/

URLs in this post:

[1] Image: http://www.cyberciti.biz/faq/faq/category/debian-ubuntu/

Copyright © 2006-2010 <u>nixCraft</u>. All rights reserved. This print / pdf version is for personal non-commercial use only. More details <a href="http://www.cyberciti.biz/tips/copyright">http://www.cyberciti.biz/tips/copyright</a>.