## **Table Of Contents**

Table Of Contents	. 1
grep command to find files by [2] content	
Highlighting searched patterns	
Displaying file names and line number for searched patterns	
Further readings: find command [4] grep command [5] man pages find and grep	

nixCraft: Linux Tips, Hacks, Tutorials, And Ideas In Blog Format <a href="http://www.cyberciti.biz/">http://www.cyberciti.biz/</a>

Home > Faq > AIX

### **How To Find Files by Content Under UNIX**

Posted by Vivek Gite <vivek@nixcraft.com>

Q. I had written lots of code in C for my school work and saved it as source code under /home/user/c/\*.c and \*.h. How do I find files by content such as string or words (function name such as main() under UNIX shell prompt?

A. You need to use following tools:

[a] grep command: print lines matching a pattern.

[b] find command: search for files in a directory hierarchy.



[1]

# grep command to find files by [2] content

Type the command as follows:

```
grep 'string' *.txt
grep 'main(' *.c
grep '#include<example.h>' *.c
grep 'getChar*' *.c
grep -i 'ultra' *.conf
grep -iR 'ultra' *.conf
```

#### Where

- -i: Ignore case distinctions in both the PATTERN (match valid, VALID, ValID string) and the input files (math file.c FILE.c FILE.C filename).
- -R: Read all files under each directory, recursively

#### Highlighting searched patterns

You can highlight patterns easily while searching large number of files:

```
$ grep --color=auto -iR 'getChar();' *.c
```

#### Displaying file names and line number for searched patterns

You may also need to display filenames and numbers:

```
$ grep --color=auto -iRnH 'getChar();' *.c
```

#### Where,

- -n: Prefix each line of output with the 1-based line number within its input file.
- -H Print the file name for each match. This is the default when there is more than one file to search.

```
$grep --color=auto -nH 'DIR' *
```

Sample output:

```
77.sh:16:# use find command to get all subdirs name in DIRS
77.sh:17:DIRS=$(find "$START" -type d)
77.sh:20:for d in $DIRS
83.sh:19: output="[DIR] $f/"
83.sh:41:[DIR] old/
83.sh:42:[DIR] test/
83.sh:47:[DIR] x/
83.sh:48:[DIR] y/
```

[3]

Fig.01: grep command displaying searched pattern

You can also use find command:

```
$ find . -name "*.c" -print | xargs grep "main("
```

### **Further readings:**

- find command [4]
- grep command [5]
- man pages find and grep

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our <u>daily email</u> newsletter or <u>weekly newsletter</u> to make sure you don't miss a single tip/tricks. Alternatively, subscribe via <u>RSS/XML</u> feed.

Article printed from Frequently Asked Questions About Linux / UNIX: http://www.cyberciti.biz/faq/

URL to article: http://www.cyberciti.biz/faq/unix-linux-finding-files-by-content/

URLs in this post:

- [1] Image: http://www.cyberciti.biz/faq/category/bash-shell/
- [2] grep command to find files by: http://www.cyberciti.biz/faq/howto-search-find-file-for-text-string/
- [3] Image: http://www.cyberciti.biz/faq/wp-content/uploads/2008/09/grep-command.png
- [4] find command: http://www.cyberciti.biz/faq/tag/find-command/
- [5] grep command: http://www.cyberciti.biz/faq/tag/grep-command/

Copyright © 2006-2010 <u>nixCraft</u>. All rights reserved. This print / pdf version is for personal non-commercial use only. More details <a href="http://www.cyberciti.biz/tips/copyright">http://www.cyberciti.biz/tips/copyright</a>.