Table Of Contents


Table Of Contents	1
Disable Apache SELinux Protection	2
GUI tool to disable SELinux for Apache	2

nixCraft: Linux Tips, Hacks, Tutorials, And Ideas In Blog Format http://www.cyberciti.biz/

Home > Faq > Apache

Disable SELinux for only Apache / httpd in Linux

Posted by Vivek Gite <vivek@nixcraft.com>





A. You can disable Apache SELinux protection easily. Please keep in mind that by disabling SELinux for apache you are inviting more security related problems.

Disable Apache SELinux Protection

Open /etc/selinux/targeted/booleans file using a text editor:

vi /etc/selinux/targeted/booleans

Append or modify value for httpd_disable_trans as follows:

httpd_disable_trans=1

Save and close the file. Type the following two commands:

- # setsebool httpd_disable_trans 1
- # /etc/init.d/httpd restart

GUI tool to disable SELinux for Apache

Open a shell prompt

Type the command system-config-securitylevel

```
system-config-securitylevel &
```

Next select SELinux tab > click on Disable SELinux protection for httpd daemon checkbox > Save the changes Finally restart httpd service:

/etc/init.d/httpd restart

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our <u>daily email</u> newsletter or <u>weekly newsletter</u> to make sure you don't miss a single tip/tricks. Alternatively, subscribe via <u>RSS/XML</u> feed.

Article printed from Frequently Asked Questions About Linux / UNIX: http://www.cyberciti.biz/faq/

URL to article: http://www.cyberciti.biz/faq/howto-disable-httpd-selinux-security-protection/

URLs in this post:

[1] Image: http://www.cyberciti.biz/faq/faq/category/apache/

Copyright © 2006-2010 <u>nixCraft</u>. All rights reserved. This print / pdf version is for personal non-commercial use only. More details http://www.cyberciti.biz/tips/copyright.