Table Of Contents	1,	/3

Table Of Contents

Fable Of Contents	. 1
Show only errors	. 2

Show only errors 2/3

nixCraft: Linux Tips, Hacks, Tutorials, And Ideas In Blog Format http://www.cyberciti.biz/

Home > Faq > CentOS

PHP: Stop Notice and Variable Warnings in Error Log Files

Posted by Vivek Gite <vivek@nixcraft.com>

Q. I'm using <u>error logging</u> [2] in place of error displaying on production web sites. However, I do not want to see error messages about the use of uninitialized variables. I'd like to see all critical errors, except for notices and coding standards warnings. How do I disable error messages?



A. PHP provides various levels of error reporting using a bit-field as follows:

Error Bit	Purpose
E_ALL	All errors and warnings (doesn't include E_STRICT)
E_ERROR	Fatal run-time errors
E_WARNING	Run-time warnings (non-fatal errors)
E_PARSE	Compile-time parse errors
E_NOTICE	Run-time notices (these are warnings which often result from a bug in your code, but it's possible that it was intentional (e.g., using an uninitialized variable and relying on the fact it's automatically initialized to an empty string)
E_STRICT	Run-time notices, enable to have PHP suggest changes to your code which will ensure the best interoperability and forward compatibility of your code.
E_CORE_ERROR	Fatal errors that occur during PHP's initial startup
E_CORE_WARNING	Warnings (non-fatal errors) that occur during PHP's initial startup
E_COMPILE_ERROR	Fatal compile-time errors
E_COMPILE_WARNING	Compile-time warnings (non-fatal errors)
E_USER_ERROR	User-generated error message
E_USER_WARNING	User-generated warning message
E_USER_NOTICE	User-generated notice message



[3]

Show only errors

Open /etc/php.ini file

vi /etc/php.ini

Set error_reporting as follows:

```
error_reporting = E_COMPILE_ERROR|E_ERROR|E_CORE_ERROR
```

Alternately, you can show all errors, except for notices and coding standards warnings

```
error_reporting = E_ALL & ~E_NOTICE
```

Save and close the file. Restart apache web server [4]:

/etc/init.d/httpd restart

Show only errors 3/3

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our <u>daily email</u> newsletter or <u>weekly newsletter</u> to make sure you don't miss a single tip/tricks. Alternatively, subscribe via <u>RSS/XML</u> feed.

Article printed from Frequently Asked Questions About Linux / UNIX: http://www.cyberciti.biz/faq/

URL to article: http://www.cyberciti.biz/faq/php-stop-notice-variable-warnings-errorlogs/

URLs in this post:

- [1] Image: http://www.cyberciti.biz/faq/category/php/
- [2] error logging: http://www.cyberciti.biz/tips/php-howto-turn-on-error-log-file.html
- [3] Image: http://www.cyberciti.biz/faq/category/unix/
- [4] Restart apache web server: http://www.cyberciti.biz/faq/star-stop-restart-apache2-webserver/

Copyright © 2006-2010 <u>nixCraft</u>. All rights reserved. This print / pdf version is for personal non-commercial use only. More details http://www.cyberciti.biz/tips/copyright.