Table Of Contents	1/2
Table Of Contents	
Table Of Contents	1

Table Of Contents 2/2

nixCraft: Linux Tips, Hacks, Tutorials, And Ideas In Blog Format http://www.cyberciti.biz/

Home > Faq > BASH Shell

-bash: enable: PrinterName: not a shell builtin Error and Solution

Posted by Vivek Gite <vivek@nixcraft.com>

Q. When I type the following command under CentOS 4.x / Fedora Linux:

enable hplj2

I see the error message:

-bash: enable: hplj2: not a shell builtin

How do I fix this error?

A. There are multiple versions of the enable command. One built in to the shell, and one in /usr/bin/enable. You need to use full path to /usr/bin/enable to avoid this error:



/usr/bin/enable hplj2

The following command print out list of internal and external command. It also indicates how it would be interpreted if used as a command name

```
$ type -a enable
```

Output:

enable is a shell builtin
enable is /usr/bin/enable

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our <u>daily email</u> newsletter or <u>weekly newsletter</u> to make sure you don't miss a single tip/tricks. Alternatively, subscribe via <u>RSS/XML</u> feed.

Article printed from Frequently Asked Questions About Linux / UNIX: http://www.cyberciti.biz/faq/

URL to article: http://www.cyberciti.biz/faq/rhel-fedora-centos-enable-not-shell-builtin/

URLs in this post:

[1] Image: http://www.cyberciti.biz/faq/faq/category/troubleshooting/

Copyright © 2006-2010 <u>nixCraft</u>. All rights reserved. This print / pdf version is for personal non-commercial use only. More details http://www.cyberciti.biz/tips/copyright.