Table Of Contents

Table Of Contents	1
nice syntax (/bin/nice command)	
Change niceness by 3	
Shell in build nice command syntax	

nixCraft: Linux Tips, Hacks, Tutorials, And Ideas In Blog Format http://www.cyberciti.biz/

Home > Faq > CentOS

Linux nice command: Run Process With Modified Scheduling Priority (nicenesses)

Posted by Vivek Gite <vivek@nixcraft.com>

Q. How do I run a process with modified scheduling priority under Linux? I'd like to change the priority in the kernel's scheduler while starting a command.

A. Use nice command to run a program with modified scheduling priority / nicenesses. Nicenesses range at least from -20 (resulting in the most favorable scheduling) through 19 (the least favorable). The default behavior is to increase the niceness by 10.



A niceness should not be confused with a scheduling priority, which lets applications determine the order in which threads are scheduled to run. Unlike a priority, a niceness is merely advice to the scheduler, which the scheduler is free to ignore.

nice syntax (/bin/nice command)

/bin/nice -n NUM

Add integer NUM (-20 to 19) to the niceness.



WARNING! There are multiple versions of the nice command. One built in to the shell, and one in /bin/nice.

The syntax may be diffrent on your system. Refer your shell and /bin/nice command man page for details.

Change niceness by 3

Type the command as follows:

\$ /bin/nice -n 3 command-name

Only a privileged user may run a process with lower niceness:

\$ /bin/nice -n -1 command-name

Shell in build nice command syntax

If you use the csh or tcsh or bash, the syntax is as follows:

nice +n command

I recommend using /bin/nice syntax to avoid confusion and to save time.

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our <u>daily email</u> newsletter or <u>weekly newsletter</u> to make sure you don't miss a single tip/tricks. Alternatively, subscribe via <u>RSS/XML</u> feed.

Article printed from Frequently Asked Questions About Linux / UNIX: http://www.cyberciti.biz/faq/

URL to article: http://www.cyberciti.biz/faq/change-the-nice-value-of-a-process/

URLs in this post:

[1] Image: http://www.cyberciti.biz/faq/faq/category/linux/

 $Copyright @ 2006-2010 ~ \underline{nixCraft}. ~ All ~ rights ~ reserved. ~ This ~ print / ~ pdf ~ version ~ is for personal ~ non-commercial ~ use ~ only. ~ More ~ details ~ \underline{http://www.cyberciti.biz/tips/copyright}.$