Table Of Contents

Table Of Contents	1
ns2.nixcraft.in Secondary NameServer Installation and Configuration	. 2
Create Directory For Your Zone File	
How Do I Replicate My DNS Data From ns1.nixcraft.in (first tinydns server)?	
Replicating Your DNS Data Using axfrDNS Program	
Replicating Your DNS Data (ns1.nixcraft.in) Using rsync or scp	3

nixCraft: Linux Tips, Hacks, Tutorials, And Ideas In Blog Format http://www.cyberciti.biz/

Home > Faq > DJBDNS

FreeBSD DJBDNS: Create Secondary TinyDNS Server

Posted by Vivek Gite <vivek@nixcraft.com>

This entry is part 6 of 6 in the series FreeBSD DJBDNS Server [1]

FreeBSD DJBDNS Server [1]

- FreeBSD Install D JBDNS Server [2]
- FreeBSD Configure DJBDNS TinyDNS Server [3]
- FreeBSD tinydns: Sets Up a DNS Publication / Authoritative Name Server [4]
- FreeBSD DJBDNS: Tinydns Create a Zone File For Domain [5]
- FreeBSD DJBDNS: Tinydns Add Additional Domain Names [6]
- FreeBSD DJBDNS: Create Secondary TinyDNS Server

How do I create a secondary djbdns dns name server to resolve names if primary went down?



You can easily create secondary dns server using djbdns. Type the following commands to install secondary DNS server on FreeBSD server itself (type all the following commands on ns2.nixcraft.in):



ns2.nixcraft.in Secondary NameServer Installation and Configuration

Install djbdns:

```
# portsnap fetch update
# cd /usr/ports/dns/djbdns
# make install clean && rehash
```

Create users and required directories:

```
# pw groupadd dnsusers
# pw useradd tinydns -s /bin/nologin -G dnsusers
# pw useradd dnslog -s /bin/nologin -G dnsusers
# pw useradd axfrdns -s /bin/nologin -G dnsusers
# mkdir /var/service/
# echo 'svscan_enable="YES"' >> /etc/rc.conf
# /usr/local/etc/rc.d/svscan.sh start
```

Create Directory For Your Zone File

You need to create /var/ns2.nixcraft.in/ as follows:

```
# mkdir /var/ns2.nixcraft.in
# tinydns-conf tinydns dnslog /var/ns2.nixcraft.in 203.51.2.1
# ln -s /var/ns2.nixcraft.in /var/service/
# sockstat -4 -p 53
```

Now, your secondary tinydns server is running.

How Do I Replicate My DNS Data From ns1.nixcraft.in (first tinydns server)?

You have two options here as follows:

Replicating Your DNS Data Using axfrDNS Program

axfrdns bind to TCP port # 53. It reads a zone-transfer request in DNS-over-TCP format from its standard input, and responds with locally configured information. This program is useful to talk with external dns servers such as BIND. Using tcp client one can request a zone-transfer request for secondary tinydns. It is also useful to answer queries on

TCP port # 53. Usually most client will use UDP port. See how to setup axfrdns on primary name server to accept a zone-transfer requests.

Replicating Your DNS Data (ns1.nixcraft.in) Using rsync or scp

You can just copy the generated data.cdb to the second tinydns name server using rsync or scp. This is preferred method when you just want to talk between your own two tindydns servers. Simply use scp command as follows to copy data.cdb from primary name server ns1.nixcraft.in:

```
# scp user@ns1.nixcraft.in:/var/ns1.nixcraft.in/root/data.cdb /var/ns2.nixcraft.in/root/
```

You can automate this procedure from ns1.nixcraft.in itself. Login to your primary name server and cd to /var/ns1.nixcraft.in/root

```
# cd /var/ns1.nixcraft.in/root
```

Open Makefile file, enter:

```
# vi Makefile
```

Update file as follows (to avoid password prompt setup <u>ssh-key based login between</u> ^[9] ns1.nixcraft.in and ns2.nixcraft.in):

```
remote: data.cdb
/usr/local/bin/rsync -az -e ssh data.cdb user@ns2.nixcraft.in:/var/ns1.nixcraft.in/root/dadata.cdb: data
/usr/local/bin/tinydns-data
```

Save and close the file. Finally, update Makefile on ns2.nixcraft.in as follows:

```
# cd /var/ns2.nixcraft.in/root
# vi Makefile
```

Append the following line protects data.cdb by stopping make:

```
# echo "foo" > Makefile
```

Series Navigation

«FreeBSD DJBDNS: Tinydns Add Additional Domain Names [6]

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our <u>daily email</u> newsletter or <u>weekly newsletter</u> to make sure you don't miss a single tip/tricks. Alternatively, subscribe via <u>RSS/XML</u> feed.

Article printed from Frequently Asked Questions About Linux / UNIX: http://www.cyberciti.biz/faq/

URL to article: http://www.cyberciti.biz/faq/freebsd-djbdns-create-secondary-tinydns-server/

URLs in this post:

- [1] FreeBSD DJBDNS Server: http://www.cyberciti.biz/faq/series/freebsd-djbdns-server/
- [2] FreeBSD Install DJBDNS Server: http://www.cyberciti.biz/faq/freebsd-install-djbdns-server/
- [3] FreeBSD Configure DJBDNS TinyDNS Server: http://www.cyberciti.biz/faq/freebsd-configure-djbdns-tinydns-server/
- [4] FreeBSD tinydns: Sets Up a DNS Publication / Authoritative Name Server: http://www.cyberciti.biz/faq/freenbsd-tinydns-sets-up-primary-dns-server/
- [5] FreeBSD DJBDNS: Tinydns Create a Zone File For Domain: http://www.cyberciti.biz/faq/freebsd-djbdns-tinydns-create-a-zone-file-for-domain/
- [6] FreeBSD DJBDNS: Tinydns Add Additional Domain Names: http://www.cyberciti.biz/faq/freebsd-djbdns-tinydns-add-additional-domain-names/

- [7] Image: http://www.cyberciti.biz/faq/category/djbdns/
- [8] Image: http://www.cyberciti.biz/faq/category/freebsd/
- [9] ssh-key based login between: http://www.cyberciti.biz/faq/ssh-password-less-login-with-dsa-publickey-authentication/

Copyright © 2006-2010 <u>nixCraft</u>. All rights reserved. This print / pdf version is for personal non-commercial use only. More details http://www.cyberciti.biz/tips/copyright.