# **Table Of Contents**

Table Of Contents	1
Procedure to change /etc/issue - pre login file	
/etc/issue - escape code	
See also	

nixCraft: Linux Tips, Hacks, Tutorials, And Ideas In Blog Format <a href="http://www.cyberciti.biz/">http://www.cyberciti.biz/</a>

Home > Faq > CentOS

### Linux display or change a pre-login message – /etc/issue file

Posted by Vivek Gite <vivek@nixcraft.com>

Q. How can I configure or change the Virtual Console login to display a pre-login message?

A. The file /etc/issue is a text file which contains a message or system identification to be printed before the login prompt. It may contain various @char and \char sequences, if supported by getty.



Just open file /etc/issue and change the text as per your requirements.

## Procedure to change /etc/issue - pre login file

Login as the root user. Open a file

```
# vi /etc/issue
```

#### Append new text as follows:

```
Welcome to nixCraft Labs! Today is \d \t @ \n
```

Save and close the file. d, t or m will expand as follows on run time.

### /etc/issue - escape code

The issue-file (/etc/issue or the file set with the -f option) may contain certain escape codes to display the system name, date and time etc. All escape codes consist of a backslash () immediately followed by one of the letters explained below.

- \b : Insert the baudrate of the current line.
- \d : Insert the current date.
- \s : Insert the system name, the name of the operating system.
- \I : Insert the name of the current tty line.
- \m : Insert the architecture identifier of the machine, eg. i486
- \n: Insert the nodename of the machine, also known as the hostname.
- \o : Insert the domainname of the machine.
- \r : Insert the release number of the OS, eq. 1.1.9.
- \t : Insert the current time.
- \u : Insert the number of current users logged in.
- \U : Insert the string "1 user" or " users" where is the number of current users logged in.
- \v : Insert the version of the OS, eg. the build-date etc.

#### See also

• Howto force sshd server to display login banner before login [2]

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our <u>daily email</u> newsletter or <u>weekly newsletter</u> to make sure you don't miss a single tip/tricks. Alternatively, subscribe via RSS/XML feed.

URL to article: http://www.cyberciti.biz/faq/howto-change-login-message/

URLs in this post:

[1] Image: http://www.cyberciti.biz/faq/faq/category/linux/

[2] Howto force sshd server to display login banner before login: http://www.cyberciti.biz/tips/change-openssh-sshd-server-login-banner.html

Copyright © 2006-2010 <u>nixCraft</u>. All rights reserved. This print / pdf version is for personal non-commercial use only. More details <a href="http://www.cyberciti.biz/tips/copyright">http://www.cyberciti.biz/tips/copyright</a>.