

Table Of Contents

Table Of Contents 1

HP-UX SSHD System Startup and Shutdown script: 2

System startup configuration file 2

Stop HP UX SSH Service 2

Start HP UX SSH Service 2

[Home](#) > [Faq](#) > [HP-UX Unix](#)

HP-UX start or stop / restart OpenSSH SSHD service

Posted by [Vivek Gite](#) <vivek@nixcraft.com>

Q. I've HP-UX installed on my HP UX UNIX server. But I'm not able to start or restart the OpenSSH ssh server. How do I stop or restart sshd under HP-UX?

A. HP-UX Secure Shell uses Pluggable Authentication Module for password authentication. Server configuration file is located at /opt/ssh/etc/sshd_config.

[1]

HP-UX SSHD System Startup and Shutdown script:

```
/sbin/init.d/secsh {start|stop}
```

System startup configuration file

```
/etc/rc.config.d/sshd
```

Stop HP UX SSH Service

Type the command:

```
# /sbin/init.d/secsh stop
```

Start HP UX SSH Service

Type the command:

```
# /sbin/init.d/secsh start
```

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our [daily email](#) newsletter or [weekly newsletter](#) to make sure you don't miss a single tip/tricks. Alternatively, subscribe via [RSS/XML](#) feed.

Article printed from Frequently Asked Questions About Linux / UNIX: <http://www.cyberciti.biz/faq/>

URL to article: <http://www.cyberciti.biz/faq/howto-hpux-sshd-service-startup-shutdown/>

URLs in this post:

[1] Image: <http://www.cyberciti.biz/faq/faq/category/unix/>