

Table Of Contents

Table Of Contents 1

List current settings 2

Gnome Disable automounting 2

[Home](#) > [Faq](#) > [CentOS](#)

Disable GNOME Automounting

Posted by [Vivek Gite](#) <vivek@nixcraft.com>

How do I disable automounting under Fedora Linux GNOME desktop?

The GNOME, runs the program gnome-volume-manager to mount devices and removable media (such as DVDs, CDs and USB flash drives) whenever they are inserted into the system.

Use gconftool-2 GNOME configuration tool to disable or enable settings related to GNOME desktop. Each preference in the GConf repository is expressed as a key-value pair. A GConf preference key is an element in the GConf repository that corresponds to an application preference. Preference keys typically have simple values such as strings, integers, or lists of strings and integers. [1]



List current settings

Type the following command:

```
$ gconftool-2 -R /desktop/gnome/volume_manager
```

Gnome Disable automounting

Type the following command:

```
$ gconftool-2 --direct --config-source xml:readwrite:/etc/gconf/gconf.xml.mandatory --  
type bool --set /desktop/gnome/volume_manager/automount_media false  
$ gconftool-2 --direct --config-source xml:readwrite:/etc/gconf/gconf.xml.mandatory --  
type bool --set /desktop/gnome/volume_manager/automount_drives false
```

The automount drives and automount media settings should be set to false to avoid automounting. Read gconftool-2 man page for further details:

```
$ man gconftool-2
```

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our [daily email](#) newsletter or [weekly newsletter](#) to make sure you don't miss a single tip/tricks. Alternatively, subscribe via [RSS/XML](#) feed.

Article printed from Frequently Asked Questions About Linux / UNIX: <http://www.cyberciti.biz/faq/>

URL to article: <http://www.cyberciti.biz/faq/disable-linux-unix-gnome-automounting/>

URLs in this post:

[1] Image: <http://www.cyberciti.biz/faq/category/gnome/>