

Table Of Contents

Table Of Contents .....	1
-------------------------	---

[Home](#) > [Faq](#) > [Apache](#)

## Apache: Make Changes In a Config File Take Effect Without Restarting Server

Posted by [Vivek Gite](#) <[vivek@nixcraft.com](mailto:vivek@nixcraft.com)>

**Q.** How do I make changes in a Apache server config file to take effect without restarting the Apache server itself w/o interrupting users' current session?

**A.** You can use httpd service or apachectl to reload configuration without interrupting users' sessions as follows:

Login as root and type the following command

```
# /etc/init.d/httpd reload
```

OR

```
# apachectl -k graceful
```

This is also known as gracefully restarting the Apache httpd daemon. If the daemon is not running, it is started. This differs from a normal restart in that currently open connections are not aborted. A side effect is that old log files will not be closed immediately. This means that if used in a log rotation script, a substantial delay may be necessary to ensure that the old log files are closed before processing them.

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our [daily email](#) newsletter or [weekly newsletter](#) to make sure you don't miss a single tip/tricks. Alternatively, subscribe via [RSS/XML](#) feed.


Article printed from Frequently Asked Questions About Linux / UNIX: <http://www.cyberciti.biz/faq/>

URL to article: <http://www.cyberciti.biz/faq/apache-making-changes-config-file-without-restarting/>

URLs in this post:

[1] Image: <http://www.cyberciti.biz/faq/category/apache/>

[2] Image: <http://www.cyberciti.biz/faq/category/unix/>



UNIX

[1]

[2]