Table Of Contents

able Of Contents	1
ask: Start httpd server:	
ask: Restart httpd server:	2
ask: Stop httpd server:	2
/etc/init.d/httpd script	
note about Debian / Ubuntu Linux	2

nixCraft: Linux Tips, Hacks, Tutorials, And Ideas In Blog Format http://www.cyberciti.biz/

Home > Faq > Apache

Restart Httpd Server

Posted by Vivek Gite <vivek@nixcraft.com>

Q. I'm using CentOS / RHEL / Fedora Linux server and I'd like to restart my httpd server after making some changes to httpd.conf file. How do I restart httpd?



A. You can use service command to restart httpd. Another option is use /etc/init.d/httpd service script.

Login as root user and type the following commands:

Task: Start httpd server:

```
# service httpd start
```

Task: Restart httpd server:

```
# service httpd restart
```

Task: Stop httpd server:

```
# service httpd stop
```

Please note that restart option is a shorthand way of stopping and then starting the Apache HTTPd Server. You need to restart server whenever you make changes to httpd.conf file. It is also good idea to check configuration error before typing restart option:

```
# httpd -t
# httpd -t -D DUMP_VHOSTS
```

Sample output:

```
Syntax OK
```

Now restart httpd server:

```
# service httpd restart
```

Where,

- -t : Run syntax check for config files
- -t -D DUMP_VHOSTS: Run syntax check for config files and show parsed settings only for vhost.

/etc/init.d/httpd script

You can also use following command:

```
# /etc/init.d/httpd restart
# /etc/init.d/httpd start
# /etc/init.d/httpd stop
```

A note about Debian / Ubuntu Linux

Type the following command under Debian / Ubuntu Linux:

Task: Start httpd server:

```
# /etc/init.d/apache2 restart
# /etc/init.d/apache2 stop
# /etc/init.d/apache2 start
```

You can also use <u>service command under Debian / Ubuntu Linux</u> [3]:

```
# service apache2 restart
# service apache2 stop
# service apache2 start
```

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our <u>daily email</u> newsletter or <u>weekly newsletter</u> to make sure you don't miss a single tip/tricks. Alternatively, subscribe via <u>RSS/XML</u> feed.

Article printed from Frequently Asked Questions About Linux / UNIX: http://www.cyberciti.biz/faq/

URL to article: http://www.cyberciti.biz/faq/restart-httpd/

URLs in this post:

- [1] Image: http://www.cyberciti.biz/faq/faq/category/redhat-and-friends/
- [2] Image: http://www.cyberciti.biz/faq/faq/category/apache/
- [3] service command under Debian / Ubuntu Linux: http://www.cyberciti.biz/tips/how-to-controlling-access-to-linux-services.html

Copyright © 2006-2010 <u>nixCraft</u>. All rights reserved. This print / pdf version is for personal non-commercial use only. More details http://www.cyberciti.biz/tips/copyright.