Table Of Contents

Table Of Contents	1
Using MS-DOS/Windows 9x boot disk	
Using Windows XP boot disk	
Using Linux	7
99.19 = 1.18/.	

nixCraft: Linux Tips, Hacks, Tutorials, And Ideas In Blog Format http://www.cyberciti.biz/

Home > Faq > Linux

How to uninstall GRUB

Posted by Vivek Gite <vivek@nixcraft.com>

Q. How do I uninstall GRUB? I need to uninstall everything before sending this hard disk to someone including GRUB. All I need to keep is windows XP.

A. GNU GRUB ("GRUB" for short) is a boot loader package from the GNU Project. GRUB is the reference implementation of the Multiboot Specification, which allows a user to have several different operating systems on their computer at once, and to choose which one to run when the computer starts.



You can overwrite MBR with standard dd command. You can also use old good MS-DOS fdisk command to overwrite MBR.

Using MS-DOS/Windows 9x boot disk

In order to remove the GRUB bootloader from a Linux and Windows XP machine, boot with a Windows 9x startup disk or CD and execute the MS-DOS command:

fdisk /mbr

Using Windows XP boot disk

Boot computer using Windows XP (Windows 2000) setup disc / CD / DVD . Next, type the following commands:

```
# fixmbr
# exit
```

Using Linux

You can also use dd command from Linux itself (it removes partition table):

```
# dd if=/dev/null of=/dev/sdX bs=512 count=1
```

Just remove MBR, without the partition table (see comment below):

```
\# dd if=/dev/null of=/dev/sdX bs=446 count=1
```

Replace /dev/hdX with your actual device name such as /dev/hda. Use fdisk -l command to find out device name:

```
# fdisk -1
```

Output:

```
Disk /dev/sda: 251.0 GB, 251000193024 bytes
255 heads, 63 sectors/track, 30515 cylinders
Units = cylinders of 16065 * 512 = 8225280 bytes
                               End
  Device Boot
                   Start
                                         Blocks
                                                 Id System
/dev/sda1
                                13
                                         104391
                                                 83
                      1
                                                     Linux
                              30384
                                      243955057+ 83 Linux
/dev/sda2
                      14
                                        1052257+ 82 Linux swap
/dev/sda3
                   30385
                              30515
```

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our <u>daily email</u> newsletter or <u>weekly newsletter</u> to make sure you don't miss a single tip/tricks. Alternatively, subscribe via <u>RSS/XML</u> feed.

Article printed from Frequently Asked Questions About Linux / UNIX: http://www.cyberciti.biz/faq/

URL to article: http://www.cyberciti.biz/faq/linux-how-to-uninstall-grub/

URLs in this post:

[1] Image: http://www.cyberciti.biz/faq/faq/category/windows/

Copyright © 2006-2010 <u>nixCraft</u>. All rights reserved. This print / pdf version is for personal non-commercial use only. More details http://www.cyberciti.biz/tips/copyright.