

Table Of Contents

Table Of Contents ..... 1

Find out if user exists in /etc/passwd file ..... 2

Find out if group exists in /etc/group file ..... 2

id command ..... 2

    Further readings: ..... 3

[Home](#) > [Faq](#) > [BASH Shell](#)

## UNIX / Linux Command To Check Existing Groups and Users

Posted by [Vivek Gite](#) <[vivek@nixcraft.com](mailto:vivek@nixcraft.com)>

[1]

**Q.** How do I check the existing Linux / UNIX users and groups under Linux operating system?

**A.** You can easily check the existing users and groups under Linux using the following commands.

### Find out if user exists in /etc/passwd file

[/etc/passwd file](#) stores essential information required during login. All you have to do is search this file for user name using following syntax:

```
$ egrep -i "^username" /etc/passwd
```

For, example find out if vivek user exists or not, enter:

```
$ egrep -i "^vivek" /etc/passwd
```

Sample output:

```
vivek:x:1000:1000:Vivek Gite,,,:/home/vivek:/bin/bash
```

A quick shell script code:

```
#!/bin/bash
# init
USERID="$1"
#....
/bin/egrep -i "^${USERID}" /etc/passwd
if [ $? -eq 0 ]; then
    echo "User $USERID exists in /etc/passwd"
else
    echo "User $USERID does not exists in /etc/passwd"
fi
# ....
```

Normally, **exit status is 0** returned if user accounts (lines) are found and 1 otherwise.

### Find out if group exists in /etc/group file

[/etc/group](#) <sup>[2]</sup> is a text file which defines the groups to which users belong under Linux and UNIX operating system. Again, you have to search /etc/group file using following syntax:

```
$ egrep -i "^groupname" /etc/group
```

For, example find out if vivek group exists or not, enter:

```
$ egrep -i "^vivek" /etc/group
```

### id command

id is another command to display user / group information for any USERNAME, or the current user. To find out more about user called, tom, enter:

```
$ id tom
```

**Sample output**

```
id: tom: No such user
```

To find out ftpuser group, enter:

```
$ id -g ftpuser
```

**Sample output:**

```
id: ftpuser: No such user
```

id command **exit status is 0** returned if user accounts (lines) are found and 1 otherwise. A sample shell script using id command:

```
#!/bin/bash
USERID="$1"
/bin/id $USERID 2>/dev/null
[ $? -eq 0 ] && echo "User found" || echo "User not found"

/bin/id -g $USERID 2>/dev/null
[ $? -eq 0 ] && echo "Group found" || echo "Group not found"
```

**Further readings:**

- Refer to id, passwd, group man pages

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our [daily email](#) newsletter or [weekly newsletter](#) to make sure you don't miss a single tip/tricks. Alternatively, subscribe via [RSS/XML](#) feed.

Article printed from Frequently Asked Questions About Linux / UNIX: <http://www.cyberciti.biz/faq/>

URL to article: <http://www.cyberciti.biz/faq/linux-check-existing-groups-users/>

URLs in this post:

[1] Image: <http://www.cyberciti.biz/faq/faq/category/linux/>

[2] /etc/group: <http://www.cyberciti.biz/faq/understanding-etcgroup-file/>

---

Copyright © 2006-2010 [nixCraft](#). All rights reserved. This print / pdf version is for personal non-commercial use only. More details <http://www.cyberciti.biz/tips/copyright>.