

Table Of Contents

Table Of Contents 1

General syntax for uninstalled foo.rpm file 2

General syntax for installed httpd package 2

[Home](#) > [Faq](#) > [BASH Shell](#)

View Installation / Uninstallation Script Inside The RPM File

Posted by [Vivek Gite](#) <vivek@nixcraft.com>

Q. How do I view the pre / post installation or uninstallation script inside the RPM file called foo.rpm under Red Hat Enterprise Linux / RHEL / CentOS / Fedora / Suse Linux? How do I list the package specific scriptlet(s) that are used as part of the installation and uninstallation processes?



[1]

A. To list the package specific scriptlet(s) that are used as part of the installation and uninstallation processes pass --scripts option to rpm command. You also need to specify the following options:

-q option : Query option

-p option : Query an (uninstalled) package PACKAGE_FILE. The PACKAGE_FILE may be specified as an ftp or http style URL, in which case the package header will be downloaded and queried).

General syntax for uninstalled foo.rpm file

```
$ rpm -qp --scripts foo.rpm
```

Find out Installation / Uninstallation scripts inside the rpm file called monit-4.9-2.el5.rf.x86_64.rpm:

```
$ rpm -qp --scripts monit-4.9-2.el5.rf.x86_64.rpm
```

Sample output:

```
warning: monit-4.9-2.el5.rf.x86_64.rpm: Header V3 DSA signature: NOKEY, key ID 6b8d79e6
preinstall scriptlet (using /bin/sh):
if ! /usr/bin/id monit &>/dev/null; then
    /usr/sbin/useradd -M -r -d /var/lib/monit -s /bin/sh -c "monit daemon" monit || \
        logger -t monit/rpm "Unexpected error adding user \"monit\". Aborting insta
fi
postinstall scriptlet (using /bin/sh):
/sbin/chkconfig --add monit
preuninstall scriptlet (using /bin/sh):
if [ $1 -eq 0 ]; then
    service monit stop &>/dev/null || :
    /sbin/chkconfig --del monit
fi
postuninstall scriptlet (using /bin/sh):
/sbin/service monit condrestart &>/dev/null || :
if [ $1 -eq 0 ]; then
    /usr/sbin/userdel monit || logger -t monit/rpm "User \"monit\" could not be deletec
fi
```

General syntax for installed httpd package

```
$ rpm -q --scripts httpd
```

Sample output:

```
preinstall scriptlet (using /bin/sh):
# Add the "apache" user
/usr/sbin/useradd -c "Apache" -u 48 \
    -s /sbin/nologin -r -d /var/www/apache 2> /dev/null || :
postinstall scriptlet (using /bin/sh):
```

```
# Register the httpd service
/sbin/chkconfig --add httpd
preuninstall scriptlet (using /bin/sh):
if [ $1 = 0 ]; then
    /sbin/service httpd stop > /dev/null 2>&1
    /sbin/chkconfig --del httpd
fi
```

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our [daily email](#) newsletter or [weekly newsletter](#) to make sure you don't miss a single tip/tricks. Alternatively, subscribe via [RSS/XML](#) feed.

Article printed from Frequently Asked Questions About Linux / UNIX: <http://www.cyberciti.biz/faq/>

URL to article: <http://www.cyberciti.biz/faq/rhel-list-package-specific-scriptlets/>

URLs in this post:

[1] Image: <http://www.cyberciti.biz/faq/faq/category/redhat-and-friends/>

Copyright © 2006-2010 [nixCraft](#). All rights reserved. This print / pdf version is for personal non-commercial use only. More details <http://www.cyberciti.biz/tips/copyright>.