

Table Of Contents


Table Of Contents 1

Freebsd Remount Command 2

[Home](#) > [Faq](#) > [File system](#)

How To FreeBSD Remount Partition

Posted by [Vivek Gite](#) <vivek@nixcraft.com>

Q. How do I remount partition under FreeBSD? How do I mount readonly partition as (remount) read write mode?  [1]

A. Linux or other Unixish oses need to pass **-o remount option** to mount command. However, FreeBSD does not require any special option to remount file system. It can use standard mount command. The mount utility calls the mount(2) system call to prepare and graft a special device or the remote node (rhost:path aka NFS) on to the file system tree at the point node. For example if your file system is mounted in read only mode then you can remount it using following command (log in as a root user):

Freebsd Remount Command

Type the following command as the root user (superuser):

```
# mount -o rw /dev/ad0s1a /
```

OR

```
# mount -o rw /
```

Where,

- -o : Takes different options as follows:
- rw : Read write
- ro : Read only

Make sure you replace /dev/ad0s1a and / with appropriate values.

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our [daily email](#) newsletter or [weekly newsletter](#) to make sure you don't miss a single tip/tricks. Alternatively, subscribe via [RSS/XML](#) feed.

Article printed from Frequently Asked Questions About Linux / UNIX: <http://www.cyberciti.biz/faq/>

URL to article: <http://www.cyberciti.biz/faq/howto-freebsd-remount-partition/>

URLs in this post:

[1] Image: <http://www.cyberciti.biz/faq/faq/category/freebsd/>