

Table Of Contents

Table Of Contents	1
-------------------------	---

[Home](#) > [Faq](#) > [AIX](#)

UNIX Delete / Remove Directory Command

Posted by [Vivek Gite](#) <vivek@nixcraft.com>

How do I delete / remove a directory under UNIX operating systems?

You need to use `rmdir` command to remove a directory. It will remove the directory entry specified by each `dirname` operand, which must refer to an empty directory.

For example, to remove a directory called "cppcode", enter:

[1]

```
rmdir cppcode
```

Note: A directory must be empty before it can be removed. Use `rm` command to remove all files from a directory:

```
cd cppcode
rm *.cpp
cd ..
rmdir cppcode
```

You can also recursively remove directories and subdirectories. The directory will be emptied of files and removed using `rm` command:

```
rm -r oldletters
```

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our [daily email](#) newsletter or [weekly newsletter](#) to make sure you don't miss a single tip/tricks. Alternatively, subscribe via [RSS/XML](#) feed.

Article printed from Frequently Asked Questions About Linux / UNIX: <http://www.cyberciti.biz/faq/>

URL to article: <http://www.cyberciti.biz/faq/delete-remove-a-directory-unix-command/>

URLs in this post:

[1] Image: <http://www.cyberciti.biz/faq/category/unix/>