

Table Of Contents

Table Of Contents	1
-------------------------	---

[Home](#) > [Faq](#) > [BASH Shell](#)

BASH Shell Redirect Output and Errors To /dev/null

Posted by [Vivek Gite](#) <vivek@nixcraft.com>

How do I redirect output and errors to /dev/null under bash / sh shell scripting? How do I redirect the output of stderr to stdout, and then redirect this combined output to /dev/null?

You can send output to /dev/null, by using **command >/dev/null** syntax. However, this will not work when command will use the standard error (FD # 2). So you need to modify >/dev/null as follows to redirect both output and errors to /dev/null:



[1]

```
$ command > /dev/null 2>&1
$ ./script.sh > /dev/null 2>&1
$ ./example.pl > /dev/null 2>&1
```

You can also use the same syntax for all your [cronjobs](#) ^[2] to avoid emails and output / error messages:

```
@hourly /scripts/backup/nas.backup >/dev/null 2>&1
```

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our [daily email](#) newsletter or [weekly newsletter](#) to make sure you don't miss a single tip/tricks. Alternatively, subscribe via [RSS/XML](#) feed.

Article printed from Frequently Asked Questions About Linux / UNIX: <http://www.cyberciti.biz/faq/>

URL to article: <http://www.cyberciti.biz/faq/how-to-redirect-output-and-errors-to-devnull/>

URLs in this post:

[1] Image: <http://www.cyberciti.biz/faq/category/bash-shell/>

[2] cronjobs: <http://www.cyberciti.biz/faq/how-do-i-add-jobs-to-cron-under-linux-or-unix-oses/>