

Table Of Contents

Table Of Contents ..... 1

Step # 1: Open sshd\_config file ..... 2

Step # 2: Add a user ..... 2

Step # 3: Restart sshd ..... 2

[Home](#) > [Faq](#) > [Debian / Ubuntu](#)

## Restrict certain users log onto a system via SSH server

Posted by [Vivek Gite](#) <[vivek@nixcraft.com](mailto:vivek@nixcraft.com)>

Q. How do I limit what users can log onto a my Linux server system via OpenSSH / SSHD server?

A. OpenSSH server allows to specify usernames for login. According to man page syntax is as follows::

**AllowUsers** **user1 user2**

AllowUsers keyword can be followed by a list of user name patterns, separated by spaces. If specified, login is allowed only for user names that match one of the patterns. \* and ? can be used as wildcards in the patterns. Only user names are valid; a numerical user ID is not recognized. By default, login is allowed for all users. If the pattern takes the form USER@HOST then USER and HOST are separately checked, restricting logins to particular users from particular hosts. [1]



### Step # 1: Open sshd\_config file

```
# vi /etc/ssh/sshd_config
```

### Step # 2: Add a user

Only allow user vivek to login by adding following line:

```
AllowUsers vivek
```

### Step # 3: Restart sshd

Save and close the file. In the above example, user vivek has already been created on the system. Now just restart sshd:

```
# /etc/init.d/sshd restart
```

You can also use -

[Linux PAM configuration that allows or deny login via the sshd server](#) [2]

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our [daily email](#) newsletter or [weekly newsletter](#) to make sure you don't miss a single tip/tricks. Alternatively, subscribe via [RSS/XML](#) feed.

Article printed from Frequently Asked Questions About Linux / UNIX: <http://www.cyberciti.biz/faq/>

URL to article: <http://www.cyberciti.biz/faq/howto-limit-what-users-can-log-onto-system-via-ssh/>

URLs in this post:

[1] Image: <http://www.cyberciti.biz/faq/faq/category/linux/>

[2] Linux PAM configuration that allows or deny login via the sshd server : <http://www.cyberciti.biz/faq/tips/linux-pam-configuration-that-allows-or-deny-login-via-the-sshd-server.html>

