

Table Of Contents

Table Of Contents 1

[Home](#) > [Faq](#) > [CentOS](#)


Block ip address of spammers with iptables under Linux

Posted by [Vivek Gite](#) <vivek@nixcraft.com>

Q. How do I block ip address of spammers with iptables based firewall under CentOS Linux 5?

A. You can simply block IP address of spammers by editing /etc/sysconfig/iptables file under:

- a) CentOS Linux
- b) Fedora Linux
- c) RHEL 4.x/5.x etc



[1]

Open file /etc/sysconfig/iptables:

```
# vi /etc/sysconfig/iptables
```

Append ip address of spammers as follows:

```
-A RH-Firewall-1-INPUT -s SPAMMER-IP -j DROP  
-A RH-Firewall-1-INPUT -s SPAMMER-SUBNET-BLOCK -j DROP
```

Save and close the file. Just restart the firewall:

```
# /etc/init.d/iptables restart
```

You can also create a small shell script [to block lots of IP address](#) [2] at a time.

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our [daily email](#) newsletter or [weekly newsletter](#) to make sure you don't miss a single tip/tricks. Alternatively, subscribe via [RSS/XML](#) feed.

Article printed from Frequently Asked Questions About Linux / UNIX: <http://www.cyberciti.biz/faq/>

URL to article: <http://www.cyberciti.biz/faq/howto-block-ipaddress-of-spammers-with-firewall/>

URLs in this post:

[1] Image: <http://www.cyberciti.biz/faq/faq/category/iptables/>

[2] to block lots of IP address: <http://www.cyberciti.biz/tips/howto-block-ipaddress-with-iptables-firewall.html>