# **Table Of Contents**

Table Of Contents	1
useradd command syntax	
Linux add a new user called rakhi	
Set account disable date	
Set default password expiry	4

nixCraft: Linux Tips, Hacks, Tutorials, And Ideas In Blog Format <a href="http://www.cyberciti.biz/">http://www.cyberciti.biz/</a>

Home > Faq > CentOS

#### **Linux Create User Account**

Posted by Vivek Gite <vivek@nixcraft.com>

Q. How do I create create a new Linux user account? How do update or modify default Linux new user information? Using the command prompt (shell) tools, how do I add a user to the system? What are command line options for adding a user?

A. To create a new user account under any Linux distribution use command called useradd. The system administrator is responsible for creating account. Login as root user (or use sudo command).



[1]

## useradd command syntax

useradd [options] {username}

Depending on command line options, the useradd command will update system files (<a href="letc/passwd"><u>letc/passwd</u><a href="letc/shadow"><u>letc/shadow</u></a> [3] file with password) and may also create the new user's home directory and copy initial files.

### Linux add a new user called rakhi

Type the command as follows:

```
useradd rakhi
```

Set a password for rakhi:

```
passwd rakhi
```

Without password user account will be in locked status. To unlock the account, you need to use above passwd command. Use passwd command to assign a password and set password aging guidelines.

#### Set account disable date

You can set date for the account to be disabled in the format YYYY-MM-DD with -e option while creating account itself:

```
useradd -e {yyyy-mm-dd} {username}
useradd -e 2008-12-31 jerry
```

## Set default password expiry

The -f {days} option set number of days after the password expires until the account is disabled. (If 0 is specified, the account is disabled immediately after the password expires. If -1 is specified, the account is not be disabled after the password expires.)

```
useradd -f {days} {username}
useradd -e 2009-12-31 -f 30 jerry
```

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our <u>daily email</u> newsletter or <u>weekly newsletter</u> to make sure you don't miss a single tip/tricks. Alternatively, subscribe via <u>RSS/XML</u> feed.

URL to article: http://www.cyberciti.biz/faq/howto-add-new-linux-user-account/

URLs in this post:

[1] Image: http://www.cyberciti.biz/faq/faq/category/linux/

 $\hbox{\cite{thm://www.cyberciti.biz/faq/understanding-etcpasswd-file-format/}} \label{thm://www.cyberciti.biz/faq/understanding-etcpasswd-file-format/} \label{thm://www.cyberciti.biz/faq/understanding-etcpasswd-file-format/$ 

[3] /etc/shadow: http://www.cyberciti.biz/faq/understanding-etcshadow-file/

Copyright © 2006-2010 <u>nixCraft</u>. All rights reserved. This print / pdf version is for personal non-commercial use only. More details <a href="http://www.cyberciti.biz/tips/copyright">http://www.cyberciti.biz/tips/copyright</a>.