

Table Of Contents

| | |
|-------------------------|---|
| Table Of Contents | 1 |
|-------------------------|---|

[Home](#) > [Faq](#) > [FreeBSD](#)

FreeBSD Jail Add Multiple IPv4 / IPv6 Address

Posted by [Vivek Gite](#) <vivek@nixcraft.com>



How do I add multiple IPv4 / Ipv6 inside jail?

FreeBSD does support Multi-IPv4/v6/no-IP jail and it was merged to STABLE release. You need to rebuild your kernel including jls(8) and to use the new features jail(8), jexec(8) and cpuset(1) with a new kernel. Another option is get FreeBSD 7.2 (RC1 or above) using [cvsup](#) ^[2], just do make buildworld. Here is what you need to put in /etc/rc.conf file for Multi-IPv4/v6/no-IP jail configuration for httpd jail (note there are 3 ips defined):

```
jail_enable="YES"
jail_list="httpd"
jail_httpd_rootdir="/iscsi/httpd"      # jail's root directory
jail_httpd_hostname="web01.cyberciti.com" # jail's hostname
jail_httpd_ip="10.24.55.106,74.86.48.99,2607:f0d0:1002:11::4" # jail's multi IPs address
jail_smtpd_devfs_enable="YES"          # mount devfs in the jail
jail_smtpd_devfs_ruleset="devfsrules_jail" # devfs ruleset to apply to jail
```

Save and close the file. Restart jail service:

```
# /etc/rc.d/jail restart
```

To verify multiple IP, enter:

```
# jls -v
```

Sample output:

| JID | Hostname Name | Path State |
|-----|----------------------|-----------------------|
| | CPUSetID | |
| | IP Address(es) | |
| 2 | web01.cyberciti.com | /iscsi/httpd ALIVE |
| 2 | 10.24.55.106 | |
| | 74.86.48.99 | |
| | 2607:f0d0:1002:11::4 | |

From the man page:

jail_httpd_ip is used to set to the primary IPv4 and/or IPv6 addresses assigned to the jail. The argument can be a sole address or a comma separated list of addresses. Additionally each address can be prefixed by the name of an interface followed by a pipe to overwrite jail__interface or jail_interface and/or suffixed by a netmask, prefixlen or prefix. In case no netmask, prefixlen or prefix is given, /32 will be used for IPv4 and /128 will be used for an IPv6 address. If no address is given for the jail then the jail will be started with no networking support.

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our [daily email](#) newsletter or [weekly newsletter](#) to make sure you don't miss a single tip/tricks. Alternatively, subscribe via [RSS/XML](#) feed.

URL to article: <http://www.cyberciti.biz/faq/freebsd-jail-add-multiple-ipv4-ipv6-address/>

URLs in this post:

[1] Image: <http://www.cyberciti.biz/faq/category/freebsd/>

[2] cvsup: <http://www.cyberciti.biz/faq/freebsd-cvsup-update-system-applications/>

Copyright © 2006-2010 [nixCraft](http://www.cyberciti.biz/tips/copyright). All rights reserved. This print / pdf version is for personal non-commercial use only. More details <http://www.cyberciti.biz/tips/copyright>.