Table Of Contents	1/2
Table Of Contents	
Table Of Contents	1

Table Of Contents 2/2

nixCraft: Linux Tips, Hacks, Tutorials, And Ideas In Blog Format http://www.cyberciti.biz/

Home > Faq > Linux

Fedora Core Linux chkconfig does not display service name

Posted by Vivek Gite <vivek@nixcraft.com>

Q. I have server / service is installed but it does not show up in the chkconfig --list output. I need to use full path /etc/init.d/service start. I am using Fedora Core Linux and Cent OS (RHEL based) distos.

How do I solve this problem?

A. Use --add option to add the service to chkconfig database. For example:

```
# chkconfig --add lighttpd
```

Where,

• lighttpd: Service name.

Now see the list with the following command:

```
# chkconfig --list | less
```

To turn on service at boot time:

chkconfig lighttpd on

To turn off service at boot time:

```
# chkconfig lighttpd off
```

Read man page of chkconfig for more information.

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our <u>daily email</u> newsletter or <u>weekly newsletter</u> to make sure you don't miss a single tip/tricks. Alternatively, subscribe via <u>RSS/XML</u> feed.

Article printed from Frequently Asked Questions About Linux / UNIX: http://www.cyberciti.biz/faq/

URL to article: http://www.cyberciti.biz/faq/fedora-core-linux-chkconfig-does-not-display-service-name/

Copyright © 2006-2010 <u>nixCraft</u>. All rights reserved. This print / pdf version is for personal non-commercial use only. More details http://www.cyberciti.biz/tips/copyright.