Table Of Contents 1/2

Table Of Contents

Table Of Contents	1
Task: Use chage command to force users to chage their password upon first login	2
Further readings:	

nixCraft: Linux Tips, Hacks, Tutorials, And Ideas In Blog Format http://www.cyberciti.biz/

Home > Faq > CentOS

Linux: Force Users To Change Their Passwords Upon First Login

Posted by Vivek Gite <vivek@nixcraft.com>

Q. How can I force my Linux users to change their passwords upon the first login under CentOS / Debian Linux?

A. You can use any one of the following command to change user passwords upon the first login:

[a] **usermod command** - Modify various user account properties including user password expiry information.

Where,

[b] chage command - Change user password expiry information



[1]

Task: Use chage command to force users to chage their password upon first login

Use the following syntax:

```
chage -d 0 {user-name}
# chage -d 0 tom
```

• -d 0: Set the number of days since January 1st, 1970 when the password was last changed. The date may also be expressed in the format YYYY-MM-DD. By setting it to zero, you are going to force user to change password upon first login.

Further readings:

• man pages usermod and chage

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our <u>daily email</u> newsletter or <u>weekly newsletter</u> to make sure you don't miss a single tip/tricks. Alternatively, subscribe via <u>RSS/XML</u> feed.

Article printed from Frequently Asked Questions About Linux / UNIX: http://www.cyberciti.biz/faq/

URL to article: http://www.cyberciti.biz/faq/rhel-debian-force-users-to-change-passwords/

URLs in this post:

[1] Image: http://www.cyberciti.biz/faq/category/linux/

Copyright © 2006-2010 <u>nixCraft</u>. All rights reserved. This print / pdf version is for personal non-commercial use only. More details http://www.cyberciti.biz/tips/copyright.