

Table Of Contents

Table Of Contents	1
-------------------------	---

[Home](#) > [Faq](#) > [CentOS](#)

Postfix mail for domain.com loops back to myself Error and Solution

Posted by [Vivek Gite](#) <vivek@nixcraft.com>

I can send and receive mail using user@example.com, but system generated emails such as root@mail.example.com bounce backup with an error:

```
May 1 03:14:52 mail postfix/smtp[62798]: 23CA4BD6B40: to=, relay=none,
delay=0.01, delays=0/0/0/0, dsn=5.4.6, status=bounced (mail for mail.example.com
loops back to myself)
```



[1]

How do I fix this error?

Postfix did found a dns reply to your email server, but it hasn't been configured to deal with address such as root@mail.example.com. In other words, your server is configured to accept user@example.com but not as user@mail.example.com. This is well known config problem with virtual domain. To fix this error either add system FQDN to mydestination or relay_domains. Postfix accepts mail for domain listed in virtual_mailbox_domains, virtual_alias_domains, and domains that resolve to IP addresses listed in inet_interfaces and proxy_interfaces. Update mydestination using postconf or by editing main.cf file:

```
mydestination = localhost.$mydomain, localhost, mail.example.com
```

Once done reload postfix:

```
# service postfix reload
```

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our [daily email](#) newsletter or [weekly newsletter](#) to make sure you don't miss a single tip/tricks. Alternatively, subscribe via [RSS/XML](#) feed.

Article printed from Frequently Asked Questions About Linux / UNIX: <http://www.cyberciti.biz/faq/>

URL to article: <http://www.cyberciti.biz/faq/postfix-mail-for-domaincom-loops-back-to-myself-error-and-solution/>

URLs in this post:

[1] Image: <http://www.cyberciti.biz/faq/category/email-servers/>