

Table Of Contents

Table Of Contents .....	1
-------------------------	---

[Home](#) > [Faq](#) > [Linux](#)

## Allow root account to use SSH (openssh)

Posted by [Vivek Gite](#) <[vivek@nixcraft.com](mailto:vivek@nixcraft.com)>



[1]

Q. Previous admin blocked root access to ssh server. How do I allow root account access to ssh server?

A. Allowing direct [root access](#) <sup>[2]</sup> over ssh is a security risk. However following steps will allow you to login as root over ssh session:

Open sshd\_config file:

```
# vi /etc/ssh/sshd_config
```

Find out line that read as follows:

**PermitRootLogin no**

Set it as follows:

**PermitRootLogin yes**

Find out line that read as follows (this line may not exists in your configuration):

```
DenyUsers root user2 user3
```

Set is as follows:

```
DenyUsers user2 user3
```

Save and close the file. Restart the sshd:

```
# /etc/init.d/ssh restart
```

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our [daily email](#) newsletter or [weekly newsletter](#) to make sure you don't miss a single tip/tricks. Alternatively, subscribe via [RSS/XML](#) feed.

Article printed from Frequently Asked Questions About Linux / UNIX: <http://www.cyberciti.biz/faq/>

URL to article: <http://www.cyberciti.biz/faq/allow-root-account-to-use-ssh-openssh/>

URLs in this post:

[1] Image: <http://www.cyberciti.biz/faq/faq/category/linux/>

[2] root access: <http://www.cyberciti.biz/tips/openssh-deny-or-restrict-access-to-users-and-groups.html>