

**ORACLE APPLICATION SERVER FORMS LOG FILES
&
CONFIGURATION FILE LOCATIONS :**

PARAMETER	LOCATION	DESCRIPTION
formsweb.cfg	\$OH[MID]/forms/server	formsweb.cfg defines parameter values used by the FormsServlet (frmservlet)
ftrace.cfg	\$OH[MID]/forms/server	This file enables to configure forms trace which file types of information to gather when a trace is initiated.
default.env	\$OH[MID]/forms/server	It is a Default forms environment file for forms runtime.
basejini.htm	\$OH[MID]/forms/server	This is the default base HTML file for running a form on the web using JInitiator-style tags to include the Forms applet.
basejpi.htm	\$OH[MID]/forms/server	The base html files are used as templates by the forms servlet when generating the html page used to start up a forms application.
console2add.xml	\$OH[MID]/forms/server	
forms.conf	\$OH[MID]/forms/server	The forms.conf file is a oracle HTTP listener configuration file for oracle application server forms services.
base.htm	\$OH[MID]/forms/server	The base html files are used as templates by the forms servlet

		when generating the html page used to start up a forms application.
formsapp.ear	\$OH[MID]/forms/j2ee	By default Forms Services is configured for OC4J by deploying it as a J2EE compliant application packaged in an EAR (Enterprise Archive) file called formsapp.ear. This EAR file is deployed during the Oracle Application Server installation process (if you choose to configure Oracle Forms). During deployment, the EAR file is unpacked into the applications directory of the OC4J instance.
<i>PARAMETER</i>	<i>LOCATION</i>	<i>DESCRIPTION</i>
<i>formsoc4j.properties</i>	\$OH[MID]/forms/j2ee	<i>This file contains the location of formsweb.cfg file path</i>
orion-web.xml	\$OH[MID]/forms/j2ee	Forms web deployment file for OC4J for use with iDS; Define virtual paths.
Registry.dat	\$OH[MID]/forms/java/oracle/forms/registry	This file allows you to change the default font, font mappings, and icons that Forms Services uses.

Forms Trace File Location.	\$OH[MID]/forms/trace	Forms Trace File Location.
<i>PARAMETER</i>	<i>LOCATION</i>	<i>DESCRIPTION</i>
orion-application.xml	\$OH[MID]/j2ee/<Deployed_Instance_name>application-deployments/deploymentName/orion-application.xml	This contains <i>OC4J-specific</i> global application information for all applications.
principals.xml	\$OH[MID]/j2ee/<INSTANCE_NAME>/config	This xml file contains information regarding users,groups and permission.
Application.log	\$OH[MID]/j2ee/OC4J_BI_Forms/application-deployments/formsapp/OC4J_BI_Forms_default_island_1	The log file where OC4J_BI_FORM Application writes.
_pages	\$OH[MID]/j2ee/OC4J_BI_Forms/application-deployments/formsapp/formsweb/persistence	
_TldCache	\$OH[MID]/j2ee/OC4J_BI_Forms/application-deployments/formsapp/formsweb/persistence	
application.xml	\$OH[INFRA]/j2ee/home/config \$OH[MID]/j2ee/<INSTANCE_NAME>/config	This is the global application configuration file, which contains the common settings for all applications in an OC4J instance,Location of the log files
default-web-site.xml	\$OH[INFRA]/j2ee/home/config	The location of the root context.
jazn-data.xml	\$OH[MID]/j2ee/<Application_name>	The file defines the realm,

	me>/config \$OH[INFRA]/j2ee/home/config	users and the roles for users.
server.xml	\$OH[INFRA]/j2ee/home/config	The Path of the application ear file.
<i>PARAMETER</i>	<i>LOCATION</i>	<i>DESCRIPTION</i>
data-sources.xml	\$OH[INFRA]/j2ee/home/config	Data Source connection information
oc4j-connectors.xml	\$OH[INFRA]/j2ee/home/config \$OH[MID]/j2ee/<INSTANCE_NAME>/config	This contains information about global connector configuration
orion-ejb-jar.xml	\$OH[MID]/j2ee/Hr_Apps/application-deployments/HrApps/hrejb.jar	file contains the deploy-time info for an application