

Table Of Contents

Table Of Contents 1

Task: Turn on Samba Client Service 2

Task: Mount a Share 2

[Home](#) > [Faq](#) > [Hardware](#)

Solaris / OpenSolaris Mount Windows Shared (CIFS)

Posted by [Vivek Gite](#) <vivek@nixcraft.com>

How do I mount a CIFS Windows share under Solaris / OpenSolaris UNIX operating systems?

Simply use the following commands to mount a CIFS share.



Task: Turn on Samba Client Service

```
svcadm enable network/smb/client
```

Task: Mount a Share

Type the following command to mount a CIFS shared called data from server called fileserver on the /data:

```
# mkdir /data
# mount -F smbfs //fileserver/sales /sales
# ls -l /sales
# cp /sales/copy/file /to/dest
# df
```

To view all available sharename, enter:

```
smbutil view //fileserver
smbutil view //windows2003
```

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our [daily email](#) newsletter or [weekly newsletter](#) to make sure you don't miss a single tip/tricks. Alternatively, subscribe via [RSS/XML](#) feed.

Article printed from Frequently Asked Questions About Linux / UNIX: <http://www.cyberciti.biz/faq/>

URL to article: <http://www.cyberciti.biz/faq/solaris-opensolaris-mount-windows-shared-cifs/>

URLs in this post:

[1] Image: <http://www.cyberciti.biz/faq/category/solaris-unix/>