

Table Of Contents

Table Of Contents 1

rmdir command syntax 2

Delete / remove directory 2

Remove DIRECTORY and its ancestors 2

Recursive delete 2

[Home](#) > [Faq](#) > [Linux](#) > [Commands](#)

Linux Delete Directory With rmdir Command

Posted by [Vivek Gite](#) <vivek@nixcraft.com>

I'm new to Linux and I'd like to know how to delete directory under any Linux distributions?

You need to use the command called rmdir. It remove empty directories.



[1]

rmdir command syntax

```
rmdir [OPTION] {directory-name}
```

Delete / remove directory

To delete directory called foo, enter:

```
rmdir foo
```

Remove DIRECTORY and its ancestors

For example remove directory structure sales/99/march

```
rmdir -p sales/99/march
```

Recursive delete

Remove all directories and subdirectories, use rm command with -r option:

```
rm -rf /home/data/2000
```

Please note that rmdir command works with all Linux and Unix like operating systems. For more information read rm and rmdir command man pages:

```
man rm  
man rmdir
```

4000+ howtos and counting! Want to read more Linux / UNIX howtos, tips and tricks? Subscribe to our [daily email](#) newsletter or [weekly newsletter](#) to make sure you don't miss a single tip/tricks. Alternatively, subscribe via [RSS/XML](#) feed.

Article printed from Frequently Asked Questions About Linux / UNIX: <http://www.cyberciti.biz/faq/>

URL to article: <http://www.cyberciti.biz/faq/linux-unix-remove-directory/>

URLs in this post:

[1] Image: <http://www.cyberciti.biz/faq/category/linux/>

