

Outputs:

```
dua_ansari@DESKTOP-4DF8P X + v
attack: OK (1.0s)
(Old xv6.out.attack failure log removed)
== Test time ==
time: OK
Score: 45/45
dua_ansari@DESKTOP-4DF8P8:~/xv6-labs-2025$ make qemu
mv -f fs.img fs.img.bk
mkfs/mkfs fs.img README user/exec.sh user/_cat user/_echo user/_forktest user/_grep user/_init user/_kill user/_ln user/_ls user/_mkdir user/_rm use
r/_sh user/_stressfs user/_usertests user/_grind user/_wc user/_zombie user/_logstress user/_forphan user/_dorphan user/_sandbox user/_attack user/
_attack user/_secret
nmeta 47 (boot, super, log blocks 31, inode blocks 13, bitmap blocks 1) blocks 1953 total 2000
ballocc: first 1066 blocks have been allocated
ballocc: write bitmap block at sector 46
qemu-system-riscv64 -machine virt -bios none -kernel kernel/kernel -m 128M -smp 3 -nographic -global virtio-mmio.force-legacy=false -drive file=fs.i
mg,if=none,format=raw,id=x0 -device virtio-blk-device,drive=x0,bus=virtio-mmio-bus.0

xv6 kernel is booting

hart 2 starting
hart 1 starting
init: starting sh
$ sandbox 32768 - cat README
sandbox: blocked syscall 15 for process cat
cat: cannot open README
$ sandbox 32768 README grep xv6 README
xv6 is a re-implementation of Dennis Ritchie's and Ken Thompson's Unix
Version 6 (v6). xv6 loosely follows the structure and style of v6,
xv6 is inspired by John Lions's Commentary on UNIX 6th Edition (Peer
(Kaashoek,rtm@mit.edu). The main purpose of xv6 is as a teaching
```

Test Cases

```
dua_ansari@DESKTOP-4DF8P X + v
riscv64-unknown-elf-ld -z max-page-size=4096 -T kernel/kernel.ld -o kernel/kernel kernel/entry.o kernel/kalloc.o kernel/string.o kernel/main.o kerne
l/_vm.o kernel/proc.o kernel/switch.o kernel/trampoline.o kernel/trap.o kernel/syscall.o kernel/sysproc.o kernel/bio.o kernel/fs.o kernel/log.o kernel
/sleeplock.o kernel/file.o kernel/pipe.o kernel/exec.o kernel/sysfile.o kernel/kernelvec.o kernel/plic.o kernel/virtio_disk.o kernel/start.o kernel/
console.o kernel/printf.o kernel/uart.o kernel/spinlock.o
riscv64-unknown-elf-ld: warning: kernel/kernel has a LOAD segment with RWX permissions
riscv64-unknown-elf-objdump -S kernel/kernel > kernel/kernel.asm
riscv64-unknown-elf-objdump -t kernel/kernel | sed '1,/SYMBOL TABLE/d; s/ /./ /; /'$/d' > kernel/kernel.sym
make[1]: Leaving directory '/home/dua_ansari/xv6-labs-2025'
== Test answers-syscall.txt ==
answers-syscall.txt: OK
== Test sandbox_mask ==
$ make qemu-gdb
sandbox_mask: OK (6.4s)
== Test sandbox_fork ==
$ make qemu-gdb
sandbox_fork: OK (0.6s)
== Test sandbox_path ==
$ make qemu-gdb
sandbox_path: OK (1.3s)
== Test sandbox_most ==
$ make qemu-gdb
sandbox_most: OK (0.7s)
== Test sandbox_minus ==
$ make qemu-gdb
sandbox_minus: OK (0.8s)
== Test attack ==
$ make qemu-gdb
attack: OK (0.6s)
(Old xv6.out.attack failure log removed)
== Test time ==
time: OK
Score: 45/45
dua_ansari@DESKTOP-4DF8P8:~/xv6-labs-2025$ |
```