

Algorithms

Algorithms by Yu Dongfeng
First version on April 12, 2013
Latest version on February 14, 2016

Contents

1	Computational Geometry	3
1.1	Convex Hull	4
1.2	Delaunay Triangulation	5
1.3	Dynamic Convex Hull (Set)	9
1.4	Dynamic Convex Hull (Treap)	11
1.5	Geometry 2D	19
1.6	Half-Plane Intersection	23
2	Data Structures	27
2.1	Binary Heap	28
2.2	Dynamic Sequence	30
2.3	Fenwick Tree	34
2.4	K-D Tree	35
2.5	Link-Cut Tree	37
2.6	Pairing Heap	43
2.7	Red-Black Tree	45
2.8	Self-Adjusting Top Tree	53
2.9	Skew Heap	64
3	Graph Algorithms	67
3.1	Chordality Test	68
3.2	Dominator Tree	69
3.3	K Shortest Path	71
3.4	Maximal Clique Count	77

3.5	Maximal Planarity Test	78
3.6	Maximum Flow	82
3.7	Maximum Matching	84
3.8	Minimum Cost Maximum Flow	87
3.9	Minimum Spanning Arborescence	90
3.10	Minimum Spanning Tree	91
3.11	Shortest Path	93
3.12	Steiner Tree	94
3.13	Virtual Tree	95
4	Number Theory	99
4.1	Discrete Logarithm	100
4.2	Integer Factorization (Pollard's Rho Algorithm)	102
4.3	Integer Factorization (Shanks' Square Forms Factorization)	104
4.4	Modular Integer	108
4.5	Möbius Function	111
4.6	Primality Test	111
4.7	Prime Number	113
4.8	Primitive Root	114
4.9	Sequence	117
5	Numerical Algorithms	119
5.1	Convolution (Fast Fourier Transform)	120
5.2	Convolution (Karatsuba Algorithm)	121
5.3	Convolution (Number Theoretic Transform)	122
5.4	Fraction	123
5.5	Integer	126
5.6	Linear Programming	133
5.7	Linear System	135
5.8	Matrix	137
5.9	Polynomial Interpolation	138
6	String Algorithms	141
6.1	Aho-Corasick Automaton	142
6.2	Factor Oracle	143
6.3	Longest Common Substring	144
6.4	Palindromic Tree	145
6.5	String Matching	146
6.6	Suffix Array (DC3 Algorithm)	148
6.7	Suffix Array (Factor Oracle)	151
6.8	Suffix Array (Prefix-Doubling Algorithm)	155
6.9	Suffix Array (Suffix Tree)	156

6.10	Suffix Array (Treap)	159
6.11	Suffix Automaton	163
6.12	Suffix Tree	165
7	Utility Tools	169
7.1	Checker	170
7.2	Date	170
7.3	Fast Reader	174
7.4	Fast Writer	175
7.5	Number Speller	177

CHAPTER 1

Computational Geometry

1.1 Convex Hull

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Convex Hull.hpp (1063 bytes, 36 lines)

```

1  #include<bits/stdc++.h>
   using namespace std;
   template<class T>struct ConvexHull{
       struct point{
           T x,y;
           point(T _x,T _y):
               x(_x),y(_y){
           }
           point operator-(point a){
               return point(x-a.x,y-a.y);
11      }
           T operator*(point a){
               return x*a.y-y*a.x;
           }
           int operator<(point a){
               return x==a.x?y<a.y:x<a.x;
           }
       };
       static int check(point a,point b,point c){
           return (a-c)*(b-c)<=0;
21      }
       static vector<vector<point> >run(vector<point>a){
           sort(a.begin(),a.end());
           vector<point>u,d;
           for(int i=0;i<a.size();u.push_back(a[i++]))
               while(u.size()>1&&check(a[i],u.back(),u[u.size()-2]))
                   u.pop_back();
           for(int i=int(a.size()-1);i>=0;d.push_back(a[i--]))
               while(d.size()>1&&check(a[i],d.back(),d[d.size()-2]))
                   d.pop_back();
31      vector<vector<point> >r;
           r.push_back(u);
           r.push_back(d);
           return r;
       }
   }

```



```
};
```

1.2 Delaunay Triangulation

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Delaunay Triangulation.hpp (4889 bytes, 159 lines)

```
#include<bits/stdc++.h>
using namespace std;
template<class T>struct DelaunayTriangulation{
4   const static double E;
    struct poi{
        T x,y;
        poi(T _x=0,T _y=0):
            x(_x),y(_y){
        }
        poi operator-(poi b){
            return poi(x-b.x,y-b.y);
        }
        int operator<(poi b)const{
14         if(fabs(x-b.x)<E)
            return y<b.y;
            return x<b.x;
        }
    };
    int n;
    vector<pair<poi,int> >pts;
    vector<vector<int> >egs;
    T det(poi a,poi b){
        return a.x*b.y-a.y*b.x;
24    }
    T dot(poi a,poi b){
        return a.x*b.x+a.y*b.y;
    }
    int dir(poi a,poi b,poi c){
        T r=det(c-a,b-a);
        if(r<-E)
            return -1;
        return r>E?1:0;
    }
};
```

```

    }
34  int inc(poi a,poi b,poi c,poi d){
        a=a-d;
        b=b-d;
        c=c-d;
        T az=a.x*a.x+a.y*a.y,bz=b.x*b.x+b.y*b.y,cz=c.x*c.x+c.y*c.y;
        return a.x*b.y*cz+b.x*c.y*az+c.x*a.y*bz-a.x*bz*c.y-b.x*a.y*cz-c.x*
b.y*az>E;
    }
    int crs(poi a,poi b,poi c,poi d){
        return dir(a,b,c)*dir(a,b,d)==-1&&dir(c,d,a)*dir(c,d,b)==-1;
    }
44  DelaunayTriangulation():
        n(0),pts(1){
    }
    void add(T x,T y){
        poi a;
        a.x=x;
        a.y=y;
        pts.push_back(make_pair(a,++n));
    }
    poi&pot(int a){
54     return pts[a].first;
    }
    void con(int a,int b){
        egs[a].push_back(b);
        egs[b].push_back(a);
    }
    void dco(int a,int b){
        egs[a].erase(find(egs[a].begin(),egs[a].end(),b));
        egs[b].erase(find(egs[b].begin(),egs[b].end(),a));
    }
64  void dnc(int l,int r){
        if(r==1)
            return;
        if(r==l+1){
            con(l,r);
            return;
        }
        if(r==l+2){
            if(dir(pot(l),pot(l+1),pot(r)))

```

```

    con(l,l+1),con(l+1,r),con(l,r);
74     else{
        if(dot(pot(l+1)-pot(l),pot(r)-pot(l))<0)
            con(l,l+1),con(l,r);
        else if(dot(pot(l)-pot(l+1),pot(r)-pot(l+1))<0)
            con(l,l+1),con(l+1,r);
        else
            con(l,r),con(l+1,r);}
    return;
}
84     int m=(l+r)/2,pl=l,pr=r;
    dnc(l,m);
    dnc(m+1,r);
    for(int f=0;;f=0){
        for(int i=0;i<egs[pl].size();++i){
            int a=egs[pl][i],d=dir(pot(pl),pot(pr),pot(a));
            if(d>0|| (d==0&&dot(pot(pl)-pot(a),pot(pr)-pot(a))<0)){
                pl=a;
                f=1;
                break;
            }
        }
94     }
    for(int i=0;i<egs[pr].size();++i){
        int a=egs[pr][i],d=dir(pot(pl),pot(pr),pot(a));
        if(d>0|| (d==0&&dot(pot(pl)-pot(a),pot(pr)-pot(a))<0)){
            pr=a;
            f=1;
            break;
        }
    }
    if(!f)
104     break;
}
con(pl,pr);
for(int pn=-1,wh=0;;pn=-1,wh=0){
    for(int i=0;i<egs[pl].size();++i){
        int a=egs[pl][i],d=dir(pot(pl),pot(pr),pot(a));
        if(d<0&&(pn== -1||inc(pot(pl),pot(pr),pot(pn),pot(a))))
            pn=a;
    }
    for(int i=0;i<egs[pr].size();++i){

```

```

114         int a=egs[pr][i],d=dir(pot(pl),pot(pr),pot(a));
            if(d<0&&(pn== -1||inc(pot(pl),pot(pr),pot(pn),pot(a))))
                pn=a,wh=1;
        }
        if(pn== -1)
            break;
        vector<int>ne;
        if(!wh){
            for(int i=0;i<egs[pl].size();++i){
124                int a=egs[pl][i];
                if(!crs(pot(pn),pot(pr),pot(pl),pot(a)))
                    ne.push_back(a);
                else
                    egs[a].erase(find(egs[a].begin(),egs[a].end(),pl));
            }
            egs[pl]=ne;
            con(pr,pn);
            pl=pn;
        }else{
134            for(int i=0;i<egs[pr].size();++i){
                int a=egs[pr][i];
                if(!crs(pot(pn),pot(pl),pot(pr),pot(a)))
                    ne.push_back(a);
                else
                    egs[a].erase(find(egs[a].begin(),egs[a].end(),pr));
            }
            egs[pr]=ne;
            con(pl,pn);
            pr=pn;
        }
144    }
}

vector<vector<int> >run(){
    egs.resize(n+1);
    sort(pts.begin()+1,pts.end());
    dnc(1,n);
    vector<vector<int> >res(n+1);
    for(int u=1;u<=n;++u)
        for(int i=0;i<egs[u].size();++i){
154            int v=egs[u][i];
            res[pts[u].second].push_back(pts[v].second);

```

```

        }
        return res;
    }
};
template<class T>const double DelaunayTriangulation<T>::E=1e-8;

```

1.3 Dynamic Convex Hull (Set)

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Dynamic Convex Hull (Set).hpp (2239 bytes, 77 lines)

```

1  #include<bits/stdc++.h>
    using namespace std;
    template<class T>struct DynamicConvexHull{
        struct point{
            T x,y;
            point(T _x=0,T _y=0):
                x(_x),y(_y){
            }
            point operator-(const point&a)const{
                point p(x-a.x,y-a.y);
11         return p;
            }
            T operator*(const point&a)const{
                return x*a.y-y*a.x;
            }
        };
        struct node{
            node**nxt;point p;
            node(node**_n,point _p):
                nxt(_n),p(_p){
21         }
            node(const node&a):
                nxt(new node*(*a.nxt)),p(a.p){
            }
            ~node(){
                delete nxt;
            }
            int operator<(const node&a)const{

```

```

        if(ctp)
            return p.x==a.p.x?p.y<a.p.y:p.x<a.p.x;
31    point p1,p2;
        int f=1;
        if(nxt)
            p1=*nxt?(*nxt)->p-p:point(0,-1),p2=a.p;
        else
            f=0,p1=*a.nxt?(*a.nxt)->p-a.p:point(0,-1),p2=p;
        T x=p1*p2;
        return f?x<0:x>0;
    }
};
41    static int ctp;
    set<node>nds;
    typedef typename set<node>::iterator P;
    int check(P a,P b,P c){
        return (b->p-a->p)*(c->p-b->p)>=0;
    }
    void next(P a,P b){
        *(a->nxt)=(node*)&b;
    }
    void insert(T x,T y){
51        ctp=1;
        node t(new node*(0),point(x,y));
        P it=nds.insert(t).first,itl1=it,itl2,itl1=it,itl2=it;
        if(it!=nds.begin())
            for(next(--itl1,it);itl1!=nds.begin()&&check(--(itl2=itl1),
itl1,it);)
                next(itl2,it),nds.erase(itl1),itl1=itl2;
        if(++(itr1=it)!=nds.end())
            next(it,itr1);
        if(itl1!=it&&itr1!=nds.end()&&check(itl1,it,itr1)){
            next(itl1,itr1);
61            nds.erase(it);
            return;
        }
        if(itr1!=nds.end())
            for(++(itr2=itr1)!=nds.end()&&check(it,itr1,itr2);)
                next(it,itr2),nds.erase(itr1),itr1=itr2;
    }
    int size(){

```

```

        return nds.size();
    }
71 pair<T,T>query(T x,T y){
    ctp=0;
    node t=*nds.lower_bound(node(0,point(x,y)));
    return make_pair(t.p.x,t.p.y);
}
};
template<class T>int DynamicConvexHull<T>::ctp=0;

```

1.4 Dynamic Convex Hull (Treap)

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Dynamic Convex Hull (Treap).hpp (9485 bytes, 327 lines)

```

#include<bits/stdc++.h>
using namespace std;
3  template<class T>struct DynamicConvexHull{
    struct point{
        T x,y;
        point(T _x,T _y):
            x(_x),y(_y){
        }
        point operator-(const point&a)const{
            point p(x-a.x,y-a.y);
            return p;
        }
13    T operator*(const point&a)const{
        return x*a.y-y*a.x;
    }
    int operator<(const point&a)const{
        return x==a.x?y<a.y:x<a.x;
    }
    int operator==(const point&a)const{
        return x==a.x&&y==a.y;
    }
};
23 struct hull{
    point*pt;

```

```

hull*ch[2],*nb[2];
int sz,fx;
hull(point*_pt):
    pt(_pt),sz(1),fx(rand()*1.0/RAND_MAX*1e9){
        ch[0]=ch[1]=nb[0]=nb[1]=0;
    }
    T check(point p){
        return (nb[1]?*nb[1]->pt-*pt:point(0,-1))*p;
    }
void update(){
    sz=1;
    for(int i=0;i<2;++i)
        if(ch[i])
            sz+=ch[i]->sz;
}
};
static int sz(hull*x){
    return x?x->sz:0;
}
static point&pt(hull*x){
    return*x->pt;
}
static struct memory{
    hull*ps,*pp,**ss,**sp;
    int pm,sm;
    vector<hull*>ns;
    memory():
        ps((hull*)malloc(sizeof(hull))),pp(ps),pm(1),ss((hull**)malloc(
sizeof(hull*)),sp(ss),sm(1){
53     ns.push_back(ps);
    }
    ~memory(){
        free(ss);
        for(int i=0;i<ns.size();++i)
            free(ns[i]);
    }
    hull*create(const hull&x){
        if(sp!=ss){
63             --sp;
            **sp=x;
            return*sp;
        }
    }

```



```

    }
    if(pp==ps+pm){
        pp=ps=(hull*)malloc(sizeof(hull)*(pm<=1));
        ns.push_back(ps);
    }
    *pp=x;
    return pp++;
}
73 void destroy(hull*x){
    if(sp==ss+sm){
        hull**t=(hull**)malloc(sizeof(hull*)*sm<1);
        memcpy(t,ss,sm*sizeof(hull*));
        free(ss);
        sp=(ss=t)+sm;
        sm<=1;}
        *(sp++)=x;
    }
}me;
83 struct array{
    hull**ps,**pp;
    int pm;
    array():
        ps((hull**)malloc(sizeof(hull*))),pp(ps),pm(1){
    }
    ~array(){
        free(ps);
    }
    int size(){
93     return pp-ps;
    }
    hull*operator[](int i){
        return ps[i];
    }
    void push(hull*x){
        if(pp==ps+pm){
            hull**t=(hull**)malloc(sizeof(hull*)*pm<1);
            memcpy(t,ps,pm*sizeof(hull*));
            free(ps);
            pp=(ps=t)+pm;
103     pm<=1;
        }
    }

```

```

        *(pp++)=x;
    }
};
static hull*link(hull*x,hull*y,hull*lb,hull*rb,int d,array&ns){
    hull*r=me.create(*x);
    if(x==lb||x==rb){
        r->nb[d]=y;
113         if(y
            y->nb[!d]=r;
        }else
            r->ch[d]=link(r->ch[d],y,lb,rb,d,ns);
        r->update();
        ns.push(r);
        return r;
    }
static hull*merge(hull*x,hull*y,hull*lb,hull*rb,array&ns){
123     if(!x)
        return y;
    if(!y)
        return x;
    int d=x->fx>y->fx;
    hull*r=me.create(d?*x:*y);
    r->ch[d]=d?merge(r->ch[1],y,lb,rb,ns):merge(x,y->ch[0],lb,rb,ns);
    if(d&&x==lb||!d&&y==rb)
        r->ch[d]=link(r->ch[d],r,lb,rb,!d,ns);
    r->update();
    ns.push(r);
133     return r;
}
static pair<hull*,hull*>split(hull*x,int k,array&ns){
    if(!x)
        return make_pair((hull*)0,(hull*)0);
    int t=sz(x->ch[0])+1;
    hull*r=me.create(*x);
    ns.push(r);
    pair<hull*,hull*>s=split(x->ch[k>=t],k-t*(k>=t),ns);
143     if(k>=t){
        r->ch[1]=s.first;r->update();
        return make_pair(r,s.second);
    }else{
        r->ch[0]=s.second;r->update();
    }
}

```

```

        return make_pair(s.first,r);
    }
}
static void turn(hull*&x,int d,int&k){
    k+=(sz((x=x->ch[d])->ch[!d])+1)*(2*d-1);
}
153 static pair<T,T>range(hull*x){
    hull*l=x,*r=x;
    while(l->ch[0])
        l=l->ch[0];
    while(r->ch[1])
        r=r->ch[1];
    return make_pair(pt(l).x,pt(r).x);
}
static hull*merge(hull*x,hull*y,array&ns){
    int kp=sz(x->ch[0])+1,kq=sz(y->ch[0])+1,pd[2],qd[2];
163 pair<T,T>pr=range(x),qr=range(y);
    int pf=1;
    hull*p=x,*q=y;
    if(pr.second==qr.first&&pr.first==pr.second&&p->ch[pf=0])
        turn(p,0,kp);
    for(point pq=pt(q)-pt(p);;pq=pt(q)-pt(p)){
        pd[0]=(p->nb[0]&&(pt(p->nb[0])-pt(p))*pq<=0)*pf;
        qd[1]=(q->nb[1]&&(pt(q->nb[1])-pt(q))*pq<=0);
        pd[1]=(p->nb[1]&&(pt(p->nb[1])-pt(p))*pq<0)*pf;
        qd[0]=(q->nb[0]&&(pt(q->nb[0])-pt(q))*pq<0);
173 if(!(pd[0]+pd[1]+qd[0]+qd[1])){
        hull*l=split(x,kp,ns).first,*r=split(y,kq-1,ns).second,*lb=
1, *rb=r;
        while(lb->ch[1])
            lb=lb->ch[1];
        while(rb->ch[0])
            rb=rb->ch[0];
        return merge(l,r,lb,rb,ns);
    }
    if(!(pd[0]+pd[1]))
        turn(q,qd[1],kq);
183 if(!(qd[0]+qd[1]))
        turn(p,pd[1],kp);
    if(pd[0]&&qd[1])
        turn(p,0,kp),turn(q,1,kq);

```

```

    if(pd[1]&&qd[1])
        turn(q,1,kq);
    if(pd[0]&&qd[0])turn(p,0,kp);
    if(pd[1]&&qd[0]){
        point vp=pt(p->nb[1])-pt(p),vq=pt(q->nb[0])-pt(q);
        if(vp.x==0&&vq.x==0)
193         turn(p,1,kp),turn(q,0,kq);
        else if(vp.x==0)
            turn(p,1,kp);
        else if(vq.x==0)
            turn(q,0,kq);
        else{
            long double m=pr.second,pb=vp.y*(m-pt(p).x),qb=vq.y*(m-
pt(q).x);
            pb=pb/vp.x+pt(p).y;
            qb=qb/vq.x+pt(q).y;
203             if(qb>pb+1e-8)
                turn(q,0,kq);
            else if(pb>qb+1e-8)
                turn(p,1,kp);
            else if(pt(q->nb[0]).x+pt(p->nb[1]).x<2*m)
                turn(q,0,kq);
            else
                turn(p,1,kp);
        }
    }
}
213 }
hull*query(hull*x,point p){
    for(hull*y=0;;){
        T d=x->check(p);
        if(d>0)
            y=x,x=x->ch[0];
        else if(d<0)
            x=x->ch[1];
        else
            y=x;
223         if(!d||!x)
            return y;
    }
}

```

```

struct treap{
    int fx,ct,sz;
    point pt;
    treap*ch[2];
    struct hull*ip,*hu;
    array ns;
233   treap(point _pt):
        fx(rand()*1.0/RAND_MAX*1e9),ct(1),sz(1),pt(_pt),ip(me.create(
hull(&pt))),hu(ip){
        ch[0]=ch[1]=0;
    }
    ~treap(){
        for(hull**i=ns.ps;i!=ns.pp;++i)
            me.destroy(*i);
        me.destroy(ip);
    }
    void update(){
243     for(hull**i=ns.ps;i!=ns.pp;++i)
        me.destroy(*i);
        ns.pp=ns.ps;
        sz=1;
        hu=ip;
        if(ch[0])
            hu=merge(ch[0]->hu,hu,ns),sz+=ch[0]->sz;
        if(ch[1])
            hu=merge(hu,ch[1]->hu,ns),sz+=ch[1]->sz;
    }
253 }*root;
void rotate(treap*&x,int d){
    treap*y=x->ch[d];
    x->ch[d]=y->ch[!d];
    y->ch[!d]=x;
    x=y;
}
int insert(treap*&x,point p){
    if(!x)
        x=new treap(p);
263     else if(p==x->pt){
        ++x->ct;
        return 0;
    }else{

```

```

    int d=x->pt<p;
    if(!insert(x->ch[d],p))
        return 0;
    if(x->ch[d]->fx>x->fx)
        rotate(x,d),x->ch[!d]->update();
    x->update();
273     }
    return 1;
}
int erase(treap*&x,point p){
    if(p==x->pt){
        if(x->ct>1){
            --x->ct;
            return 0;
        }
        treap*y=x;
283     if(!x->ch[0])
            x=x->ch[1],delete y;
        else if(!x->ch[1])
            x=x->ch[0],delete y;
        else{
            int d=x->ch[0]->fx<x->ch[1]->fx;
            rotate(x,d);
            erase(x->ch[!d],p);
            x->update();
        }
293     return 1;
    }
    if(erase(x->ch[x->pt<p],p)){
        x->update();
        return 1;
    }else{
        --x->sz;
        return 0;
    }
}
303 void clear(treap*x){
    if(x)
        clear(x->ch[0]),clear(x->ch[1]),delete x;
}
DynamicConvexHull():

```

```

        root(0){
    }
    ~DynamicConvexHull(){
        clear(root);
    }
313 int size(){
        return root?root->sz:0;
    }
    void insert(T x,T y){
        insert(root,point(x,y));
    }
    void erase(T x,T y){
        erase(root,point(x,y));
    }
323 pair<T,T>query(T x,T y){
        point r=pt(query(root->hu,point(x,y)));
        return make_pair(r.x,r.y);
    }
};
template<class T>typename DynamicConvexHull<T>::memory DynamicConvexHull<T
>::me;

```

1.5 Geometry 2D

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Geometry 2D.hpp (5031 bytes, 159 lines)

```

#include<bits/stdc++.h>
using namespace std;
3 namespace Geometry2D{
    double eps=1e-8;
    long double pi=acos((long double)-1);
    template<class T>T sqr(T a){
        return a*a;
    }
    template<class T>int cmp(T a,T b){
        if(typeid(T)==typeid(int)||typeid(T)==typeid(long long)){
            if(a==b)
                return 0;

```

```

13         return a<b?-1:1;
        }
        if(a<b-eps)
            return -1;
        if(a>b+eps)
            return 1;
        return 0;
    }
    template<class T>struct Point{
        T x,y;
23     Point(T _x=0,T _y=0):
        x(_x),y(_y){
        }
        Point<T>&operator+=(const Point<T>&a){
            return*this=*this+a;
        }
        Point<T>&operator-=(const Point<T>&a){
            return*this=*this-a;
        }
    };
33 #define Vector Point
    template<class T>Point<T>operator+(const Point<T>&a,const Point<T>&b){
        return Point<T>(a.x+b.x,a.y+b.y);
    }
    template<class T>Point<T>operator-(const Point<T>&a,const Point<T>&b){
        return Point<T>(a.x-b.x,a.y-b.y);
    }
    template<class T>Point<T>operator*(T a,const Point<T>&b){
        return Point<T>(b.x*a,b.y*a);
    }
43 template<class T>Point<T>operator*(const Point<T>&a,T b){
        return b*a;
    }
    template<class T>Point<T>operator/(const Point<T>&a,T b){
        return Point<T>(a.x/b,a.y/b);
    }
    template<class T>bool operator==(const Point<T>&a,const Point<T>&b){
        return !cmp(a.x,b.x)&&!cmp(a.y,b.y);
    }
    template<class T>bool operator!=(const Point<T>&a,const Point<T>&b){
53     return !(a==b);

```



```

}
template<class T>bool operator<(const Point<T>&a,const Point<T>&b){
    int t=cmp(a.x,b.x);
    if(t)
        return t<0;
    return cmp(a.y,b.y)<0;
}
template<class T>bool operator>(const Point<T>&a,const Point<T>&b){
    return b<a;
}
63 template<class T>Point<T>NaP(){
    T t=numeric_limits<T>::max();
    return Point<T>(t,t);
}
template<class T>T det(const Point<T>&a,const Point<T>&b){
    return a.x*b.y-a.y*b.x;
}
template<class T>T dot(const Point<T>&a,const Point<T>&b){
    return a.x*b.x+a.y*b.y;
}
73 template<class T>T abs(const Point<T>&a){
    return sqrt(sqr(a.x)+sqr(a.y));
}
template<class T>T dis(const Point<T>&a,const Point<T>&b){
    return abs(a-b);
}
template<class T>istream&operator>>(istream&s,Point<T>&a){
    return s>>a.x>>a.y;
}
83 template<class T>ostream&operator<<(ostream&s,const Point<T>&a){
    return s<<a.x<<" "<<a.y;
}
template<class T>struct Segment;
template<class T>struct Line{
    Point<T>u,v;
    Line(const Point<T>&_u=Point<T>(),const Point<T>&_v=Point<T>()):
        u(_u),v(_v){
    }
    Line(const Segment<T>&a):
        u(a.u),v(a.v){
93 }

```

```

};
template<class T>Point<T>nor(const Line<T>&a){
    Point<T>t=a.v-a.u;
    return Point<T>(t.y,-t.x);
}
template<class T>Point<T>dir(const Line<T>&a){
    return a.v-a.u;
}
103 template<class T>int dir(const Line<T>a,const Point<T>b){
    return cmp(det(b-a.u,a.v-a.u),T(0));
}
template<class T>Point<T>operator&(const Line<T>&a,const Line<T>&b){
    T p=det(b.u-a.v,b.v-b.u),q=det(a.u-b.v,b.v-b.u);
    return (a.u*p+a.v*q)/(p+q);
}
template<class T>struct Segment{
    Point<T>u,v;
    Segment(const Point<T>&_u=Point<T>(),const Point<T>&_v=Point<T>()):
113     u(_u),v(_v){
    }
};
template<class T>Point<T>nor(const Segment<T>&a){
    Point<T>t=a.v-a.u;
    return Point<T>(t.y,-t.x);
}
template<class T>Point<T>dir(const Segment<T>&a){
    return a.v-a.u;
}
123 template<class T>int dir(const Segment<T>a,const Point<T>b){
    return cmp(b-a.u,a.v-a.u);
}
template<class T>Point<T>operator&(const Line<T>&a,const Segment<T>&b){
    if(dir(a,b.u)*dir(a,b.v)<=0)
        return a&Line<T>(b);
    return NaP<T>();
}
template<class T>Point<T>operator&(const Segment<T>&a,const Line<T>&b){
    return b&a;
}
133 template<class T>pair<T,T>dis(const Segment<T>&a,const Point<T>&b){
    pair<T,T>d(dis(a.u,b),dis(a.v,b));
}

```

```

        if(d.first>d.second)
            swap(d.first,d.second);
        Point<T>t=Line<T>(b,b+nor(a))&a;
        if(t!=NaP<T>())
            d.first=dis(t,b);
        return d;
    }
143 template<class T>pair<T,T>dis(const Point<T>&a,const Segment<T>&b){
        return dis(b,a);
    }
    template<class T>struct Circle{
        Point<T>c;
        T r;
        Circle(const Point<T>&_c=Point<T>(),T _r=0):
            c(_c),r(_r){
        }
    };
153 template<class T>T abs(const Circle<T>&a){
        return pi*sqr(a.r);
    }
    template<class T>bool col(const Point<T>&a,const Point<T>&b,const Point
<T>&c){
        return !cmp(det(a-c,b-c),T(0));
    }
}

```

1.6 Half-Plane Intersection

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Half-Plane Intersection.hpp (1950 bytes, 70 lines)

```

1 #include<bits/stdc++.h>
using namespace std;
namespace HalfPlaneIntersection{
    const double E=1e-8;
    struct pot{
        pot(double a=0,double b=0):
            x(a),y(b){
        }
    }
}

```

```

    double x,y;
};
11 double ag(pot p){
    return atan2(double(p.x),double(p.y));
}
pot operator+(pot p,pot q){
    return pot(p.x+q.x,p.y+q.y);
}
pot operator-(pot p,pot q){
    return pot(p.x-q.x,p.y-q.y);
}
21 pot operator*(pot p,double q){
    return pot(p.x*q,p.y*q);
}
pot operator/(pot p,double q){
    return pot(p.x/q,p.y/q);
}
double det(pot p,pot q){
    return p.x*q.y-q.x*p.y;
}
double dot(pot p,pot q){
    return p.x*q.x+p.y*q.y;
31 }
struct lin{
    pot p,q;
    double a;
    lin(pot a,pot b):
        p(a),q(b),a(ag(b-a)){
    }
};
pot operator*(lin a,lin b){
    double a1=det(b.p-a.q,b.q-b.p);
    double a2=det(a.p-b.q,b.q-b.p);
    return (a.p*a1+a.q*a2)/(a1+a2);
}
41 bool cmp(lin a,lin b){
    if(fabs(a.a-b.a)>E)
        return a.a<b.a;
    else
        return det(a.q-b.p,b.q-b.p)<-E;
}

```

```

    bool left(lin a, lin b, lin c){
51      pot t=a*b;
        return det(t-c.p,c.q-c.p)<-E;
    }
    deque<lin>run(vector<lin>lns){
        deque<lin>ans;
        sort(lns.begin(),lns.end(),cmp);
        for(int i=0;i<lns.size();++i){
            while(ans.size()>1&&!left(ans.back(),ans[ans.size()-2],lns[i]))
                ans.pop_back();
            while(ans.size()>1&&!left(ans[0],ans[1],lns[i]))
61              ans.pop_front();
            if(ans.empty()||fabs(ans.back().a-lns[i].a)>E)
                ans.push_back(lns[i]);
            while(ans.size()>1&&!left(ans[ans.size()-1],ans[ans.size()-2],ans.
front()))
                ans.pop_back();
            if(ans.size()<3)
                ans.clear();
            return ans;
        }
    }
}

```

CHAPTER 2

Data Structures

2.1 Binary Heap

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Binary Heap.hpp (1629 bytes, 73 lines)

```

#include<bits/stdc++.h>
using namespace std;
template<class T,class C>struct BinaryHeap{
    struct node{
        node(int _p,T _v):
            p(_p),v(_v){
        }
        int p;
        T v;
10    };
    vector<node*>a;
    BinaryHeap():
        a(1){
    }
    ~BinaryHeap(){
        clear();
    }
    void move(int i,int j){
        swap(a[i]->p,a[j]->p);
20    swap(a[i],a[j]);
    }
    int check(int i,int j){
        if(!j||j>=a.size()||a[i]->v==a[j]->v)
            return 0;
        return a[i]->v<a[j]->v?-1:1;
    }
    int up(int i){
        if(check(i,i>>1)<0){
            move(i,i>>1);
            return i>>1;
30        }else
            return 0;
    }
    int down(int i){
        if(check(i,i<<1)<=0&&check(i,i<<1^1)<=0)

```



```

        return a.size();
        if(check(i<<1,i<<1^1)<=0){
            move(i,i<<1);
            return i<<1;
40    }else{
            move(i,i<<1^1);
            return i<<1^1;
        }
    }
    void maintain(int i){
        for(int j=up(i);j;i=j,j=up(i));
        for(int j=down(i);j<a.size();i=j,j=down(i));
    }
    void clear(){
50    for(int i=1;i<a.size();++i)
        delete a[i];
        a.resize(1);
    }
    node*push(T v){
        a.push_back(new node(a.size(),v));
        node*r=a.back();
        maintain(a.size()-1);
        return r;
    }
60    T top(){
        return a[1]->v;
    }
    void pop(){
        move(1,a.size()-1);
        delete a.back();
        a.pop_back();
        maintain(1);
    }
    void modify(node*x,T v){
70    x->v=v;
        maintain(x->p);
    }
};

```

```

        pp=ps=(node*)malloc(sizeof(node)*(pm<=1));
        ns.push_back(ps);
37     }
        *pp=node(a);
        return pp++;
    }
    void des(node*x){
        if(sp==ss+sm){
            node**t=(node**)malloc(sizeof(node*)*sm<1);
            memcpy(t,ss,sm*sizeof(node*));
            free(ss);
            sp=(ss=t)+sm;
47         sm<=1;
        }
        *(sp++)=x;
    }
}me;
node*bud(T*a,int l,int r){
    if(l>r)
        return 0;
    int m=l+r>>1;
    node*t=me.crt(a[m]);
57     t->c[0]=bud(a,l,m-1);
    t->c[1]=bud(a,m+1,r);
    pup(t);
    return t;
}
void pdw(node*x){
    for(int d=0;d<2&&(x->i>x->v,1);++d)
        if(x->c[d])
            x->i>x->c[d]->i;
    *x->i;
    *x->v;
67     if(x->r){
        -x->i;
        for(int d=0;d<2;++d)
            if(x->c[d])
                x->c[d]->r^=1;
        swap(x->c[0],x->c[1]);
        x->r=0;
    }
}

```

```

    }
77 void pup(node*x){
    x->i=x->v;
    x->s=1;
    for(int d=0;d<2;++d)
        if(x->c[d])
            pdw(x->c[d]),x->s+=x->c[d]->s,x->i=d?x->i+x->c[d]->i:x->
c[d]->i+x->i;
    }
    void jon(node*x){
        rt=jon(jon(sl,x),sr);
    }
87 node*jon(node*x,node*y){
    if(!x)
        return y;
    if(!y)
        return x;
    pdw(x);
    pdw(y);
    if(x->w<y->w){
        x->c[1]=jon(x->c[1],y);
        pup(x);
        return x;
97    }else{
        y->c[0]=jon(x,y->c[0]);
        pup(y);
        return y;
    }
}
node*spt(int l,int r){
    spt(rt,l-1);
    node*t=sl;
    spt(sr,r-l+1);
    swap(sl,t);
    return t;
107 }
void spt(node*x,int p){
    if(!x){
        sl=sr=0;
        return;
    }

```

```

117     pdw(x);
        int t=x->c[0]?x->c[0]->s:0;
        if(t<p)
            spt(x->c[1],p-t-1),x->c[1]=s1,s1=x;
        else
            spt(x->c[0],p),x->c[0]=sr,sr=x;
        pup(x);
    }
    void clr(node*x){
        if(x)
            clr(x->c[0]),clr(x->c[1]),me.des(x);
127 }
    DynamicSequence(T*a=0,int n=0){
        rt=bud(a,1,n);
    }
    ~DynamicSequence(){
        clr(rt);
    }
    void clear(){
        clr(rt);
        rt=0;
137 }
    void insert(T a,int p){
        insert(&a-1,1,p);
    }
    void insert(T*a,int n,int p){
        spt(p+1,p);
        jon(bud(a,1,n));
    }
    void erase(int p){
        erase(p,p);
147 }
    void erase(int l,int r){
        clr(spt(l,r));
        jon(0);
    }
    T query(int p){
        return query(p,p);
    }
    T query(int l,int r){
        node*t=spt(l,r);

```

```

157         T i=t->i;
           jon(t);
           return i;
       }
       void modify(T a,int l){
           modify(a,l,l);
       }
       void modify(T a,int l,int r){
           node*t=spt(l,r);
           a>t->i;
           jon(t);
167     }
       void reverse(int l,int r){
           node*t=spt(l,r);
           t->r=1;
           jon(t);
       }
       int length(){
           return rt?rt->s:0;
       }
177 };

```

2.3 Fenwick Tree

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Fenwick Tree.hpp (529 bytes, 25 lines)

```

#include<bits/stdc++.h>
using namespace std;
3  template<class T>struct FenwickTree{
    FenwickTree(int _n):
        n(_n),l(log2(n)),a(n+1){
    }
    void add(int v,T d){
        for(;v<=n;v+=v&-v)
            a[v]+=d;
    }
    T sum(int v){
        T r=0;

```

```

13         for(;v;v-=v&-v)
            r+=a[v];
        return r;
    }
    int kth(T k,int r=0){
        for(int i=1<<1;i;i>=1)
            if(r+i<=n&& a[r+i]<k)
                k-=a[r+=i];
        return r+1;
    }
23    int n,l;
    vector<T>a;
};

```

2.4 K-D Tree

warning: old style will be replaced ... see Suffix Array (DC3) for new style

K-D Tree.hpp (2467 bytes, 80 lines)

```

#include<bits/stdc++.h>
using namespace std;
struct KDTree{
    struct node{
5        node(int x0,int x1,int d):
            color(1),cover(0),dir(d){
                ch[0]=ch[1]=0;
                x[0]=mi[0]=mx[0]=x0;
                x[1]=mi[1]=mx[1]=x1;
            }
            node*ch[2];
            int x[2],mi[2],mx[2],color,cover,dir;
    }*root;
    KDTree(pair<int,int>*a,int n){
15        root=build(a,1,n,0);
    }
    static int direct;
    static int cmp(pair<int,int>a,pair<int,int>b){
        if(direct)
            return make_pair(a.second,a.first)<make_pair(b.second,b.first);
    }
};

```

```

        return a<b;
    }
    node*build(pair<int,int>*a,int l,int r,int d){
        int m=(r+l)/2;
        direct=d;
25      nth_element(a+l,a+m,a+r+1,cmp);
        node*p=new node((a+m)->first,(a+m)->second,d);
        if(l!=m)
            p->ch[0]=build(a,l,m-1,!d);
        if(r!=m)
            p->ch[1]=build(a,m+1,r,!d);
        for(int i=0;i<2;++i)
            for(int j=0;j<2;++j)
35              if(p->ch[j]){
                    p->mi[i]=min(p->mi[i],p->ch[j]->mi[i]);
                    p->mx[i]=max(p->mx[i],p->ch[j]->mx[i]);
                }
        return p;
    }
}
void down(node*a){
    if(a->cover){
        for(int i=0;i<2;++i)
            if(a->ch[i])
45              a->ch[i]->cover=a->cover;
        a->color=a->cover;
        a->cover=0;
    }
}
void modify(node*a,int mi0,int mx0,int mi1,int mx1,int c){
    if(mi0>a->mx[0]||mx0<a->mi[0]||mi1>a->mx[1]||mx1<a->mi[1])
        return;
    if(mi0<=a->mi[0]&&mx0>=a->mx[0]&&mi1<=a->mi[1]&&mx1>=a->mx[1]){
        a->cover=c;
        return;
    }
55  down(a);
    if(mi0<=a->x[0]&&mx0>=a->x[0]&&mi1<=a->x[1]&&mx1>=a->x[1])
        a->color=c;
    for(int i=0;i<2;++i)
        if(a->ch[i])
            modify(a->ch[i],mi0,mx0,mi1,mx1,c);
}

```



```

    }
    void modify(int mi0,int mx0,int mi1,int mx1,int c){
        modify(root,mi0,mx0,mi1,mx1,c);
65    }
    int query(node*a,int x0,int x1){
        down(a);
        if(x0==a->x[0]&&x1==a->x[1])
            return a->color;
        direct=a->dir;
        if(cmp(make_pair(x0,x1),make_pair(a->x[0],a->x[1])))
            return query(a->ch[0],x0,x1);
        else
            return query(a->ch[1],x0,x1);
75    }
    int query(int x0,int x1){
        return query(root,x0,x1);
    }
};
int KDTree::direct=0;

```

2.5 Link-Cut Tree

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Link-Cut Tree.hpp (5518 bytes, 215 lines)

```

#include<bits/stdc++.h>
using namespace std;
template<class T>struct LinkCutTree{
    struct node{
        node():
            ch({0,0}),pr(0),rev(0){
        }
        node*ch[2],*pr;
        T ifo;
10    int rev;
    }*ptrs;
    LinkCutTree(int n):
        ptrs(new node[n]-1){
    }

```

```

~LinkCutTree(){
    delete ptrs;
}
int direct(node*x){
    if(!x->pr)
        return 2;
    if(x==x->pr->ch[0])
        return 0;
    if(x==x->pr->ch[1])
        return 1;
    return 2;
}
void down(node*x){
    if(x->rev){
        x->ifo.reverse();
        swap(x->ch[0],x->ch[1]);
        for(int i=0;i<2;++i)
            if(x->ch[i])
                x->ch[i]->rev^=1;
        x->rev=0;
    }
    x->ifo.down(x->ch[0]?&x->ch[0]->ifo:0,x->ch[1]?&x->ch[1]->ifo:0);
}
void up(node*x){
    for(int i=0;i<2;++i)
        if(x->ch[i])
            down(x->ch[i]);
    x->ifo.up(x->ch[0]?&x->ch[0]->ifo:0,x->ch[1]?&x->ch[1]->ifo:0);
}
void setchild(node*x,node*y,int d){
    x->ch[d]=y;
    if(y)
        y->pr=x;
    up(x);
}
void rotate(node*x){
    node*y=x->pr,*z=y->pr;
    int d1=direct(x),d2=direct(y);
    setchild(y,x->ch[!d1],d1);
    setchild(x,y,!d1);
    if(d2<2)

```

```

        setchild(z,x,d2);
    else
        x->pr=z;
}
60 void release(node*x){
    if(direct(x)<2)
        release(x->pr);
    down(x);
}
void splay(node*x){
    for(release(x);direct(x)<2;){
        node*y=x->pr;
        if(direct(y)==2)
            rotate(x);
70     else if(direct(x)==direct(y))
            rotate(y),rotate(x);
        else
            rotate(x),rotate(x);
    }
}
node*access(node*x){
    node*y=0;
    for(;x;y=x,x=x->pr){
        splay(x);
80     setchild(x,y,1);
    }
    return y;
}
void evert(node*x){
    access(x);
    splay(x);
    x->rev=1;
}
90 void set(int x,T v){
    ptrs[x].ifo=v;
}
int linked(int a,int b){
    access((ptrs+a));
    node*z=access((ptrs+b));
    return z==access((ptrs+a));
}

```

```

100 void link(int a,int b){
    evert((ptrs+b));
    (ptrs+b)->pr=(ptrs+a);
}
void cut(int a,int b){
    access((ptrs+b));
    node*z=access((ptrs+a));
    if(z==(ptrs+a))
        splay((ptrs+b)),(ptrs+b)->pr=0;
    else
        access((ptrs+b)),splay((ptrs+a)),(ptrs+a)->pr=0;
}
110 int root(int a){
    access((ptrs+a));
    splay((ptrs+a));
    node*r=(ptrs+a);
    while(r->ch[1])
        r=r->ch[1];
    return r-ptrs;
}
void evert(int a){
    evert((ptrs+a));
}
120 int lca(int a,int b){
    access((ptrs+a));
    return access((ptrs+b))-ptrs;
}
T query(int a){
    splay((ptrs+a));
    T p=(ptrs+a)->ifo;
    p.up(0,0);
    return p;
}
130 T query(int a,int b){
    if((ptrs+a)==(ptrs+b))
        return query((ptrs+a));
    access((ptrs+a));
    node*c=access((ptrs+b));
    T p=c.ifo;
    if(c==(ptrs+b)){
        splay((ptrs+a));
    }
}

```

```

    T q=(ptrs+a)->ifo;
    q.reverse();
140    p.up(&q,0);
    return p;
}else if(c==(ptrs+a))
    p.up(0,&(ptrs+a)->ch[1]->ifo);
else{
    splay((ptrs+a));
    T q=(ptrs+a)->ifo;
    q.reverse();
    p.up(&q,&c->ch[1]->ifo);
}
150    return p;
}
T equery(int a){
    return query(a);
}
T equery(int a,int b){
    access((ptrs+a));
    node*c=access((ptrs+b));
    if(c==(ptrs+b)){
160        splay((ptrs+a));
        T q=(ptrs+a)->ifo;
        q.reverse();
        return q;
    }else if(c==(ptrs+a))
        return (ptrs+a)->ch[1]->ifo;
    else{
        splay((ptrs+a));
        node*t=c->ch[1];
        while(t->ch[0])
            t=t->ch[0];
170        splay(t);
        if(t->ch[1])
            down(t->ch[1]);
        T p=t->ifo,q=(ptrs+a)->ifo;
        q.reverse();
        p.up(&q,t->ch[1]?&t->ch[1]->ifo:0);
        return p;
    }
}

```

```

180  template<class F>void modify(int a,F f){
        splay((ptrs+a));
        f(&(ptrs+a)->ifo);
        up((ptrs+a));
    }
    template<class F>void modify(int a,int b,F f){
        if((ptrs+a)==(ptrs+b)){
            splay((ptrs+a));
            f(0,&(ptrs+a)->ifo,0);
            up((ptrs+a));
            return;
190     }
        access((ptrs+a));
        node*c=access((ptrs+b));
        if(c==(ptrs+b))
            splay((ptrs+a)),f(&(ptrs+a)->ifo,&(ptrs+b)->ifo,0);
        else if(c==a)
            f(0,&(ptrs+a)->ifo,&(ptrs+a)->ch[1]->ifo);
        else
            splay(a),f(&(ptrs+a)->ifo,&c->ifo,&c->ch[1]->ifo);
200     up(c);
    }
    template<class F>void emodify(int a,F f){
        modify(a,f);
    }
    template<class F>void emodify(int a,int b,F f){
        access((ptrs+a));
        node*c=access((ptrs+b));
        if(c==(ptrs+b))
            splay((ptrs+a)),f(&(ptrs+a)->ifo,0);
        else if(c==a)
210     f(0,&(ptrs+a)->ch[1]->ifo);
        else
            splay(a),f(&(ptrs+a)->ifo,&c->ch[1]->ifo);
        up(c);
    }
};

```

2.6 Pairing Heap

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Pairing Heap.hpp (2226 bytes, 102 lines)

```

#include<bits/stdc++.h>
using namespace std;
template<class T,class C>struct PairingHeap{
    PairingHeap():
5      root(0),siz(0){
    }
    ~PairingHeap(){
        clear(root);
    }
    struct node{
        node(const T&_val):
            val(_val),ch(0),br(0),pr(0){
        }
        T val;
15      node*ch,*br,*pr;
    }*root;
    int siz;
    void merge(node*&x,node*y){
        if(!x)
            x=y;
        else if(y){
            if(C()(y->val,x->val))
                swap(x,y);
            y->br=x->ch;
25          if(x->ch)
                x->ch->pr=y;
            y->pr=x;
            x->ch=y;
        }
    }
    void cut(node*&x,node*y){
        if(x==y)
            x=0;
        else{
35          if(y==y->pr->ch)

```

```

        y->pr->ch=y->br;
    else
        y->pr->br=y->br;
    if(y->br)
        y->br->pr=y->pr;
    y->pr=y->br=0;
}
}
node*split(node*x){
45     vector<node*>t;
        for(node*i=x->ch;i;i=i->br)
            t.push_back(i);
        x->ch=0;
        node*r=0;
        for(int i=0;i<t.size();++i)
            t[i]->pr=t[i]->br=0;
        for(int i=0;i+1<t.size();i+=2)
            merge(t[i],t[i+1]);
55     for(int i=0;i<t.size();i+=2)
        merge(r,t[i]);
        return r;
}
void clear(node*x){
    if(x){
        clear(x->ch);
        clear(x->br);
        delete x;
    }
}
65 void clear(){
    clear(root);
    root=0;
    siz=0;
}
node*push(T a){
    node*r=new node(a);
    merge(root,r);
    ++siz;
    return r;
75 }
void erase(node*x){

```



```

        cut(root,x);
        merge(root,split(x));
        --siz;
    }
    T top(){
        return root->val;
    }
    void pop(){
85      erase(root);
    }
    void merge(PairingHeap<T,C>&a){
        merge(root,a.root);
        a.root=0;
        siz+=a.siz;
        a.siz=0;
    }
    void modify(node*x,T v){
95      if(C()(x->val,v))
        x->val=v,merge(root,split(x));
      else
        x->val=v,cut(root,x),merge(root,x);
    }
    int size(){
        return siz;
    }
};

```

2.7 Red-Black Tree

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Red-Black Tree.hpp (7432 bytes, 307 lines)

```

#include<bits/stdc++.h>
using namespace std;
template<class T,class C>struct RedBlackTree{
    struct node{
        node(T _v,node*l,node*r,node*_p,int _b,int _s):
            v(_v),p(_p),b(_b),s(_s){
                c[0]=1;

```

```

8          c[1]=r;
          }
          T v;
          node*c[2],*p;
          int b,s;
          }*root,*nil;
void clear(node*x){
          if(x!=nil){
              clear(x->c[0]);
              clear(x->c[1]);
18          delete x;
          }
      }
void rotate(node*x,int d){
      node*y=x->c[!d];
      x->c[!d]=y->c[d];
      if(y->c[d]!=nil)
          y->c[d]->p=x;
      y->p=x->p;
      if(x->p==nil)
28          root=y;
      else
          x->p->c[x!=x->p->c[0]]=y;
      y->c[d]=x;
      x->p=y;
      y->s=x->s;
      x->s=x->c[0]->s+x->c[1]->s+1;
  }
void insert_fixup(node*z){
      while(!z->p->b){
38          int d=z->p==z->p->p->c[0];
          node*y=z->p->p->c[d];
          if(!y->b)
              z->p->b=1,y->b=1,(z=z->p->p)->b=0;
          else{
              if(z==z->p->c[d])
                  rotate(z=z->p,!d);
              z->p->b=1;
              z->p->p->b=0;
              rotate(z->p->p,d);
48          }
      }
  }

```

```

    }
    root->b=1;
}
void erase(node*z){
    node*y;
    for(y=z;y!=nil;y=y->p)
        --y->s;
    if(z->c[0]==nil || z->c[1]==nil)
        y=z;
58  else{
        for(y=z->c[1];y->c[0]!=nil;)
            y=y->c[0];
        z->v=y->v;
        y=z->c[1];
        while(y->c[0]!=nil)
            --y->s,y=y->c[0];
    }
    node*x=y->c[y->c[0]==nil];
    x->p=y->p;
68  if(y->p==nil)
        root=x;
    else
        y->p->c[y!=y->p->c[0]]=x;
    if(y->b)
        erase_fixup(x);
    delete y;
}
void erase_fixup(node*x){
78  while(x!=root&& x->b){
        int d=x==x->p->c[0];
        node*w=x->p->c[d];
        if(!w->b){
            w->b=1;
            x->p->b=0;
            rotate(x->p,!d);
            w=x->p->c[d];
        }
        if(w->c[0]->b&&w->c[1]->b)
            w->b=0,x=x->p;
88  else{
            if(w->c[d]->b)

```

```

        w->c[!d]->b=1,w->b=0,rotate(w,d),w=x->p->c[d];
        w->b=x->p->b;
        x->p->b=1;
        w->c[d]->b=1;
        rotate(x->p,!d);
        x=root;
    }
}
98     x->b=1;
}
node*clone(node*x,node*y){
    if(x.size==0)
        return nil;
    node*z=new node(*x);
    z->c[0]=clone(x->c[0],z);
    z->c[1]=clone(x->c[1],z);
    z->p=y;
    return z;
108 }
node*precursor(node*x){
    if(x->c[0]->count){
        for(x=x->c[0];x->c[1]->count;)
            x=x->c[1];
        return x;
    }else{
        node*y=x->p;
        while(y->count&&x==y->c[0])
            x=y,y=y->p;
118     return y;
    }
}
node*successor(node*x){
    if(x->c[1]->count){
        for(x=x->c[1];x->c[0]->count;)
            x=x->c[0];
        return x;
    }else{
        node*y=x->p;
        while(y->count&&x==y->c[1])
            x=y,y=y->p;
128     return y;
    }
}

```

```

    }
}
RedBlackTree(){
    root=nil=(node*)malloc(sizeof(node));
    nil->b=1;
    nil->s=0;
}
138 RedBlackTree(const RedBlackTree&a){
    nil=new node(*a.nil);
    root=clone(a.root,nil);
}
~RedBlackTree(){
    clear(root);
    free(nil);
}
RedBlackTree&operator=(const RedBlackTree&a){
148     clear(root);
    root=clone(a.root,nil);
    return*this;
}
node*begin(){
    node*z=root;
    while(z!=nil&&z->c[0]!=nil)
        z=z->c[0];
    return z;
}
158 node*reverse_begin(){
    node*z=root;
    while(z!=nil&&z->c[1]!=nil)
        z=z->c[1];
    return z;
}
node*end(){
    return nil;
}
node*reverse_end(){
    return nil;
168 }
void clear(){
    clear(root);
    root=nil;
}

```

```

}
void insert(T a){
    node*y=nil,*x=root;
    while(x!=nil)
        y=x,++x->s,x=x->c[C()](x->v,a)];
    node*z=new node(a,nil,nil,y,0,1);
178    if(y==nil)
        root=z;
    else
        y->c[C()](y->v,z->v)]=z;
    insert_fixup(z);
}
void erase(T a){
    node*z=root;
    for(;;)
        if(C() (a,z->v))
            z=z->c[0];
188        else if(C() (z->v,a))
            z=z->c[1];
        else
            break;
    erase(z);
}
int count(T a){
    return count_less_equal(a)-count_less(a);
}
198 int count_less(T a){
    int r=0;
    node*z=root;
    while(z!=nil)
        if(C() (z->v,a))
            r+=z->c[0]->s+1,z=z->c[1];
        else
            z=z->c[0];
    return r;
}
208 int count_less_equal(T a){
    int r=0;
    node*z=root;
    while(z!=nil){
        if(!C() (a,z->v))

```

```

        r+=z->c[0]->s+1,z=z->c[1];
    else
        z=z->c[0];
    }
    return r;
218 }
int count_greater(T a){
    int r=0;
    node*z=root;
    while(z!=nil)
        if(C()(a,z->v))
            r+=z->c[1]->s+1,z=z->c[0];
        else
            z=z->c[1];
    return r;
228 }
int count_greater_equal(T a){
    int r=0;
    node*z=root;
    while(z!=nil)
        if(!C()(z->v,a))
            r+=z->c[1]->s+1,z=z->c[0];
        else
            z=z->c[1];
    return r;
238 }
node*nth_element(int a){
    node*z=root;
    for(;;)
        if(z->c[0]->s>=a)
            z=z->c[0];
        else if((z->c[0]->s+1)<a)
            a-=z->c[0]->s+1,z=z->c[1];
        else
            return z;
248 }
node*precursor(T a){
    node*z=root,*r=nil;
    while(z!=nil)
        if(C()(z->v,a))
            r=z,z=z->c[1];

```

```

        else
            z=z->c[0];
        return r;
    }
258 node*successor(T a){
    node*z=root,*r=nil;
    while(z!=nil)
        if(C()(a,z->v))
            r=z,z=z->c[0];
        else
            z=z->c[1];
    return r;
}
268 node*find(T a){
    node*z=root,*r=nil;
    while(z!=nil)
        if(C()(a,z->v))
            z=z->c[0];
        else if(C()(z->v,a))
            z=z->c[1];
        else
            break;
    return r;
}
278 node*lower_bound(T a){
    node*z=root,*r=nil;
    while(z!=nil)
        if(C()(z->v,a))
            r=z,z=z->c[1];
        else if(C()(a,z->v))
            z=z->c[0];
        else
            r=z,z=z->c[0];
    return r;
}
288 node*upper_bound(T a){
    return successor(a);
}
pair<node*,node*> equal_range(T a){
    return make_pair(lower_bound(a),upper_bound(a));
}

```



```

    int size(){
        return root->s;
    }
298 int empty(){
        return !root->s;
    }
    T front(){
        return*begin();
    }
    T back(){
        return*reverse_begin();
    }
};

```

2.8 Self-Adjusting Top Tree

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Self-Adjusting Top Tree.hpp (12629 bytes, 443 lines)

```

#include<bits/stdc++.h>
using namespace std;
3 struct SelfAdjustingTopTree{
    const static int inf=~0u>>1;
    static void gmin(int&a,int b){
        a=min(a,b);
    }
    static void gmax(int&a,int b){
        a=max(a,b);
    }
    struct treap{
        SelfAdjustingTopTree*tr;
13    treap(struct SelfAdjustingTopTree*a,int n):
        tr(a),ns(n){
    }
    struct node{
        node(){
        }
        node(int a,int b,int c,int d,int e){
            ch[0]=ch[1]=0;

```

```

23         val=a;
           fix=rand();
           add=0;
           mi=vmi=b;
           mx=vmx=c;
           sum=vsum=d;
           siz=vsiz=e;
           sam=inf;
       }
       node*ch[2];
       int val,fix,vmi,vmx,vsum,vsiz,mi,mx,sum,siz,add,sam;
};
33 vector<node>ns;
void down(node*a){
    if(a->sam!=inf){
        a->mi=a->mx=a->vmi=a->vmx=a->sam;
        a->vsum=a->sam*a->vsiz;
        a->sum=a->sam*a->siz;
        (&tr->ns[0]+(a-&ns[0]))->viradd=0;
        (&tr->ns[0]+(a-&ns[0]))->virsam=a->sam;
        (&tr->ns[0]+(a-&ns[0]))->add=0;
        (&tr->ns[0]+(a-&ns[0]))->sam=a->sam;
43     for(int i=0;i<=1;++i)
        if(a->ch[i])
            a->ch[i]->add=0,a->ch[i]->sam=a->sam;
        a->sam=inf;
    }
    if(a->add){
        a->mi+=a->add;
        a->mx+=a->add;
        a->vmi+=a->add;
        a->vmx+=a->add;
53     a->vsum+=a->add*a->vsiz;
        a->sum+=a->add*a->siz;
        (&tr->ns[0]+(a-&ns[0]))->viradd+=a->add;
        (&tr->ns[0]+(a-&ns[0]))->add+=a->add;
        for(int i=0;i<=1;++i)
            if(a->ch[i])
                a->ch[i]->add+=a->add;
        a->add=0;
    }
}

```

```

    }
63    void update(node*a){
        for(int i=0;i<=1;++i)
            if(a->ch[i])
                down(a->ch[i]);
        a->mi=a->vmi;
        for(int i=0;i<=1;++i)
            if(a->ch[i])
                gmin(a->mi,a->ch[i]->mi);
        a->mx=a->vmx;
73    for(int i=0;i<=1;++i)
            if(a->ch[i])
                gmax(a->mx,a->ch[i]->mx);
        a->sum=a->vsum;
        for(int i=0;i<=1;++i)
            if(a->ch[i])
                a->sum+=a->ch[i]->sum;
        a->siz=a->vsiz;
        for(int i=0;i<=1;++i)
            if(a->ch[i])
                a->siz+=a->ch[i]->siz;
83    }
    void rotate(node*&a,int d){
        node*b=a->ch[d];
        a->ch[d]=b->ch[!d];
        b->ch[!d]=a;
        update(a);
        update(b);
        a=b;
    }
    void insert(node*&a,node*b){
93    if(!a)
        a=b;
    else{
        down(a);
        int d=b->val>a->val;
        insert(a->ch[d],b);
        update(a);
        if(a->ch[d]->fix<a->fix)
            rotate(a,d);
    }

```

```

103     }
        void erase(node*&a,int b){
            down(a);
            if(a->val==b){
                if(!a->ch[0])
                    a=a->ch[1];
                else if(!a->ch[1])
                    a=a->ch[0];
                else{
113                     int d=a->ch[1]->fix<a->ch[0]->fix;
                        down(a->ch[d]);
                        rotate(a,d);
                        erase(a->ch[!d],b);
                        update(a);
                }
            }else{
                int d=b>a->val;
                erase(a->ch[d],b);
                update(a);
            }
123     }
};
int n;
SelfAdjustingTopTree(int _n,vector<int>*to,int*we,int rt):
    trp(this,_n+1),ns(_n+1),n(_n){
    build(to,we,rt);
}
struct node{
    node(){}
    node(int a,node*b){
133         ch[0]=ch[1]=0;
            pr=b;
            vir=0;
            val=a;
            mi=mx=a;
            siz=1;
            rev=virsum=add=0;
            virmi=inf;
            virmx=-inf;
            sam=inf;
143         virsam=inf;

```

```

        virsiz=0;
        viradd=0;
    }
    node*ch[2],*pr;
    int val,mi,mx,sum,virmi,virmx,virsum,virsam,viradd,virsiz,rev,sam,
siz,add;
    treap::node*vir;
};
vector<node>ns;
treap trp;
153 int direct(node*a){
    if(!a->pr)
        return 3;
    else if(a==a->pr->ch[0])
        return 0;
    else if(a==a->pr->ch[1])
        return 1;
    else
        return 2;
}
163 void down(node*a){
    if(a->rev){
        swap(a->ch[0],a->ch[1]);
        for(int i=0;i<=1;++i)
            if(a->ch[i])
                a->ch[i]->rev^=1;
        a->rev=0;
    }
    if(a->sam!=inf){
        a->val=a->mi=a->mx=a->sam;
        a->sum=a->sam*a->siz;
        173 for(int i=0;i<=1;++i)
            if(a->ch[i])a->ch[i]->sam=a->sam,a->ch[i]->add=0;
        a->sam=inf;
    }
    if(a->add){
        a->val+=a->add;
        a->mi+=a->add;
        a->mx+=a->add;
        a->sum+=a->add*a->siz;
        183 for(int i=0;i<=1;++i)

```

```

        if(a->ch[i])a->ch[i]->add+=a->add;
        a->add=0;
    }
    if(a->virsam!=inf){
        if(a->virsiz){
            a->virmi=a->virmx=a->virsam;
            a->virsum=a->virsam*a->virsiz;
            if(a->vir)
                a->vir->add=0,a->vir->sam=a->virsam;
193         for(int i=0;i<=1;++i)
                if(a->ch[i])
                    a->ch[i]->viradd=0,a->ch[i]->virsam=a->virsam;
        }
        a->virsam=inf;
    }
    if(a->viradd){
        if(a->virsiz){
            a->virmi+=a->viradd;
            a->virmx+=a->viradd;
            a->virsum+=a->viradd*a->virsiz;
            if(a->vir)a->vir->add+=a->viradd;
            for(int i=0;i<=1;++i)
                if(a->ch[i])
                    a->ch[i]->viradd+=a->viradd;
        }
        a->viradd=0;
    }
}
}
void update(node*a){
213     for(int i=0;i<=1;++i)
        if(a->ch[i])
            down(a->ch[i]);
    if(a->vir)
        trp.down(a->vir);
    a->mi=a->val;
    for(int i=0;i<=1;++i)
        if(a->ch[i])
            gmin(a->mi,a->ch[i]->mi);
    a->virmi=inf;
223     for(int i=0;i<=1;++i)
        if(a->ch[i])

```

```

                gmin(a->virmi,a->ch[i]->virmi);
    if(a->vir)
        gmin(a->virmi,a->vir->mi);
    a->mx=a->val;
    for(int i=0;i<=1;++i)
        if(a->ch[i])
            gmax(a->mx,a->ch[i]->mx);
233 a->virmx=-inf;
    for(int i=0;i<=1;++i)
        if(a->ch[i])
            gmax(a->virmx,a->ch[i]->virmx);
    if(a->vir)
        gmax(a->virmx,a->vir->mx);
    a->sum=a->val;
    for(int i=0;i<=1;++i)
        if(a->ch[i])
            a->sum+=a->ch[i]->sum;
243 a->virsum=0;
    for(int i=0;i<=1;++i)
        if(a->ch[i])
            a->virsum+=a->ch[i]->virsum;
    if(a->vir)
        a->virsum+=a->vir->sum;
    a->siz=1;
    for(int i=0;i<=1;++i)
        if(a->ch[i])
            a->siz+=a->ch[i]->siz;
253 a->virsiz=0;
    for(int i=0;i<=1;++i)
        if(a->ch[i])
            a->virsiz+=a->ch[i]->virsiz;
    if(a->vir)
        a->virsiz+=a->vir->siz;
}
void setchd(node*a,node*b,int d){
    a->ch[d]=b;
    if(b)
        b->pr=a;
263 update(a);
}
void connect(node*a,node*b){

```

```

        down(a);
        *(&trp.ns[0]+(a-&ns[0]))=treap::node(a-&ns[0],min(a->virmi,a->mi),
max(a->virmx,a->mx),a->virsum+a->sum,a->virsiz+a->siz);
        trp.insert(b->vir,&trp.ns[0]+(a-&ns[0]));
    }
    void disconnect(node*a,node*b){
        trp.erase(b->vir,a-&ns[0]);
    }
273 void rotate(node*a){
        node*b=a->pr,*c=a->pr->pr;
        int d1=direct(a),d2=direct(b);
        setchd(b,a->ch[!d1],d1);
        setchd(a,b,!d1);
        if(d2<2)
            setchd(c,a,d2);
        else if(d2==2){
            disconnect(b,c);
            connect(a,c);
            a->pr=c;
283 }else
            a->pr=0;
    }
    void release(node*a){
        if(direct(a)<2)
            release(a->pr);
        else if(a->pr)
            disconnect(a,a->pr),connect(a,a->pr);
        down(a);
293 }
    void splay(node*a){
        release(a);
        while(direct(a)<2){
            node*b=a->pr;
            if(!b->pr||direct(b)>1)
                rotate(a);
            else if(direct(a)==direct(b))
                rotate(b),rotate(a);
            else
303         rotate(a),rotate(a);
        }
    }
}

```



```

node*access(node*a){
    node*b=0;
    while(a){
        splay(a);
        if(a->ch[1])
            connect(a->ch[1],a);
        if(b)
            disconnect(b,a);
        setchd(a,b,1);
        b=a;
        a=a->pr;
    }
    return b;
}
void evert(node*a){
    access(a);
    splay(a);
    a->rev=1;
}
int qchain(node*a,node*b,int d){
    access(a);
    node*c=access(b);
    splay(c);
    splay(a);
    int ret=c->val;
    if(d==1){
        if(a!=c)
            gmin(ret,a->mi);
        if(c->ch[1])
            down(c->ch[1]),gmin(ret,c->ch[1]->mi);
    }else if(d==2){
        if(a!=c)
            gmax(ret,a->mx);
        if(c->ch[1])
            down(c->ch[1]),gmax(ret,c->ch[1]->mx);
    }else if(d==3){
        if(a!=c)
            ret+=a->sum;
        if(c->ch[1])
            down(c->ch[1]),ret+=c->ch[1]->sum;
    }
}

```

```

        return ret;
    }
    void mchain(node*a,node*b,int u,int d){
        access(a);
        node*c=access(b);
        splay(c);
        splay(a);
353     if(d==1){
            c->val+=u;
            if(a!=c)
                a->add=u,disconnect(a,c),connect(a,c);
            if(c->ch[1])
                down(c->ch[1]),c->ch[1]->add=u;
        }else if(d==2){
            c->val=u;
            if(a!=c)
363         a->sam=u,disconnect(a,c),connect(a,c);
            if(c->ch[1])
                down(c->ch[1]),c->ch[1]->sam=u;
        }
        update(c);
    }
    int qtree(node*a,int d){
        access(a);
        splay(a);
        int ret=a->val;
373     if(d==1){
            if(a->vir)
                trp.down(a->vir),gmin(ret,a->vir->mi);
        }else if(d==2){
            if(a->vir)
                trp.down(a->vir),gmax(ret,a->vir->mx);
        }else if(d==3){
            if(a->vir)
                trp.down(a->vir),ret+=a->vir->sum;
        }
383     return ret;
    }
    void mtree(node*a,int u,int d){
        access(a);
        splay(a);

```

```

        if(d==1){
            a->val+=u;
            if(a->vir)
                trp.down(a->vir),a->vir->add=u;
        }else if(d==2){
393     a->val=u;
            if(a->vir)
                trp.down(a->vir),a->vir->sam=u;
        }
        update(a);
    }
    void stparent(node*a,node*b){
        access(b);
        if(access(a)!=a){
403     splay(a);
            node*c=a->ch[0];
            down(c);
            while(c->ch[1])
                c=c->ch[1],down(c);
            splay(c);
            c->ch[1]=0;
            update(c);
            access(b);
            splay(b);
            connect(a,b);
413     a->pr=b;
            update(b);
        }
    }
    void build(vector<int>*to,int*we,int rt){
        vector<int>pr(n);
        vector<int>vec;
        queue<int>qu;
        qu.push(rt);
        while(!qu.empty()){
423     int u=qu.front();
            qu.pop();
            vec.push_back(u);
            for(int i=0;i<to[u].size();++i){
                int v=to[u][i];
                if(v!=pr[u])

```

```

        qu.push(v),pr[v]=u;
    }
}
433 for(int i=0;i<n;++i){
    int u=vec[i];
    ns[u]=node(we[u],pr[u]?&ns[0]+pr[u]:0);
}
    for(int i=n-1;i>=0;--i){
        int u=vec[i];
        update(&ns[0]+u);
        if(pr[u])
            connect(&ns[0]+u,&ns[0]+pr[u]);
    }
}
443 };

```

2.9 Skew Heap

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Skew Heap.hpp (1220 bytes, 61 lines)

```

#include<bits/stdc++.h>
using namespace std;
template<class T,class C>struct SkewHeap{
    SkewHeap():
        root(0),siz(0){
    }
7    ~SkewHeap(){
        clear(root);
    }
    struct node{
        node(T _val):
            val(_val){
                ch[0]=ch[1]=0;
            }
            T val;
            node*ch[2];
17 }*root;
    int siz;

```

```

node*merge(node*x,node*y){
    if(!x)
        return y;
    if(!y)
        return x;
    if(C()(y->val,x->val))
        swap(x,y);
    swap(x->ch[0],x->ch[1]=merge(x->ch[1],y));
27     return x;
}
void clear(node*x){
    if(x){
        clear(x->ch[0]);
        clear(x->ch[1]);
        delete x;
    }
}
37 void clear(){
    clear(root);
    root=0;
    siz=0;
}
void push(T a){
    root=merge(root,new node(a));
    ++siz;
}
T top(){
    return root->val;
47 }
void pop(){
    root=merge(root->ch[0],root->ch[1]);
    --siz;
}
void merge(SkewHeap<T,C>&a){
    root=merge(root,a.root);
    a.root=0;
    siz+=a.siz;
    a.siz=0;
57 }
int size(){
    return siz;
}

```

```
    }  
};
```

CHAPTER 3

Graph Algorithms

3.1 Chordality Test

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Chordality Test.hpp (1343 bytes, 42 lines)

```

#include<bits/stdc++.h>
using namespace std;
struct ChordalityTest{
    int n,ns;
    vector<vector<int> >to;
    ChordalityTest(int _n):
        n(_n),ns(n),to(n+1){
    }
9  void add(int u,int v){
        to[u].push_back(v),to[v].push_back(u);
    }
    bool run(){
        vector<int>pos(n+1),idx(n+2),lab(n+1),tab(n+1);
        vector<list<int>>>qu(n);
        for(int i=1;i<=n;++i)
            qu[0].push_back(i);
        for(int b=0,i=1,u=0;i<=n;++i,u=0){
            for(;u?++b,0:1;--b)
19         for(auto j=qu[b].begin();j!=qu[b].end()&&!u;qu[b].erase(j++))
                if(!pos[*j]&&lab[*j]==b)
                    u=*j;
            pos[u]=ns,idx[ns--]=u;
            for(int v:to[u])
                if(!pos[v])
                    b=max(b,++lab[v]),qu[lab[v]].push_back(v);}
        for(int i=1,u=idx[1],v=-1;i<=n;++i,u=idx[i],v=-1){
            for(int w:to[u])
                if(pos[w]>pos[u]&&(v==-1||pos[w]<pos[v]))
29                 v=w;
            if(v!=-1){
                for(int w:to[v])
                    tab[w]=1;
                for(int w:to[u])
                    if(pos[w]>pos[u]&&w!=v&&!tab[w])

```



```

        return false;
        for(int w:to[v])
            tab[w]=0;
    }
39     }
        return true;
    }
};

```

3.2 Dominator Tree

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Dominator Tree.hpp (2916 bytes, 94 lines)

```

#include<bits/stdc++.h>
using namespace std;
struct DominatorTree{
    int n,r;
    vector<vector<int>> >to,rto,chd,rsemi;
    vector<int>dfn,res,prt,rdfn,semi,misemi;
    DominatorTree(int _n,int _r):n(_n),r(_r),to(n+1),rto(n+1),dfn(n+1),res(
8    n+1),prt(n+1),rdfn(1),semi(n+1),misemi(n+1),chd(n+1),rsemi(n+1){
    }
    int fd(int a){
        stack<int>stk;
        for(int b=a;prt[b]!=prt[prt[b]];b=prt[b])
            stk.push(b);
        for(int b;stk.empty()?0:(b=stk.top(),stk.pop(),1);){
            if(dfn[semi[misemi[prt[b]]]]<dfn[semi[misemi[b]]])
                misemi[b]=misemi[prt[b]];
            prt[b]=prt[prt[b]];
        }
18    return prt[a];
    }
    void add(int a,int b){
        to[a].push_back(b);
        rto[b].push_back(a);
    }
    void dfs(){

```

```

stack<pair<int,int> >stk;
semi[r]=r;
for(stk.push(make_pair(r,0));!stk.empty();){
28     int a=stk.top().first,i=stk.top().second;
        stk.pop();
        if(!i)
            dfn[a]=rdfn.size(),rdfn.push_back(a);
        if(i<to[a].size()){
            stk.push(make_pair(a,i+1));
            int b=to[a][i];
            if(!semi[b])
                semi[b]=a, chd[a].push_back(b),
38                stk.push(make_pair(b,0));
        }
    }
    semi[r]=0;
}
void calcsemi(){
    for(int i=1;i<=n;++i)
        prt[i]=i, misemi[i]=i;
    for(int i=rdfn.size()-1;i>=1;--i){
        int a=rdfn[i];
        for(int b:rto[a]){
48            if(!dfn[b])
                continue;
            if(dfn[b]<dfn[a]){
                if(dfn[b]<dfn[semi[a]])
                    semi[a]=b;
            }else{
                int c=fd(b);
                if(dfn[semi[c]]<dfn[semi[a]])
                    semi[a]=semi[c];
                if(dfn[semi[misemi[b]]]<dfn[semi[a]])
58                semi[a]=semi[misemi[b]];
            }
        }
        for(int b:chd[a])
            prt[b]=a;
    }
}
void calcres(){

```

```

        for(int i=1;i<=n;++i)
            prt[i]=i,misemi[i]=i,rsemi[semi[i]].push_back(i);
68    for(int i=rdfn.size()-1;i>=1;--i){
        int a=rdfn[i];
        for(int b:rsemi[a]){
            fd(b);
            int c=misemi[b];
            if(dfn[semi[c]]>dfn[semi[prt[b]]])
                c=prt[b];
            if(semi[c]==semi[b])
                res[b]=semi[b];
            else
78                res[b]=-c;}
        for(int b:chd[a])
            prt[b]=a;
    }
    for(int i=1;i<rdfn.size();++i){
        int a=rdfn[i];
        if(res[a]<0)
            res[a]=res[-res[a]];
    }
}
88    vector<int>run(){
        dfs();
        calcsemi();
        calcres();
        return res;
    }
};

```

3.3 K Shortest Path

Description

Find the length of k shortest path between two vertices in a given weighted directed graph. The path does not need to be loopless. But the edge weights must be non-negative.

Methods

template<class T>KShortestPath<T>::KShortestPath(int n);	
Description	construct an object of KShortestPath
Parameters	Description
T	type of edge weights, be careful since the result can be $\Theta(nkC)$
n	number of vertices
Time complexity	$\Theta(n)$
Space complexity	$\Theta(11n)$
Return value	an object of KShortestPath
template<class T>void KShortestPath<T>::add(int a,int b,T c);	
Description	add a directed weighted edge to the graph
Parameters	Description
a	start vertex of the edge, indexed from one
b	end vertex of the edge, indexed from one
c	weight of the edge, should be non-negative
Time complexity	$\Theta(1)$ (amortized)
Space complexity	$\Theta(1)$ (amortized)
Return value	none
template<class T>T KShortestPath<T>::run(int s,int t,int k);	
Description	find the length of k shortest path
Parameters	Description
s	start vertex of the path, indexed from one
t	end vertex of the path, indexed from one
k	k in 'k shortest path'
Time complexity	$O((n + m) \log n + k \log(nmk))$
Space complexity	$O(n \log n + m + k \log(nm))$
Return value	length of k shortest path from s to t or -1 if it doesn't exist

Fields

Name	Description
------	-------------

Performance

Problem	Constraints	Time	Memory	Date
JDFZ P2978	$N = 10^4, M = 10^5, K = 10^4$	324 ms	14968 kB	2016-02-13

References

Title	Author
堆的可持久化和 k 短路	俞鼎力

Code

K Shortest Path.hpp (5105 bytes, 170 lines)

```
#include<bits/stdc++.h>
using namespace std;
template<class T>struct KShortestPath{
    KShortestPath(int _n):
        n(_n),m(1<<(int)ceil(log2(n)+1e-8)),from(n+1,-1),
6        tov(n+1),wev(n+1),to(n+1),we(n+1),inf(numeric_limits<T>::max()),
        sg(2*m,make_pair(inf,0)),di(n+1,inf),nxt(n+1),chd(n+1),torev(n+1){
    }
    ~KShortestPath(){
        for(int i=0;i<all.size();++i)
            free(all[i]);
    }
    void add(int u,int v,T w){
        tov[v].push_back(u);
        wev[v].push_back(w);
16        to[u].push_back(v);
        we[u].push_back(w);
        torev[v].push_back(to[u].size()-1);
    }
    int upd(T&a,T b,T c){
        if(b!=inf&&c!=inf&&b+c<a){
            a=b+c;
            return 1;
        }
        return 0;
26    }
    void mod(int u,T d){
        for(sg[u+m-1]=make_pair(d,u),u=u+m-1>>1;u;u>>=1)
            sg[u]=min(sg[u<<1],sg[u<<1^1]);
    }
    template<class T2>struct node{
        node(T2 _v):
```

```

        v(_v),s(0),l(0),r(0){
    }
    T2 v;
36   int s;
    node*l,*r;
};
template<class T2>node<T2>*merge(node<T2>*a,node<T2>*b){
    if(!a||!b)
        return a?a:b;
    if(a->v>b->v)
        swap(a,b);
    a->r=merge(a->r,b);
    if(!a->l||a->l->s<a->r->s)
46     swap(a->l,a->r);
    a->s=(a->r?a->r->s:-1)+1;
    return a;
}
template<class T2>node<T2>*mak(T2 v){
    node<T2>*t=(node<T2>*)malloc(sizeof(node<T2>));
    *t=node<T2>(v);
    all.push_back(t);
    return t;
}
56 template<class T2>node<T2>*pmerge(node<T2>*a,node<T2>*b){
    if(!a||!b)
        return a?a:b;
    if(a->v>b->v)
        swap(a,b);
    node<T2>*r=mak(a->v);
    r->l=a->l;
    r->r=pmerge(a->r,b);
    if(!r->l||r->l->s<r->r->s)
        swap(r->l,r->r);
66     r->s=(r->r?r->r->s:-1)+1;
    return r;
}
struct edge{
    edge(T _l,int _v):
        l(_l),v(_v){
    }
    bool operator>(const edge&a){

```

```

        return l>a.l;
    }
76    T l;
    int v;
};
struct edgeheap{
    edgeheap(node<edge>*r):
        root(r){
    }
    bool operator>(const edgeheap&a){
        return root->v.l>a.root->v.l;
    }
86    node<edge>*root;
};
edgeheap merge(edgeheap a,edgeheap b){
    return edgeheap(pmerge(a->root,b->root));
}
edgeheap popmin(edgeheap a){
    return edgeheap(pmerge(a.root->l,a.root->r));
}
node<edgeheap>*popmin(node<edgeheap>*a){
    node<edgeheap>*x=pmerge(a->l,a->r);
96    a=mak(popmin(a->v));
    if(a->v.root)
        x=pmerge(x,a);
    return x;
}
struct path{
    path(int _vp,int _v,T _l,T _d,node<edgeheap>*_c):
        vp(_vp),v(_v),l(_l),d(_d),can(_c){
    }
    bool operator<(const path&a)const{
106    return l>a.l;
    }
    int vp,v;
    T l,d;
    node<edgeheap>*can;
};
T run(int s,int t,int k){
    di[t]=0;
    for(int i=1;i<=n;++i)

```

```

    sg[i+m-1]=make_pair(di[i],i);
116  for(int i=m-1;i>=1;--i)
        sg[i]=min(sg[i<<1],sg[i<<1^1]);
    for(int u=sg[1].second;sg[1].first!=inf;u=sg[1].second){
        mod(u,inf),tre.push_back(u);
        for(int i=0;i<tov[u].size();++i){
            int v=tov[u][i];
            T w=wev[u][i];
            if(upd(di[v],di[u],w))
                mod(v,di[v]),nxt[v]=u,
126         from[v]=torev[u][i];
        }
    }
    for(int i=0;i<tre.size();++i){
        queue<node<edge>*>qu;
        for(int j=0;j<to[tre[i]].size();++j)
            if(di[to[tre[i]][j]]!=inf&&j!=from[tre[i]])
                qu.push(mak(edge(we[tre[i]][j]-di[tre[i]]+di[to[tre[i]][
j]],to[tre[i]][j])));
        for(node<edge>*x,*y;qu.size()>1;)
            x=qu.front(),qu.pop(),y=qu.front(),qu.pop(),
            qu.push(merge(x,y));
136     if(qu.size())
        chd[tre[i]]=pmerge(mak(edgeheap(qu.front()))),chd[nxt[tre[i
]]]);
    else
        chd[tre[i]]=chd[nxt[tre[i]]];
    }
    priority_queue<path>pth;
    if(di[s]==inf)
        return -1;
    pth.push(path(0,s,di[s],0,0));
    for(int i=1;i<k;++i){
146     if(pth.empty())
        return -1;
        path p=pth.top();
        pth.pop();
        if(p.can){
            edge t=p.can->v.root->v;
            pth.push(path(p.vp,t.v,p.l-p.d+t.l,t.l,popmin(p.can)));
        }
    }

```



```

        if(chd[p.v]){
            edge t=chd[p.v]->v.root->v;
156         pth.push(path(p.v,t.v,p.l+t.l,t.l,popmin(chd[p.v])));
        }
    }
    return pth.size()?pth.top().l:-1;
}
T inf;
int n,m;
vector<T>di;
vector<int>nxt,tre,from;
vector<void*>all;
166 vector<node<edgeheap*>>chd;
vector<pair<T,int> >sg;
vector<vector<T> >wev,we;
vector<vector<int> >tov,to,torev;
};

```

3.4 Maximal Clique Count

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Maximal Clique Count.hpp (927 bytes, 34 lines)

```

#include<bits/stdc++.h>
using namespace std;
template<int N>struct MaximalCliqueCount{
    int n,r;
    vector<bitset<N> >e,rht,msk;
    MaximalCliqueCount(int _n):
        n(_n),e(n),rht(n),msk(n),r(0){
    }
10 void add(int u,int v){
    e[u-1][v-1]=e[v-1][u-1]=1;
}
void dfs(int u,bitset<N>cur,bitset<N>can){
    if(cur==can){
        ++r;
        return;
    }
}

```

```

    for(int v=0;v<u;++v)
        if(can[v]&&!cur[v]&&(e[v]&rht[u]&can)==(rht[u]&can))
            return;
20    for(int v=u+1;v<n;++v)
        if(can[v])
            dfs(v,cur|msk[v],can&e[v]);
    }
    int run(){
        for(int i=1;i<=n;++i){
            rht[i-1]=bitset<N>(string(n-i,'1')+string(i,'0'));
            msk[i-1]=bitset<N>(1)<<i-1;
            e[i-1]|=msk[i-1];
        }
30    for(int i=0;i<n;++i)
        dfs(i,msk[i],e[i]);
    return r;
}
};

```

3.5 Maximal Planarity Test

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Maximal Planarity Test.hpp (5195 bytes, 165 lines)

```

#include<bits/stdc++.h>
using namespace std;
struct MaximalPlanarityTesting{
    int n,m;
    vector<set<int> >to2;
6    vector<vector<int> >to;
    vector<int>dec,rmd,mrk,invc,rt;
    vector<list<int>::iterator>dpos,pos;
    bool order(int v1,int v2,int vn){
        rt[0]=v1;
        rt[1]=v2;
        rt[n-1]=vn;
        fill(invc.begin(),invc.end(),0);
        invc[v1]=1;
        invc[v2]=1;
    }
};

```

```

16      invc[vn]=1;
      list<int>deg;
      dpos[vn]=deg.insert(deg.begin(),vn);
      fill(dec.begin(),dec.end(),0);
      dec[v1]=2;
      dec[v2]=2;
      dec[vn]=2;
      for(int i=n-1;i>=2;--i){
          if(deg.empty())
              return false;
26      int v=*deg.begin();
      deg.erase(deg.begin());
      invc[v]=-1;
      rt[i]=v;
      for(int u:to[v]){
          if(invc[u]==1){
              if(u!=v1&&u!=v2&&dec[u]==2)
                  deg.erase(dpos[u]);
              --dec[u];
              if(u!=v1&&u!=v2&&dec[u]==2)
36                  dpos[u]=deg.insert(deg.begin(),u);
          }else if(invc[u]==0)
              invc[u]=2;
      }
      for(int u:to[v])
          if(invc[u]==2)
              for(int w:to[u])
                  if(invc[w]==1){
                      if(w!=v1&&w!=v2&&dec[w]==2)
                          deg.erase(dpos[w]);
46                      ++dec[w];
                      if(w!=v1&&w!=v2&&dec[w]==2)
                          dpos[w]=deg.insert(deg.begin(),w);
                      ++dec[u];
                  }else if(invc[w]==2)
                      ++dec[u];
      for(int u:to[v]){
          if(invc[u]==2){
              invc[u]=1;
              if(dec[u]==2)
56                  dpos[u]=deg.insert(deg.begin(),u);

```

```

    }
    }
    }
    return true;
}
bool embed(){
    list<int>ext;
    int mker=0;
    fill(mrk.begin(),mrk.end(),0);
66 pos[rt[1]]=ext.insert(ext.begin(),rt[1]);
    pos[rt[2]]=ext.insert(ext.begin(),rt[2]);
    pos[rt[0]]=ext.insert(ext.begin(),rt[0]);
    fill(rmd.begin(),rmd.end(),0);
    rmd[rt[1]]=1;
    rmd[rt[2]]=1;
    rmd[rt[0]]=1;
    for(int i=3;i<n;++i){
        int v=rt[i];
        rmd[v]=1;
76 vector<int>can;
        ++mker;
        for(int u:to[v])
            if(rmd[u])
                mrk[u]=mker,can.push_back(u);
        int start=-1,end=-1;
        for(int u:can){
            list<int>::iterator it=pos[u];
            if(it==list<int>::iterator())
                return false;
86 if(it==ext.begin()){
                if(start!=-1)
                    return false;
                start=u;
            }else{
                list<int>::iterator tmp=it;
                if(mrk[--tmp]!=mker){
                    if(start!=-1)
                        return false;
                    start=u;
                }
            }
96 }
    }
}

```

```

list<int>::iterator tmp=it;++tmp;
if(tmp==ext.end()){
    if(end!=-1)
        return false;
    end=u;
}
else{
    if(mrk[*tmp]!=mker){
        if(end!=-1)
            return false;
        end=u;
    }
}
}
if(start==-1||end==-1)
    return false;
for(int u:can)
    if(u!=start&&u!=end)
        ext.erase(pos[u]),pos[u]=list<int>::iterator();
116 pos[v]=ext.insert(pos[end],v);
}
return true;
}
bool istri(int u,int v,int w){
    return to2[u].count(v)&&to2[v].count(w)&&to2[w].count(u);
}
MaximalPlanarityTesting(int _n):
    n(_n),to(n),to2(n),m(0),rt(n),invc(n),dec(n),dpos(n),pos(n),rmd(n),
mrk(n){
}
126 void add(int u,int v){
    to[u-1].push_back(v-1);
    to[v-1].push_back(u-1);
    to2[u-1].insert(v-1);
    to2[v-1].insert(u-1);++m;
}
bool run(){
    if(n==1&&m==0)
        return true;
    if(n==2&&m==1)
        return true;
136 if(n==3&&m==3)
```

```

        return true;
    if(n<=3)
        return false;
    if(m!=3*n-6)
        return false;
    int v1;
    for(v1=0;v1<n;++v1)
        if(to[v1].size()<3)
            return false;
    for(v1=0;v1<n;++v1)
        if(to[v1].size()<=5)
            break;
    if(v1>=n)
        return false;
    int v2=to[v1].back();
    for(int i=0;i+1<to[v1].size();++i){
        int vn=to[v1][i];
        if(istri(v1,v2,vn)){
            if(!order(v1,v2,vn))
                continue;
            if(!embed())
                continue;
            return true;
        }
    }
    return false;
}
};

```

3.6 Maximum Flow

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Maximum Flow.hpp (2311 bytes, 79 lines)

```

#include<bits/stdc++.h>
using namespace std;
template<class T>struct MaximumFlow{
    struct edge{
5        int v;

```

```

    T c,l;
    edge(int _v,T _c):
        v(_v),c(_c),l(_c){
    }
};
int n,src,snk;
vector<edge>egs;
vector<vector<int>> >bge;
vector<int>hei,gap,cur,frm;
15 MaximumFlow(int _n,int _src,int _snk):
    bge(_n),hei(_n,_n),gap(_n+1),n(_n),cur(_n),frm(_n),src(_src-1),snk(
    _snk-1){
    }
    void lab(){
        hei[snk]=0;
        queue<int>qu;
        qu.push(snk);
        for(int u;qu.empty()?0:(u=qu.front(),qu.pop(),1);)
            for(int i=0;i<bge[u].size();++i){
                edge&e=egs[bge[u][i]],&ev=egs[bge[u][i]^1];
                25 if(ev.c>0&&hei[e.v]==n)
                    hei[e.v]=hei[u]+1,qu.push(e.v);
            }
        for(int i=0;i<n;++i)
            ++gap[hei[i]];
    }
    T aug(){
        T f=0;
        for(int u=snk;u!=src;u=egs[frm[u]^1].v)
            if(f<=0||f>egs[frm[u]].c)
                f=egs[frm[u]].c;
        35 for(int u=snk;u!=src;u=egs[frm[u]^1].v)
            egs[frm[u]].c-=f,egs[frm[u]^1].c+=f;
        return f;
    }
    void add(int u,int v,T c){
        bge[u-1].push_back(egs.size());
        egs.push_back(edge(v-1,c));
        bge[v-1].push_back(egs.size());
        egs.push_back(edge(u-1,0));
        45 }

```

```

T run(){
    lab();
    T r=0;
    for(int u=src;hei[src]!=n;){
        if(u==snk)
            r+=aug(),u=src;
        int f=0;
        for(int i=cur[u];i<bge[u].size();++i){
            edge&e=egs[bge[u][i]];
55         if(e.c>0&&hei[u]==hei[e.v]+1){
                f=1;
                frm[e.v]=bge[u][i];
                u=e.v;
                break;
            }
        }
        if(!f){
            int mh=n-1;
            for(int i=0;i<bge[u].size();++i){
65                 edge&e=egs[bge[u][i]];
                if(e.c>0&&mh>hei[e.v])
                    mh=hei[e.v];
            }
            if(!--gap[hei[u]])
                break;
            ++gap[hei[u]=mh+1];
            cur[u]=0;
            if(u!=src)
                u=egs[frm[u]^1].v;
75         }
    }
    return r;
}
};

```

3.7 Maximum Matching

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Maximum Matching.hpp (3123 bytes, 112 lines)

```

1  #include<bits/stdc++.h>
    using namespace std;
    struct MaximumMatching{
        int n;
        vector<int>res,nxt,mrk,vis,top,prt,rnk;
        vector<vector<int> >to;
        queue<int>qu;
        MaximumMatching(int _n):
            n(_n),res(n+1),nxt(n+1),mrk(n+1),vis(n+1),top(n+1),to(n+1),prt(n+1)
        ,rnk(n+1){
        }
11  int fd(int x){
        return x==prt[x]?x:prt[x]=fd(prt[x]);
    }
    void lk(int x,int y){
        if(rnk[x=fd(x)]>rnk[y=fd(y)])
            prt[y]=x;
        else if(rnk[x]<rnk[y])
            prt[x]=y;
        else
            prt[x]=y,++rnk[y];
21  }
    int lca(int x,int y){
        static int t;
        ++t;
        for(;;swap(x,y))
            if(x){
                x=top[fd(x)];
                if(vis[x]==t)
                    return x;
                vis[x]=t;
31  if(res[x])
                    x=nxt[res[x]];
                else
                    x=0;
            }
    }
    void uni(int x,int p){
        for(;fd(x)!=fd(p);){
            int y=res[x],z=nxt[y];

```

```

    if(fd(z)!=fd(p))
41      nxt[z]=y;
    if(mrk[y]==2)
        mrk[y]=1,qu.push(y);
    if(mrk[z]==2)
        mrk[z]=1,qu.push(z);
    int t=top[fd(z)];
    lk(x,y);
    lk(y,z);
    top[fd(z)]=t;
    x=z;
51  }
}
void aug(int s){
    for(int i=1;i<=n;++i)
        nxt[i]=0,mrk[i]=0,top[i]=i,prt[i]=i,rnk[i]=0;
    mrk[s]=1;
    qu=queue<int>();
    for(qu.push(s);!qu.empty();){
        int x=qu.front();
        qu.pop();
61      for(int i=0;i<to[x].size();++i){
          int y=to[x][i];
          if(res[x]==y || fd(x)==fd(y) || mrk[y]==2)
              continue;
          if(mrk[y]==1){
              int z=lca(x,y);
              if(fd(x)!=fd(z))
                  nxt[x]=y;
              if(fd(y)!=fd(z))
                  nxt[y]=x;
71      uni(x,z);
              uni(y,z);
          }else if(!res[y]){
              for(nxt[y]=x;y;){
                  int z=nxt[y],mz=res[z];
                  res[z]=y;
                  res[y]=z;
                  y=mz;
              }
              return;
          }
      }
  }

```

```

81         }else{
            nxt[y]=x;
            mrk[res[y]]=1;
            qu.push(res[y]);
            mrk[y]=2;
        }
    }
}
}
void add(int x,int y){
91     to[x].push_back(y);
    to[y].push_back(x);
}
int run(){
    for(int i=1;i<=n;++i)
        if(!res[i])
            for(int j=0;j<to[i].size();++j)
                if(!res[to[i][j]]){
                    res[to[i][j]]=i;
                    res[i]=to[i][j];
101                break;
                }
    for(int i=1;i<=n;++i)
        if(!res[i])
            aug(i);
    int r=0;
    for(int i=1;i<=n;++i)
        if(res[i])
            ++r;
    return r/2;
111 }
};

```

3.8 Minimum Cost Maximum Flow

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Minimum Cost Maximum Flow.hpp (2278 bytes, 82 lines)

```
#include<bits/stdc++.h>
```

```

using namespace std;
template<class F=int,class C=int>struct MinimumCostMaximumFlow{
    struct edge{
        edge(int _v,F _c,C _w):
            v(_v),c(_c),w(_w){
        }
8      int v;
        F c;
        C w;
    };
    MinimumCostMaximumFlow(int _n,int _src,int _snk,F _all):
        n(_n),src(_src-1),snk(_snk-1),bg(_n),vis(n),dis(n),all(_all),flow
        (0),cost(0){}
    void add(int u,int v,F c,C w){
        bg[u-1].push_back(eg.size());
        eg.push_back(edge(v-1,c,w));
        bg[v-1].push_back(eg.size());
18      eg.push_back(edge(u-1,0,-w));
    }
    int spfa(){
        vector<int>in(n,0);
        queue<int>qu;
        fill(vis.begin(),vis.end(),0);
        dis[src]=0;
        vis[src]=in[src]=1;
        qu.push(src);
        while(!qu.empty()){
28          int u=qu.front();
          qu.pop();
          in[u]=0;
          for(int i=0;i<bg[u].size();++i){
              edge&e=eg[bg[u][i]];
              if(e.c!=0&&(!vis[e.v]||dis[u]+e.w<dis[e.v])){
                  dis[e.v]=dis[u]+e.w;
                  vis[e.v]=1;
                  if(!in[e.v]){
38                      in[e.v]=1;
                      qu.push(e.v);
                  }
              }
          }
        }
    }
}

```

```

    }
    return vis[snk]&&dis[snk]<0;
}
F dfs(int u,F f){
    if(u==snk)
        return f;
48    F g=f;
    vis[u]=1;
    for(int i=0;i<bg[u].size();++i){
        edge&e=eg[bg[u][i]],&ev=eg[bg[u][i]^1];
        if(e.c!=0&&dis[e.v]==dis[u]+e.w&&!vis[e.v]){
            F t=dfs(e.v,min(g,e.c));
            g-=t;
            e.c-=t;
            ev.c+=t;
            cost+=t*e.w;
58            if(g==0)
                return f;
        }
    }
    return f-g;
}
pair<F,C>run(){
    while(all!=0&&spfa()){
        F t;
        do{
68            fill(vis.begin(),vis.end(),0);
            flow+=(t=dfs(src,all));
            all-=t;
        }while(t!=0);
    }
    return make_pair(flow,cost);
}
int n,src,snk;
vector<vector<int> >bg;
vector<edge>eg;
78 vector<int>vis;
vector<C>dis;
F all,flow;
C cost;
};

```

3.9 Minimum Spanning Arborescence

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Minimum Spanning Arborescence.hpp (1933 bytes, 64 lines)

```

#include<bits/stdc++.h>
using namespace std;
template<class T>struct MinimumSpanningArborescence{
    struct eg{
        int u,v;
        T w;
    };
8   int n,rt;
    vector<eg>egs;
    vector<int>vi,in,id;
    vector<T>inw;
    MinimumSpanningArborescence(int _n,int _rt):
        n(_n),rt(_rt),vi(n+1),in(n+1),inw(n+1),id(n+1){
    }
    void add(int u,int v,T w){
        eg e;
        e.u=u;
18    e.v=v;
        e.w=w;
        egs.push_back(e);
    }
    T run(){
        int nv=0;
        for(T r=0;;n=nv,nv=0,rt=id[rt]){
            for(int i=1;i<=n;++i)
                in[i]=-1;
            for(int i=0;i<egs.size();++i)
28    if(egs[i].u!=egs[i].v&&(in[egs[i].v]==-1||egs[i].w<inw[egs[
i].v]))
                in[egs[i].v]=egs[i].u,inw[egs[i].v]=egs[i].w;
            for(int i=1;i<=n;++i)
                if(i!=rt&&in[i]==-1)
                    return numeric_limits<T>::max();
            for(int i=1;i<=n;++i){
                if(i!=rt)

```

```

        r+=inw[i];
        id[i]=-1,vi[i]=0;
    }
38   for(int i=1;i<=n;++i)
        if(i!=rt&&!vi[i]){
            int u=i;
            do{
                vi[u]=i;
                u=in[u];
            }while(!vi[u]&&u!=rt);
            if(u!=rt&&vi[u]==i){
                int v=u;
                ++nv;
48             do{
                id[v]=nv;
                v=in[v];
            }while(v!=u);
        }
    }
    if(nv==0)
        return r;
    for(int i=1;i<=n;++i)
        if(id[i]==-1)
            id[i]=++nv;
58   for(int i=0;i<egs.size();++i)
        egs[i].w-=inw[egs[i].v],egs[i].u=id[egs[i].u],
        egs[i].v=id[egs[i].v];
    }
}
};

```

3.10 Minimum Spanning Tree

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Minimum Spanning Tree.hpp (1049 bytes, 44 lines)

```

#include<bits/stdc++.h>
using namespace std;
template<class T,class C=less<T> >struct MinimumSpanningTree{

```

```

    struct edge{
        T w;
        int u,v;
        int operator<(const edge&b)const{
            return C()(w,b.w);
        }
    };
    int n;
    vector<edge>egs;
    vector<int>pr;
    MinimumSpanningTree(int _n):
        n(_n),pr(n+1){
16    }
    void add(int u,int v,T w){
        edge e;
        e.u=u;
        e.v=v;
        e.w=w;
        egs.push_back(e);
    }
    int fd(int x){
26    return x==pr[x]?x:pr[x]=fd(pr[x]);
    }
    void lk(int x,int y){
        pr[fd(x)]=y;
    }
    pair<T,vector<edge> >run(){
        vector<edge>ret;
        T sum=0;
        sort(egs.begin(),egs.end());
        for(int i=1;i<=n;++i)
            pr[i]=i;
36    for(int i=0;i<egs.size();++i){
        int u=egs[i].u,v=egs[i].v;
        T w=egs[i].w;
        if(fd(u)!=fd(v))
            lk(u,v),ret.push_back(egs[i]),sum+=w;
        }
        return make_pair(sum,ret);
    }
};

```

3.11 Shortest Path

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Shortest Path.hpp (1293 bytes, 45 lines)

```

#include<bits/stdc++.h>
using namespace std;
template<class T>struct ShortestPath{
    int n,m;
    vector<vector<int> >to;
6    vector<vector<T> >we;
    T inf;
    vector<pair<T,int> >sg;
    vector<T>di;
    ShortestPath(int _n):
        n(_n),m(1<<(int)ceil(log2(n)+1e-8)),to(n+1),we(n+1),inf(
        numeric_limits<T>::max()),sg(2*m,make_pair(inf,0)),di(n+1,inf){
    }
    void set(int u,T d){
        di[u]=d;
    }
16    void add(int u,int v,T w){
        to[u].push_back(v);
        we[u].push_back(w);
    }
    int upd(T&a,T b,T c){
        if(b!=inf&&c!=inf&&b+c<a){
            a=b+c;
            return 1;
        }
        return 0;
26    }
    void mod(int u,T d){
        for(sg[u+m-1]=make_pair(d,u),u=(u+m-1)>>1;u>=>1)
            sg[u]=min(sg[u<<1],sg[u<<1^1]);
    }
    vector<T>run(){
        for(int i=1;i<=n;++i)
            sg[i+m-1]=make_pair(di[i],i);
        for(int i=m-1;i>=1;--i)

```

```

    sg[i]=min(sg[i<<1],sg[i<<1^1]);
36   for(int u=sg[1].second;sg[1].first!=inf?(mod(u,inf),1):0;u=sg[1].
      second)
      for(int i=0;i<to[u].size();++i){
          int v=to[u][i];
          T w=we[u][i];
          if(upd(di[v],di[u],w))
              mod(v,di[v]);
      }
      return di;
  }
};

```

3.12 Steiner Tree

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Steiner Tree.hpp (1745 bytes, 56 lines)

```

#include<bits/stdc++.h>
using namespace std;
template<class T>struct SteinerTree{
    int n,k,z;
5   T inf=numeric_limits<T>::max();
    vector<vector<T> >wei,dp;
    vector<int>im;
    SteinerTree(int _n):
        n(_n),k(0),wei(n+1,vector<T>(n+1,inf)),im(n+1){
    }
    void set(int u){
        if(!im[u])
            im[z=u]=++k;
    }
15   void add(int u,int v,T w){
        wei[u][v]=wei[v][u]=min(w,wei[u][v]);
    }
    int upd(T&a,T b,T c){
        if(b!=inf&&c!=inf&&b+c<a){
            a=b+c;
            return 1;
        }
    }
};

```

```

    }
    return 0;
}
25 int ins(int s,int u){
    return im[u]&&((s>>im[u]-1)&1);
}
T run(){
    for(int l=1;l<=n;++l)
        for(int i=1;i<=n;++i)
            for(int j=1;j<=n;++j)
                upd(wei[i][j],wei[i][l],wei[l][j]);
    dp=vector<vector<T>>>(1<<k-1,vector<T>(n+1,inf));
    fill(begin(dp[0]),end(dp[0]),0);
35 for(int s=1;s<(1<<k-1);++s){
    queue<int>qu;
    vector<int>in(n+1);
    for(int u=1;u<=n;++u){
        if(ins(s,u))
            continue;
        qu.push((u));
        in[u]=1;
        for(int t=(s-1)&s;t=(t-1)&s)
            upd(dp[s][u],dp[t][u],dp[s^t][u]);
45 for(int v=1;v<=n;++v)
        if(ins(s,v))
            upd(dp[s][u],dp[s^(1<<im[v]-1)][v],wei[u][v]);
    }
    for(int u;qu.empty()?0:(u=qu.front(),qu.pop(),in[u]=0,1);)
        for(int v=1;v<=n;++v)
            if(!ins(s,v)&&upd(dp[s][v],dp[s][u],wei[u][v])&&!in[v])
                in[v]=1,qu.push(v);
    }
    return k?dp[(1<<k-1)-1][z]:0;
55 }
};

```

3.13 Virtual Tree

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Virtual Tree.hpp (2375 bytes, 77 lines)

```

#include<bits/stdc++.h>
using namespace std;
struct VirtualTree{
4   int n,r,l;
    vector<vector<int> >to,vto,up;
    vector<int>lst,dp,dfn,edf,imp;
    VirtualTree(int _n,int _r):
        n(_n),r(_r),l(ceil(log2(n)+1e-8)),to(n+1),vto(n+1),up(n+1,vector<
int>(l+1)),dp(n+1),dfn(n+1),edf(n+1),imp(n+1){
    }
    void add(int u,int v){
        to[u].push_back(v);
        to[v].push_back(u);
    }
14   void vadd(int u,int v){
        vto[u].push_back(v);
    }
    int lca(int u,int v){
        if(dp[u]<dp[v])
            swap(u,v);
        for(int i=0;i<=l;++i)
            if(((dp[u]-dp[v])>>i)&1)
                u=up[u][i];
        if(u==v)
24         return u;
        for(int i=l;i>=0;--i)
            if(up[u][i]!=up[v][i])
                u=up[u][i],v=up[v][i];
        return up[u][0];
    }
    void dfs(int u){
        dfn[u]=++dfn[0];
        for(int i=1;i<=l;++i)
            up[u][i]=up[up[u][i-1]][i-1];
34        for(int i=0;i<to[u].size();++i){
            int v=to[u][i];
            if(v!=up[u][0])
                up[v][0]=u,dp[v]=dp[u]+1,dfs(v);
        }
        edf[u]=dfn[0];

```

```

    }
    void build(){
        dfs(r);
    }
44 void run(int*a,int m){
        for(int i=0;i<lst.size();++i)
            imp[lst[i]]=0,vto[lst[i]].clear();
        vector<pair<int,int> >b(m+1);
        for(int i=1;i<=m;++i)
            imp[a[i]]=1,b[i]=make_pair(dfn[a[i]],a[i]);
        sort(b.begin()+1,b.end());
        vector<int>st(1,r);
        lst=st;
        for(int i=1;i<=m;++i){
54         int u=b[i].second,v=st.back();
            if(u==r)
                continue;
            if(dfn[u]<=edf[v])
                st.push_back(u);
            else{
                int w=lca(u,v);
                while(st.size()>=2&&dp[st[st.size()-2]]>=dp[w]){
                    vadd(st[st.size()-2],*st.rbegin());
                    lst.push_back(*st.rbegin()),st.pop_back();
64                 }
                if(st.size()>=2&&w!=st[st.size()-1]){
                    vadd(w,*st.rbegin()),lst.push_back(*st.rbegin());
                    st.pop_back(),st.push_back(w);
                }
                st.push_back(u);
            }
        }
        while(st.size()>=2){
74         vadd(st[st.size()-2],*st.rbegin());
            lst.push_back(*st.rbegin()),st.pop_back();
        }
    }
};

```

CHAPTER 4

Number Theory

4.1 Discrete Logarithm

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Discrete Logarithm.hpp (1819 bytes, 74 lines)

```

#include<bits/stdc++.h>
using namespace std;
3 namespace DiscreteLogarithm{
    typedef long long T;
    int ti[1<<16],va[1<<16],mp[1<<16],nx[1<<16],hd[1<<16],tm,nw;
    void ins(int x,int v){
        int y=x&65535;
        if(ti[y]!=tm)
            ti[y]=tm,hd[y]=0;
        for(int i=hd[y];i;i=nx[i])
            if(va[i]==x){
13             mp[i]=v;
                return;
            }
        va[++nw]=x;
        mp[nw]=v;
        nx[nw]=hd[y];
        hd[y]=nw;
    }
    int get(int x){
        int y=x&65535;
        if(ti[y]!=tm)
23         ti[y]=tm,hd[y]=0;
        for(int i=hd[y];i;i=nx[i])
            if(va[i]==x){
                return mp[i];
            }
        return -1;
    }
    T pow(T a,T b,T c){
        T r=1;
        for(;b;b&1?r=r*a%c:0,b>>=1,a=a*a%c);
33     return r;
    }
    T gcd(T a,T b){

```



```

        return b?gcd(b,a%b):a;
    }
    void exg(T a,T b,T&x,T&y){
        if(!b)
            x=1,y=0;
        else
            exg(b,a%b,y,x),y-=a/b*x;
43    }
    T inv(T a,T b){
        T x,y;
        exg(a,b,x,y);
        return x+b;
    }
    T bgs(T a,T b,T c){
        ++tm;
        nw=0;
        T m=sqrt(c);
53    for(T i=m-1,u=pow(a,i,c),v=inv(a,c);i>=0;--i,u=u*v%c)
        ins(u,i);
        for(T i=0,u=1,v=inv(pow(a,m,c),c);i*m<=c;++i,u=u*v%c){
            T t=u*b%c,j;
            if((j=get(t))!=-1)
                return i*m+j;
        }
        return -1;
    }
    T run(T a,T b,T c){
63    T u=1,t=0;
        a=(a%c+c)%c;
        b=(b%c+c)%c;
        for(int i=0;i<32;++i)
            if(pow(a,i,c)==b)
                return i;
        for(T d;(d=gcd(a,c))!=1;++t,u=a/d*u%c,b/=d,c/=d)
            if(b%d)
                return -1;
        return (u=bgs(a,b*inv(u,c)%c,c))<0?-1:u+t;
73    }
}

```

4.2 Integer Factorization (Pollard's Rho Algorithm)

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Integer Factorization (Pollard's Rho Algorithm).hpp (2848 bytes, 93 lines)

```
#include<bits/stdc++.h>
using namespace std;
namespace IntegerFactorization{
    template<class T>T mul(T x,T y,T z){
        if(typeid(T)==typeid(int))
6         return (long long)x*y%z;
        else if(typeid(T)==typeid(long long))
            return (x*y-(T)(((long double)x*y+0.5)/z)*z+z)%z;
        else
            return x*y%z;
    }
    template<class T>T pow(T a,T b,T c){
        T r=1;
        for(;b;b&&1?r=mul(r,a,c):0,b>>=1,a=mul(a,a,c));
        return r;
    }
16   template<class T>int chk(T a,int c=10){
        if(a==2)
            return 1;
        if(a%2==0||a<2)
            return 0;
        static int pi[]={2,7,61},pl
[ ]={2,325,9375,28178,450775,9780504,1795265022};
        if(typeid(T)==typeid(int))
            c=3;
        else if(typeid(T)==typeid(long long))
26         c=7;
        T u=a-1,t=0,p=1;
        for(;u%2==0;u/=2,++t);
        for(int i=0;i<c;++i){
            if(typeid(T)==typeid(int))
                p=pi[i]%a;
            else if(typeid(T)==typeid(long long))
                p=pl[i]%a;
            else
```

```

36         p=(p*29+7)%a;
        if(!p||p==1||p==a-1)
            continue;
        T x=pow(p,u,a);
        if(x==1)
            continue;
        for(int j=0;x!=a-1&&j<t;++j){
            x=mul(x,x,a);
            if(x==1)
                return 0;
        }
46        if(x==a-1)
            continue;
        return 0;
    }
    return 1;
}
template<class T>T gcd(T a,T b){
    if(a<0)
        a=-a;
    if(b<0)
        b=-b;
56    return b?gcd(b,a%b):a;
}
template<class T>T rho(T a,T c){
    T x=double(rand())/RAND_MAX*(a-1),y=x;
    for(int i=1,k=2;;){
        x=(mul(x,x,a)+c)%a;
        T d=gcd(y-x,a);
        if(d!=1&&d!=a)
            return d;
66        if(y==x)
            return a;
        if(++i==k)
            y=x,k=2*k;
    }
}
template<class T>vector<pair<T,int> >run(T a){
    if(a==1)
        return vector<pair<T,int> >();
    if(chk(a))

```

```

76     return vector<pair<T,int> >(1,make_pair(a,1));
    T b=a;
    while((b=rho(b,T(double(rand())/RAND_MAX*(a-1))))==a);
    vector<pair<T,int> >u=run(b),v=run(a/b),r;
    for(int pu=0,pv=0;pu<u.size()||pv<v.size();){
        if(pu==u.size())
            r.push_back(v[pv++]);
        else if(pv==v.size())
            r.push_back(u[pu++]);
        else if(u[pu].first==v[pv].first)
86         r.push_back(make_pair(u[pu].first,(u[pu].second+v[pv].second
        )),++pu,++pv;
        else if(u[pu].first>v[pv].first)
            r.push_back(v[pv++]);
        else
            r.push_back(u[pu++]);}
    return r;
}
}

```

4.3 Integer Factorization (Shanks' Square Forms Factorization)

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Integer Factorization (Shanks' Square Forms Factorization).hpp (4675 bytes, 147 lines)

```

#include<bits/stdc++.h>
using namespace std;
namespace IntegerFactorization{
    typedef long long ll;
    typedef unsigned long long ull;
    ll lim=3689348814694258326ll;
7    ull srt(const ull&a){
        ull b=sqrt(a);
        b-=b*b>a;
        return b+=(b+1)*(b+1)<=a;
    }
    int sqr(const ull&a,ll&b){

```

```

        b=srt(a);
        return b*b==a;
    }
17  ull gcd(const ull&a,const ull&b){
        return b?gcd(b,a%b):a;
    }
    ll amb(ll a,const ll&B,const ll&dd,const ll&D){
        for(ll q=(dd+B/2)/a,b=q*a*2-B,c=(D-b*b)/4/a,qc,qcb,a0=a,b0=a,b1=b,
c0=c;;b1=b,c0=c){
            if(c0>dd)
                qcb=c0-b,b=c0+qcb,c=a-qcb;
            else{
                q=(dd+b/2)/c0;
                if(q==1)
                    qcb=c0-b,b=c0+qcb,c=a-qcb;
27             else
                qc=q*c0,qcb=qc-b,b=qc+qcb,c=a-q*qcb;
            }
            if(a=c0,b==b1)
                break;
            if(b==b0&&a==a0)
                return 0;
        }
        return a&1?a:a>>1;
    }
37  ull fac(const ull&n){
        if(n&1^1)
            return 2;
        if(n%3==0)
            return 3;
        if(n%5==0)
            return 5;
        if(srt(n)*srt(n)==n)
            return srt(n);
        static ll d1,d2,a1,b1,c1,dd1,L1,a2,b2,c2,dd2,L2,a,q,c,qc,qcb,D1,D2,
b11[1<<19],b12[1<<19];
47     int p1=0,p2=0,ac1=1,ac2=1,j,nm4=n&3;
        if(nm4==1)
            D1=n,D2=5*n,d2=srt(D2),dd2=d2/2+d2%2,b2=(d2-1)|1;
        else
            D1=3*n,D2=4*n,dd2=srt(D2),d2=dd2*2,b2=d2;

```

```

    d1=srt(D1),b1=(d1-1)|1,c1=(D1-b1*b1)/4,c2=(D2-b2*b2)/4,L1=srt(d1),
    L2=srt(d2),dd1=d1/2+d1%2;
    for(int i=a1=a2=1;ac1||ac2;++i){
        #define m(t)\
        if(ac##t){\
            c=c##t;\
57         q=c>dd##t?1:(dd##t+b##t/2)/c;\
            if(q==1)\
                qcb=c-b##t,b##t=c+qcb,c##t=a##t-qcb;\
            else\
                qc=q*c,qcb=qc-b##t,b##t=qc+qcb,c##t=a##t-q*qcb;\
            if((a##t=c)<=L##t)\
                bl##t[p##t++]=a##t;\
        }
        m(1)m(2)
        if(i&1)
67         continue;
        #define m(t)\
        if((ac##t=ac##t&a##t!=1)&&sq(r(a##t,a))){\
            if(a<=L##t)\
                for(j=0;j<p##t;j++)\
                    if(a==bl##t[j]){
                        a=0;\
                        break;\
                    }\
77         if(a>0){\
            if((q=gcd(a,b##t))>1)\
                return q*q;\
            q=amb(a,b##t,dd##t,D##t);\
            if(nm4==5-2*t&&(q=amb(a,b##t,dd##t,D##t))%(2*t+1)==0)\
                q/=2*t+1;\
            if(q>1)\
                return q;\
        }\
    }
    m(1)m(2)
    #undef m
87 }
    for(int i=3;;i+=2)
        if(n%i==0)
            return i;

```

```

}
11 mul(const ll&x,const ll&y,const ll&z){
    return(x*y-((ll)(((long double)x*y+0.5)/z)*z+z)%z;
}
97 11 pow(ll a,ll b,const ll&c){
    ll r=1;
    for(;b;b&1?r=mul(r,a,c):0,b>>=1,a=mul(a,a,c));
    return r;
}
11 int chk(const ll&a){
    if(a==2)
        return 1;
    if(a%2==0||a<2)
        return 0;
107 static int pf[]={2,325,9375,28178,450775,9780504,1795265022};
    ll u=a-1,t=0,p;
    for(;u%2==0;u/=2,++t);
    for(int i=0;i<7;++i){
        p=pf[i]%a;
        if(!p||p==a-1)
            continue;
        ll x=pow(p,u,a);
        if(x==1)
            continue;
        for(int j=0;x!=a-1&&j<t;++j){
            x=mul(x,x,a);
            if(x==1)
                return 0;
        }
        if(x==a-1)
            continue;
        return 0;
    }
    return 1;
}
117 }
127 vector<pair<ll,int> >run(const ll&a){
    if(a==1)
        return vector<pair<ll,int> >();
    if(chk(a))
        return vector<pair<ll,int> >(1,make_pair(a,1));
    ll b=fac(a);

```

```

vector<pair<ll,int> >u=run(b),v=run(a/b),r;
for(int pu=0,pv=0;pu<u.size()||pv<v.size();){
    if(pu==u.size())
        r.push_back(v[pv++]);
    else if(pv==v.size())
        r.push_back(u[pu++]);
    else if(u[pu].first==v[pv].first)
        r.push_back(make_pair(u[pu].first,(u[pu].second+v[pv].second
137 )),++pu,++pv;
    else if(u[pu].first>v[pv].first)
        r.push_back(v[pv++]);
    else
        r.push_back(u[pu++]);}
return r;
}
147 }
```

4.4 Modular Integer

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Modular Integer.hpp (2886 bytes, 98 lines)

```

#include<bits/stdc++.h>
using namespace std;
3  template<class T>struct ModularInteger{
    ModularInteger(T t=0):
        v(t){
            if(v<0||v>=p)
                v=(v%p+p)%p;
        }
    ModularInteger<T>&operator=(T a){
        v=a;
        if(v<0||v>=p)
            v%=p;
13    return*this;
    }
    ModularInteger<T>operator-(){
        return v?p-v:0;
    }
}
```



```

    ModularInteger<T>&operator+=(ModularInteger<T>a){
        return*this=*this+a;
    }
    ModularInteger<T>&operator--=(ModularInteger<T>a){
        return*this=*this-a;
23    }
    ModularInteger<T>&operator*=(ModularInteger<T>a){
        return*this=*this*a;
    }
    ModularInteger<T>&operator/=(ModularInteger<T>a){
        return*this=*this/a;
    }
    T v;
    static T p;
};
33 template<class T>ModularInteger<T>pow(ModularInteger<T>a,long long b){
    ModularInteger<T>r(1);
    for(;b;b>>=1,a=a*a)
        if(b&1)
            r=r*a;
    return r;
}
template<class T>ModularInteger<T>inv(ModularInteger<T>a){
    return pow(a,a.p-2);
}
43 template<class T>vector<ModularInteger<T> >sqrt(ModularInteger<T>a){
    vector<ModularInteger<T> >r;
    if(!a.v)
        r.push_back(ModularInteger<T>(0));
    else if(pow(a,a.p-1>>1).v==1){
        int s=a.p-1,t=0;
        ModularInteger<T>b=1;
        for(;pow(b,a.p-1>>1).v!=a.p-1;b=rand()*1.0/RAND_MAX*(a.p-1));
        for(;s%2==0;++t,s/=2);
        ModularInteger<T>x=pow(a,(s+1)/2),e=pow(a,s);
53     for(int i=1;i<t;++i,e=x*x/a)
        if(pow(e,1<<t-i-1).v!=1)
            x=x*pow(b,(1<<i-1)*s);
        r.push_back(x);
        r.push_back(-x);
    }
}

```

```

    return r;
}
template<class T>ModularInteger<T>operator+(ModularInteger<T>a,
ModularInteger<T>b){
    ModularInteger<T>c(a.v+b.v);
63    if(c.v>=a.p)
        c.v-=a.p;
    return c;
}
template<class T>ModularInteger<T>operator-(ModularInteger<T>a,
ModularInteger<T>b){
    ModularInteger<T>c(a.v-b.v);
    if(c.v<0)
        c.v+=a.p;
    return c;
}
73 template<class T>ModularInteger<T>operator*(ModularInteger<T>a,
ModularInteger<T>b){
    if(typeid(T)!=typeid(int))
        return ModularInteger<T>((a.v*b.v-(long long)(((long double)a.v*b.v
+0.5)/a.p)*a.p+a.p)%a.p);
    else
        return ModularInteger<T>((long long)a.v*b.v%a.p);
}
template<class T>ModularInteger<T>operator/(ModularInteger<T>a,
ModularInteger<T>b){
    return a*inv(b);
}
template<class T>bool operator==(ModularInteger<T>a,ModularInteger<T>b){
83    return a.v==b.v;
}
template<class T>bool operator!=(ModularInteger<T>a,ModularInteger<T>b){
    return a.v!=b.v;
}
template<class T>istream&operator>>(istream&s,ModularInteger<T>&a){
    s>>a.v;
    return s;
}
template<class T>ostream&operator<<(ostream&s,ModularInteger<T>a){
93    s<<a.v;
    if(a.v<0||a.v>=a.p)

```

```

        a.v%=a.p;
    return s;
}
template<class T>T ModularInteger<T>::p=1e9+7;

```

4.5 Möbius Function

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Möbius Function.hpp (534 bytes, 21 lines)

```

#include<bits/stdc++.h>
2 using namespace std;
namespace MobiusFunction{
    vector<int>run(int n){
        vector<int>p,ntp(n+1),u(n+1);
        ntp[1]=1;
        u[1]=1;
        for(int i=2;i<=n;++i){
            if(!ntp[i])
                p.push_back(i),u[i]=-1;
            for(int j=0;j<p.size()&&p[j]*i<=n;++j){
12         ntp[p[j]*i]=1;
                if(i%p[j]==0)
                    break;
                else
                    u[p[j]*i]=-u[i];
            }
        }
        return u;
    }
}

```

4.6 Primality Test

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Primality Test.hpp (1509 bytes, 52 lines)

```

#include<bits/stdc++.h>
using namespace std;
namespace PrimalityTest{
    template<class T>T mul(T x,T y,T z){
        if(typeid(T)==typeid(int))
            return (long long)x*y%z;
        else if(typeid(T)==typeid(long long))
            return (x*y-(T)(((long double)x*y+0.5)/z)*z+z)%z;
9         else
            return x*y%z;
    }
    template<class T>T pow(T a,T b,T c){
        T r=1;
        for(;b;b&1?r=mul(r,a,c):0,b>>=1,a=mul(a,a,c));
        return r;
    }
    template<class T>int run(T a,int c=10){
        if(a==2)
19         return 1;
        if(a%2==0 || a<2)
            return 0;
        static int pi[]={2,7,61},pl
[ ]={2,325,9375,28178,450775,9780504,1795265022};
        if(typeid(T)==typeid(int))
            c=3;
        else if(typeid(T)==typeid(long long))
            c=7;
        T u=a-1,t=0,p=1;
        for(;u%2==0;u/=2,++t);
29         for(int i=0;i<c;++i){
            if(typeid(T)==typeid(int))
                p=pi[i]%a;
            else if(typeid(T)==typeid(long long))
                p=pl[i]%a;
            else
                p=(p*29+7)%a;
            if(!p || p==1 || p==a-1)
                continue;
            T x=pow(p,u,a);
39         if(x==1)

```

```

        continue;
    for(int j=0;x!=a-1&&j<t;++j){
        x=mul(x,x,a);
        if(x==1)
            return 0;
    }
    if(x==a-1)
        continue;
    return 0;
49 }
    }
    return 1;
}
}

```

4.7 Prime Number

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Prime Number.hpp (473 bytes, 18 lines)

```

#include<bits/stdc++.h>
using namespace std;
namespace PrimeNumber{
    pair<vector<int>,vector<int> >run(int n){
        vector<int>p,ntp(n+1);
        ntp[1]=1;
        for(int i=2;i<=n;++i){
8           if(!ntp[i])
                p.push_back(i);
            for(int j=0;j<p.size()&&p[j]*i<=n;++j){
                ntp[p[j]*i]=1;
                if(i%p[j]==0)
                    break;
            }
        }
        return make_pair(p,ntp);
18 }
}

```

4.8 Primitive Root

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Primitive Root.hpp (3256 bytes, 106 lines)

```

#include<bits/stdc++.h>
2  using namespace std;
namespace PrimitiveRoot{
    template<class T>T mul(T x,T y,T z){
        if(typeid(T)==typeid(int))
            return (long long)x*y%z;
        else
            return (x*y-(T)(((long double)x*y+0.5)/z)*z+z)%z;
    }
    template<class T>T pow(T a,T b,T c){
        T r=1;
12     for(;b&1?r=mul(r,a,c):0,b>>=1,a=mul(a,a,c));
        return r;
    }
    template<class T>bool chk(T a,int c=10){
        if(a==1)
            return false;
        T u=a-1,t=0;
        for(;u%2==0;u/=2,++t);
        for(int i=0;i<c;++i){
22     T x=pow(T(rand()*1.0/RAND_MAX*(a-2)+1),u,a),y;
            for(int j=0;j<t;++j){
                y=x;
                x=mul(x,x,a);
                if(x==1&&y!=1&&y!=a-1)
                    return false;
            }
            if(x!=1)
                return false;
        }
        return true;
    }
32 }
    template<class T>T gcd(T a,T b){
        if(a<0)
            a=-a;

```

```

        if(b<0)
            b=-b;
        return b?gcd(b,a%b):a;
    }
    template<class T>T rho(T a,T c){
        T x=double(rand())/RAND_MAX*(a-1),y=x;
42    for(int i=1,k=2;;){
            x=(mul(x,x,a)+c)%a;
            T d=gcd(y-x,a);
            if(d!=1&&d!=a)
                return d;
            if(y==x)
                return a;
            if(++i==k)
                y=x,k=2*k;
        }
52    }
    template<class T>vector<pair<T,int> >fac(T a){
        if(a==1)
            return vector<pair<T,int> >();
        if(chk(a))
            return vector<pair<T,int> >(1,make_pair(a,1));
        T b=a;
        while((b=rho(b,T(double(rand())/RAND_MAX*(a-1))))==a);
        vector<pair<T,int> >u=fac(b),v=fac(a/b),r;
        for(int pu=0,pv=0;pu<u.size()||pv<v.size();){
62            if(pu==u.size())
                r.push_back(v[pv++]);
            else if(pv==v.size())
                r.push_back(u[pu++]);
            else if(u[pu].first==v[pv].first)
                r.push_back(make_pair(u[pu].first,(u[pu].second+v[pv].second
))) ,++pu,++pv;
            else if(u[pu].first>v[pv].first)
                r.push_back(v[pv++]);
            else
                r.push_back(u[pu++]);
72        return r;
    }
    template<class T>void dfs(vector<pair<T,int> >&f,int i,T now,vector<T>&
r){

```

```

    if(i==f.size()){
        r.push_back(now);
        return;
    }
    for(int j=0;j<=f[i].second;++j,now*=f[i].first)
        dfs(f,i+1,now,r);
}
82 template<class T>T run(T a){
    vector<pair<T,int> >fa=fac(a),fpa;
    if(fa.size()==0||fa.size()>2)
        return -1;
    if(fa.size()==1&&fa[0].first==2&&fa[0].second>2)
        return -1;
    if(fa.size()==2&&fa[0]!=make_pair(T(2),1))
        return -1;
    T pa=a;
    for(int i=0;i<fa.size();++i)
92     pa=pa/fa[i].first*(fa[i].first-1);
    fpa=fac(pa);
    vector<T>fs;
    dfs(fpa,0,1,fs);
    for(T g=1,f=0;;++g,f=0){
        for(int i=0;i<fs.size();++i)
            if(fs[i]!=pa&&pow(g,fs[i],a)==1){
                f=1;
                break;
            }
102     if(!f)
        return g;
    }
}
}

```

4.9 Sequence

Numbers n such that a Hadamard matrix of order n exists.
1, 2, 4, 8, 12, 16, 20, 24, 28, 32, 36, 40, 44, 48, 52, 56, 60, 64, 68, 72, 76, 80, 84, 88, 92, 96, 100, 104, 108, 112, 116, 120, 124, 128, 132, 136, 140, 144, 148, 152, 156, 160, 164, 168, 172, 176, 180, 184, 188, 192, 196, 200, 204, 208, 212, 216, 220, 224, 228, 232, 236, 240, ...
Catalan numbers: $C_n = \frac{1}{n+1} \binom{2n}{n} = \frac{(2n)!}{(n+1)!n!}$. Also called Segner numbers.
1, 1, 2, 5, 14, 42, 132, 429, 1430, 4862, 16796, 58786, 208012, 742900, 2674440, 9694845, 35357670, 129644790, 477638700, 1767263190, 6564120420, 24466267020, 91482563640, 343059613650, 1289904147324, 4861946401452, 18367353072152, 69533550916004, 263747951750360, 1002242216651368, 3814986502092304, ...
Bell or exponential numbers: number of ways to partition a set of n labeled elements.
1, 1, 2, 5, 15, 52, 203, 877, 4140, 21147, 115975, 678570, 4213597, 27644437, 190899322, 1382958545, 10480142147, 82864869804, 682076806159, 5832742205057, 51724158235372, 474869816156751, 4506715738447323, 44152005855084346, 445958869294805289, 4638590332229999353, 49631246523618756274, ...

CHAPTER 5

Numerical Algorithms

5.1 Convolution (Fast Fourier Transform)

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Convolution (Fast Fourier Transform).hpp (1300 bytes, 39 lines)

```

#include<bits/stdc++.h>
using namespace std;
namespace Convolution{
4   typedef complex<double>T;
   void fft(vector<T>&a,int n,double s,vector<int>&rev){
       T im(0,1);
       double pi=acos(-1);
       for(int i=0;i<n;++i)
           if(i<rev[i])
               swap(a[i],a[rev[i]]);
       for(int i=1,m=2;(1<i)<=n;++i,m<=1){
           T wm=exp(s*im*2.0*pi/double(m)),w;
           for(int j=(w=1,0);j<n;j+=m,w=1)
14          for(int k=0;k<(m>>1);++k,w*=wm){
               T u=a[j+k],v=w*a[j+k+(m>>1)];
               a[j+k]=u+v;
               a[j+k+(m>>1)]=u-v;
           }
       }
   }
   vector<double>run(const vector<double>&a,const vector<double>&b){
       int l=ceil(log2(a.size()+b.size()-1)),n=1<<l;
       vector<int>rv;
24      for(int i=(rv.resize(n),0);i<n;++i)
           rv[i]=(rv[i>>1]>>1)|((i&1)<<(l-1));
       vector<T>ta(n),tb(n);
       copy(a.begin(),a.end(),ta.begin());
       copy(b.begin(),b.end(),tb.begin());
       fft(ta,n,1,rv);
       fft(tb,n,1,rv);
       for(int i=0;i<n;++i)
           ta[i]*=tb[i];
       fft(ta,n,-1,rv);
34      vector<double>c(a.size()+b.size()-1);
       for(int i=0;i<c.size();++i)

```

```

        c[i]=real(ta[i])/n;
    return c;
}
}

```

5.2 Convolution (Karatsuba Algorithm)

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Convolution (Karatsuba Algorithm).hpp (1416 bytes, 43 lines)

```

1  #include<bits/stdc++.h>
    using namespace std;
    namespace Convolution{
        template<class T>void kar(T*a,T*b,int n,int l,T**r){
            T*r1=r[l],*r11=r[l-1];
            for(int i=0;i<2*n;++i)
                *(r1+i)=0;
            if(n<=30){
                for(int i=0;i<n;++i)
                    for(int j=0;j<n;++j)
11                 *(r1+i+j)+=(a+i)**(b+j);
                return;
            }
            kar(a,b,n>>1,l-1,r);
            for(int i=0;i<n;++i)
                *(r1+i)+=(r11+i),*(r1+i+(n>>1))+=(r11+i);
            kar(a+(n>>1),b+(n>>1),n>>1,l-1,r);
            for(int i=0;i<n;++i)
                *(r1+i+n)+=(r11+i),*(r1+i+(n>>1))+=(r11+i);
            for(int i=0;i<(n>>1);++i){
21                 *(r1+(n<<1)+i)=(a+(n>>1)+i)-(a+i);
                *(r1+i+(n>>1)*5)=(b+i)-(b+(n>>1)+i);
            }
            kar(r1+(n<<1),r1+(n>>1)*5,n>>1,l-1,r);
            for(int i=0;i<n;++i)
                *(r1+i+(n>>1))+=(r11+i);}
        template<class T>vector<T>run(vector<T>a,vector<T>b){
            int l=ceil(log2(max(a.size(),b.size()))+1e-8);
            vector<T>rt(a.size()+b.size()-1);

```

```

31     a.resize(1<<1);
        b.resize(1<<1);
        T**r=new T*[1+1];
        for(int i=0;i<=1;++i)
            r[i]=new T[(1<<i)*3];
        kar(&a[0],&b[0],1<<1,1,r);
        for(int i=0;i<rt.size();++i)
            rt[i]=(r[1]+i);
        for(int i=0;i<=1;++i)
            delete r[i];
        delete r;
41     return rt;
    }
}

```

5.3 Convolution (Number Theoretic Transform)

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Convolution (Number Theoretic Transform).hpp (1620 bytes, 51 lines)

```

#include<bits/stdc++.h>
using namespace std;
namespace Convolution{
    typedef long long T;
    T pow(T a,T b,T c){
        T r=1;
7        for(;b;b&1?r=r*a%c:0,b>>=1,a=a*a%c);
        return r;
    }
    void ntt(vector<T>&a,int n,int s,vector<int>&rev,T p,T g){
        g=s==1?g:pow(g,p-2,p);
        vector<T>wm;
        for(int i=0;1<<i<=n;++i)
            wm.push_back(pow(g,(p-1)>>i,p));
        for(int i=0;i<n;++i)
            if(i<rev[i])
17                swap(a[i],a[rev[i]]);
        for(int i=1,m=2;1<<i<=n;++i,m<=<=1){
            vector<T>wmk(1,1);

```

```

    for(int k=1;k<(m>>1);++k)
        wmk.push_back(wmk.back()*wm[i]%p);
    for(int j=0;j<n;j+=m)
        for(int k=0;k<(m>>1);++k){
            T u=a[j+k],v=wmk[k]*a[j+k+(m>>1)]%p;
            a[j+k]=u+v;
            a[j+k+(m>>1)]=u-v+p;
            if(a[j+k]>=p)
                a[j+k]-=p;
            if(a[j+k+(m>>1)]>=p)
                a[j+k+(m>>1)]=-p;
        }
    }
}
vector<T>run(vector<T>a,vector<T>b,T p=15*(1<<27)+1,T g=31){
    int tn,l=ceil(log2(tn=a.size()+b.size()-1)),n=1<<l;
    vector<int>rv;
37    for(int i=(rv.resize(n),0);i<n;++i)
        rv[i]=(rv[i>>1]>>1)|((i&1)<<(l-1));
    a.resize(n);
    b.resize(n);
    ntt(a,n,1,rv,p,g);
    ntt(b,n,1,rv,p,g);
    for(int i=0;i<n;++i)
        a[i]=a[i]*b[i]%p;
    ntt(a,n,-1,rv,p,g);
    n=pow(n,p-2,p);
47    for(T&v:a)
        v=v*n%p;
    return a.resize(tn),a;
}
}

```

5.4 Fraction

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Fraction.hpp (2217 bytes, 100 lines)

```
#include<bits/stdc++.h>
```

```

using namespace std;
template<class T>struct Fraction{
    T p,q;
    int s;
    T gcd(T a,T b){
        return b?gcd(b,a%b):a;
    }
9   void reduce(){
        T d=gcd(p,q);
        p/=d;
        q/=d;
        if(p==0)
            s=0;
    }
    Fraction(int _s=0,T _p=0,T _q=1):
        s(_s),p(_p),q(_q){
        reduce();
19   }
    Fraction(string a){
        if(a[0]=='-'){
            s=-1;
            a=a.substr(1,a.size()-1);
        }else if(a[0]=='+'){
            s=1;
            a=a.substr(1,a.size()-1);
        }else
            s=1;
29   stringstream ss;
        char tc;
        ss<<a;
        ss>>p>>tc>>q;
        reduce();
    }
    Fraction(const char*a){
        *this=Fraction(string(a));
    }
    Fraction<T>&operator=(string a){
39   return*this=Fraction<T>(a);
    }
    Fraction<T>&operator=(const char*a){
        return*this=Fraction<T>(a);
    }

```



```

    }
};
template<class T>ostream&operator<<(ostream&s,const Fraction<T>&a){
    if(a.s== -1)
        s<<'-' ;
    return s<<a.p<<'/'<<a.q;
49 }
template<class T>istream&operator>>(istream&s,Fraction<T>&a){
    string t;
    s>>t;
    a=t;
    return s;
}
template<class T>vector<string>real(const Fraction<T>&a){
    vector<string>r;
    stringstream ss;
    string st;
59 if(a.s<0)
        r.push_back("-");
    else
        r.push_back("+");
    T p=a.p,q=a.q;
    ss<<p/q;
    ss>>st;
    r.push_back(st);
    p%=q;
69 st.clear();
    map<T,int>mp;
    while(true){
        if(p==0){
            r.push_back(st);
            r.push_back("");
            return r;
        }
        if(mp.count(p)){
            r.push_back(st.substr(0,mp[p]));
79 r.push_back(st.substr(mp[p],st.size()-mp[p]));
            return r;
        }
        p*=10;
        mp[p/10]=st.size();
    }
}

```

```

        st.push_back('0'+p/q);
        p%=q;
    }
    return r;
}
89 template<class T>string decimal(const Fraction<T>&a){
    string r;
    vector<string>t=real(a);
    if(t[0]=="-")
        r.push_back('-');
    r+=t[1];
    if(t[2].size()||t[3].size())
        r+="."+t[2];
    if(t[3].size())
        r+="("+t[3]+")";
99    return r;
}

```

5.5 Integer

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Integer.hpp (6378 bytes, 269 lines)

```

#include<bits/stdc++.h>
using namespace std;
struct Integer operator+(Integer a,Integer b);
Integer operator+(Integer a,int b);
Integer operator-(Integer a,Integer b);
Integer operator*(Integer a,Integer b);
Integer operator*(Integer a,Integer b);
Integer operator/(Integer a,Integer b);
Integer operator%(Integer a,Integer b);
10 Integer operator%(Integer a,int b);
Integer operator%(Integer a,long long b);
bool operator!=(Integer a,int b);
bool operator<=(Integer a,int b);
struct Integer{
    operator bool(){
        return *this!=0;
    }
}

```

```

}
Integer(long long a=0){
    if(a<0){
20         s=-1;
        a=-a;
    }else
        s=a!=0;
    do{
        d.push_back(a%B);
        a/=B;
    }while(a);
}
Integer(string a){
30     s=(a[0]=='-')?-1:(a!="0");
    for(int i=a.size()-1;i>=(a[0]=='-');i-=L){
        int t=0,j=max(i-L+1,int(a[0]=='-'));
        for(int k=j;k<=i;++k)
            t=t*10+a[k]-'0';
        d.push_back(t);
    }
}
Integer(const Integer&a){
40     d=a.d;
    s=a.s;
}
Integer&operator=(long long a){
    return*this=Integer(a);
}
Integer&operator+=(Integer a){
    return*this=*this+a;
}
Integer&operator-=(Integer a){
50     return*this=*this-a;
}
Integer&operator*=(Integer a){
    return*this=*this*a;
}
Integer&operator/=(Integer a){
    return*this=*this/a;
}
Integer&operator%=(Integer a){

```

```

        return*this=*this%a;
    }
60 Integer&operator++(){
        return*this=*this+1;
    }
    operator string()const{
        string r;
        for(int i=0;i<d.size();++i){
            stringstream ts;
            ts<<d[i];
            string tt;
            ts>>tt;
70         reverse(tt.begin(),tt.end());
            while(i+1!=d.size()&&tt.size()<L)
                tt.push_back('0');
            r+=tt;
        }
        reverse(r.begin(),r.end());
        return r;
    }
    int s;
    vector<int>d;
80     static const int B=1e8,L=8;
};
string str(const Integer&a){
    return string(a);
}
bool operator<(Integer a,Integer b){
    if(a.s!=b.s)
        return a.s<b.s;
    if(a.d.size()!=b.d.size())
        return (a.s!=1)^(a.d.size()<b.d.size());
90     for(int i=a.d.size()-1;i>=0;--i)
        if(a.d[i]!=b.d[i])
            return (a.s!=1)^(a.d[i]<b.d[i]);
    return false;
}
bool operator>(Integer a,Integer b){
    return b<a;
}
bool operator<=(Integer a,Integer b){

```

```

        return !(a>b);
100 }
    bool operator>=(Integer a,Integer b){
        return !(a<b);
    }
    bool operator==(Integer a,Integer b){
        return !(a<b)&&!(a>b);
    }
    bool operator!=(Integer a,Integer b){
        return !(a==b);
    }
110 istream&operator>>(istream&s,Integer&a){
    string t;
    s>>t;
    a=Integer(t);
    return s;
}
    ostream&operator<<(ostream&s,Integer a){
        if(a.s== -1)
            s<<'-' ;
        for(int i=a.d.size()-1;i>=0;--i){
120         if(i!=a.d.size()-1)
            s<<setw(Integer::L)<<setfill('0');
            s<<a.d[i];
        }
        s<<setw(0)<<setfill(' ');
        return s;
    }
    void dzero(Integer&a){
        while(a.d.size()>1&&a.d.back() ==0)
            a.d.pop_back();
130 }
    Integer operator-(Integer a){
        a.s*=-1;
        if(a.d.size() ==1&&a.d[0] ==0)
            a.s=1;
        return a;
    }
    Integer operator+(Integer a,int b){
        return a+Integer(b);
    }

```

```

140 Integer operator*(Integer a,int b){
    return a*Integer(b);
}
Integer operator%(Integer a,int b){
    return a%Integer(b);
}
Integer operator%(Integer a,long long b){
    return a%Integer(b);
}
bool operator!=(Integer a,int b){
150     return a!=Integer(b);
}
bool operator<=(Integer a,int b){
    return a<=Integer(b);
}
Integer operator+(Integer a,Integer b){
    if(a.s*b.s!=-1){
        Integer c;c.s=a.s?a.s:b.s;
        c.d.resize(max(a.d.size(),b.d.size()+1));
        for(int i=0;i<c.d.size()-1;++i){
160             if(i<a.d.size())
                c.d[i]+=a.d[i];
            if(i<b.d.size())
                c.d[i]+=b.d[i];
            if(c.d[i]>=Integer::B){
                c.d[i]-=Integer::B;
                ++c.d[i+1];
            }
        }
        dzero(c);
170     return c;
    }
    return a-(-b);
}
Integer operator-(Integer a,Integer b){
    if(a.s*b.s==1){
        if(a.s==1)
            return (-b)-(-a);
        if(a<b)
            return -(b-a);
180     if(a==b)

```

```

        return 0;
    for(int i=0;i<b.d.size();++i){
        a.d[i]-=b.d[i];
        if(a.d[i]<0){
            a.d[i]+=Integer::B;
            --a.d[i+1];
        }
    }
    dzero(a);
    return a;
190 }
    return a+(-b);
}
Integer operator*(Integer a,Integer b){
    vector<long long>t(a.d.size()+b.d.size());
    for(int i=0;i<a.d.size();++i)
        for(int j=0;j<b.d.size();++j)
            t[i+j]+=(long long)a.d[i]*b.d[j];
    for(int i=0;i<t.size()-1;++i){
200     t[i+1]+=t[i]/Integer::B;
        t[i]%=Integer::B;
    }
    Integer c;
    c.s=a.s*b.s;c.d.resize(t.size());
    copy(t.begin(),t.end(),c.d.begin());
    dzero(c);
    return c;
}
Integer div2(Integer a){
210     for(int i=a.d.size()-1;i>=0;--i){
        if(i)
            a.d[i-1]+=(a.d[i]&1)*Integer::B;
        a.d[i]>>=1;
    }
    dzero(a);
    if(a.d.size()==1&&a.d[0]==0)
        a.s=0;
    return a;
}
220 Integer operator/(Integer a,Integer b){
    if(!a.s)

```

```

        return 0;
    if(a.s<0)
        return-((-a)/b);
    if(a<b)
        return 0;
    Integer l=1,r=1;
    while(r*b<=a)
        r=r*2;
230  while(l+1<r){
        Integer m=div2(l+r);
        if(m*b>a)
            r=m;
        else
            l=m;
    }
    return 1;
}
Integer operator%(Integer a,Integer b){
240  return a-a/b*b;
}
Integer gcd(Integer a,Integer b){
    Integer r=1;
    while(a!=0&&b!=0){
        if(!(a.d[0]&1)&&!(b.d[0]&1)){
            a=div2(a);
            b=div2(b);
            r=r*2;
        }else if(!(a.d[0]&1))
250     a=div2(a);
        else if(!(b.d[0]&1))
            b=div2(b);
        else{
            if(a<b)
                swap(a,b);
            a=div2(a-b);
        }
    }
    if(a!=0)
260     return r*a;
    return r*b;
}

```



```

int length(Integer a){
    a.s=1;
    return string(a).size();
}
int len(Integer a){
    return length(a);
}

```

5.6 Linear Programming

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Linear Programming.hpp (2522 bytes, 89 lines)

```

1  #include<bits/stdc++.h>
   using namespace std;
   struct LinearProgramming{
       const double E;
       int n,m,p;
       vector<int>mp,ma,md;
       vector<vector<double> >a;
       vector<double>res;
       LinearProgramming(int _n,int _m):
           n(_n),m(_m),p(0),a(n+2,vector<double>(m+2)),mp(n+1),ma(m+n+2),md(m
11  +2),res(m+1),E(1e-8){
       }
       void piv(int l,int e){
           swap(mp[l],md[e]);
           ma[mp[l]]=1;
           ma[md[e]]=-1;
           double t=-a[l][e];
           a[l][e]=-1;
           vector<int>qu;
           for(int i=0;i<=m+1;++i)
               if(fabs(a[l][i]/t)>E)
21  qu.push_back(i);
           for(int i=0;i<=n+1;++i)
               if(i!=l&&fabs(a[i][e])>E){
                   t=a[i][e];
                   a[i][e]=0;

```

```

        for(int j=0;j<qu.size();++j)
            a[i][qu[j]]+=a[l][qu[j]]*t;
    }
    if(-p==1)
        p=e;
31    else if(p==e)
        p=-1;
}
int opt(int d){
    for(int l=-1,e=-1;;piv(l,e),l=-1,e=-1){
        for(int i=1;i<=m+1;++i)
            if(a[d][i]>E){
                e=i;
                break;
            }
41    if(e==-1)
        return 1;
    double t;
    for(int i=1;i<=n;++i)
        if(a[i][e]<-E&&(l==-1||a[i][0]/-a[i][e]<t))
            t=a[i][0]/-a[i][e],l=i;
    if(l==-1)
        return 0;
    }
}
51 double&at(int x,int y){
    return a[x][y];
}
vector<double>run(){
    for(int i=1;i<=m+1;++i)
        ma[i]=-1,md[i]=i;
    for(int i=m+2;i<=m+n+1;++i)
        ma[i]=i-(m+1),mp[i-(m+1)]=i;
    double t;
    int l=-1;
61    for(int i=1;i<=n;++i)
        if(l==-1||a[i][0]<t)
            t=a[i][0],l=i;
    if(t<-E){
        for(int i=1;i<=n;++i)
            a[i][m+1]=1;
    }
}

```

```

71     a[n+1][m+1]=-1;
        p=m+1;
        piv(1,m+1);
        if(!opt(n+1)||fabs(a[n+1][0])>E)
            return vector<double>();
        if(p<0)
            for(int i=1;i<=m;++i)
                if(fabs(a[-p][i])>E){
                    piv(-p,i);
                    break;
                }
            for(int i=0;i<=n;++i)
                a[i][p]=0;
81     }
        if(!opt(0))
            return vector<double>();
        res[0]=a[0][0];
        for(int i=1;i<=m;++i)
            if(ma[i]!=-1)
                res[i]=a[ma[i]][0];
        return res;
    }
};

```

5.7 Linear System

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Linear System.hpp (1477 bytes, 56 lines)

```

1  #include<bits/stdc++.h>
    using namespace std;
    template<class T>struct LinearSystem{
        int n;
        vector<vector<T> >a;
        vector<int>main,pos;
        vector<T>ans;
        int cmp(T a){
            if(typeid(T)==typeid(double)||typeid(T)==typeid(long double)||
               typeid(T)==typeid(float)){

```

```

11         if(a<-1e-8)
            return -1;
        if(a>1e-8)
            return 1;
        return 0;
    }
    if(a<0)
        return -1;
    if(a>0)
        return 1;
    return 0;
21 }
T&at(int i,int j){
    return a[i][j];
}
vector<T>&at(int i){
    return a[i];
}
LinearSystem(int _n):
    n(_n),a(n+1,vector<T>(n+1)),main(n+1),pos(n+1),ans(n){
}
31 vector<T>run(){
    for(int i=1;i<=n;++i){
        int j=1;
        for(;j<=n&&!cmp(a[i][j]);++j);
        if(j<=n){
            main[i]=j;
            pos[j]=i;
            T t=a[i][j];
            for(int k=0;k<=n;++k)
                a[i][k]/=t;
41         for(int k=1;k<=n;++k)
            if(k!=i&&cmp(a[k][j])){
                t=a[k][j];
                for(int l=0;l<=n;++l)
                    a[k][l]-=a[i][l]*t;
            }
        }
    }
    for(int i=1;i<=n;++i){
        if(!pos[i])

```

```

51         return vector<T>();
           ans[i-1]=a[pos[i]][0];
       }
       return ans;
   }
};

```

5.8 Matrix

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Matrix.hpp (1457 bytes, 51 lines)

```

#include<bits/stdc++.h>
template<class T,int N>struct Matrix{
    Matrix(T t=0){
4        for(int i=0;i<N;++i)
            for(int j=0;j<N;++j)
                u[i][j]=i==j?t:0;
    }
    T u[N][N];
};
template<class T,int N>Matrix<T,N>operator+(const Matrix<T,N>&a,const
    Matrix<T,N>&b){
    Matrix<T,N>c;
    for(int i=0;i<N;++i)
        for(int j=0;j<N;++j)
14        c.u[i][j]=a.u[i][j]+b.u[i][j];
    return c;
}
template<class T,int N>Matrix<T,N>operator*(const Matrix<T,N>&a,const
    Matrix<T,N>&b){
    Matrix<T,N>c;
    for(int i=0;i<N;++i)
        for(int j=0;j<N;++j)
            for(int k=0;k<N;++k)
                c.u[i][j]+=a.u[i][k]*b.u[k][j];
    return c;
24 }
template<class T,int N>Matrix<T,N>operator*(const Matrix<T,N>&a,const T&b){

```

```

    Matrix<T,N>c=a;
    for(int i=0;i<N;++i)
        for(int j=0;j<N;++j)
            c.u[i][j]*=b;
    return c;
}
template<class T,int N>Matrix<T,N>operator/(const Matrix<T,N>&a,const T&b){
    Matrix<T,N>c=a;
34   for(int i=0;i<N;++i)
        for(int j=0;j<N;++j)
            c.u[i][j]/=b;
    return c;
}
template<class T,int N>Matrix<T,N>pow(Matrix<T,N>a,long long b){
    Matrix<T,N>r(1);
    for(;b;a=a*a,b>=>1)
        if(b&1)
            r=r*a;
44   return r;
}
template<class T,int N>ostream&operator<<(ostream&s,const Matrix<T,N>a){
    for(int i=0;i<N;++i)
        for(int j=0;j<N;++j)
            s<<a.u[i][j]<<(j+1==N?'\\n':' ');
    return s;
}

```

5.9 Polynomial Interpolation

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Polynomial Interpolation.hpp (372 bytes, 15 lines)

```

#include<bits/stdc++.h>
using namespace std;
template<class T>T PolynomialInterpolation(vector<T>x,vector<T>y,T x0){
    T r=0;
    for(int i=0;i<x.size();++i){
        T p=1,q=1;
        for(int j=0;j<x.size();++j)

```

```
9      if(j!=i){
        p*=(x0-x[j]);
        q*=(x[i]-x[j]);
      }
      r+=p/q*y[i];
    }
    return r;
  }
```

CHAPTER 6

String Algorithms

6.1 Aho-Corasick Automaton

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Aho-Corasick Automaton.hpp (1369 bytes, 50 lines)

```

#include<bits/stdc++.h>
using namespace std;
struct AhoCorasickAutomaton{
    struct node{
5        node(int m):
            tr(m),fail(0),cnt(0){
        }
        vector<node*>tr;
        node*fail;
        int cnt;
    };
    int m;
    node*root;
    vector<node*>all;
15    AhoCorasickAutomaton(int _m):
        m(_m),root(new node(m)),all(1,root){
    }
    ~AhoCorasickAutomaton(){
        for(int i=0;i<all.size();++i)
            delete all[i];
    }
    node*insert(int*s){
        node*p;
        for(p=root;*s!=-1;p=p->tr[*s++])
25            if(!p->tr[*s])
                p->tr[*s]=new node(m);
        return p;
    }
    void build(){
        queue<node*>qu;
        for(int i=0;i<m;++i)
            if(!root->tr[i])
                root->tr[i]=root;
            else
35                root->tr[i]->fail=root,qu.push(root->tr[i]);

```

```

        for(node*u;qu.size()? (u=qu.front(),qu.pop(),all.push_back(u),1):0;)
            for(int i=0;i<m;++i)
                if(!u->tr[i])
                    u->tr[i]=u->fail->tr[i];
                else
                    u->tr[i]->fail=u->fail->tr[i],qu.push(u->tr[i]);
    }
    void run(int*s){
        for(node*p=root;*s!=-1;++(p=p->tr[*s]))->cnt);
45 }
    void count(){
        for(int i=all.size()-1;i>=1;--i)
            all[i]->fail->cnt+=all[i]->cnt;
    }
};

```

6.2 Factor Oracle

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Factor Oracle.hpp (569 bytes, 16 lines)

```

#include<bits/stdc++.h>
using namespace std;
template<class T,int N,int M,T D>struct FactorOracle{
    void insert(T*s,int n){
        memset(tr,(lrs[0]=0,sp[0]=-1),4*M);
        for(int i=0,j,c=s[i]-D,u,v;i<n;c=s[++i]-D){
            memset(tr+i+1,(lrs[i+1]=0)-1,4*M);
            for(j=i;j>-1&&tr[j][c]<0;tr[j][c]=i+1,j=sp[u=j]);
            if(v=sp[i+1]=j<0?0:tr[j][c]){
10         for(v=v-1==sp[u]?u:v-1;sp[u]!=sp[v];v=sp[v]);
            lrs[i+1]=min(lrs[u],lrs[v])+1;
        }
    }
}
int sp[N+1],lrs[N+1],tr[N+1][M];
};

```

6.3 Longest Common Substring

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Longest Common Substring.hpp (1181 bytes, 28 lines)

```

#include<bits/stdc++.h>
using namespace std;
template<class T,int N,int M,T D>struct LongestCommonSubstring{
4   void ins(int c){
        memset(tr+i+1,(lrs[i+1]=0)-1,4*M);
        for(j=i;j>-1&&((v=tr[j][c])>=11+2&&v<=11+1b+1||v<0);tr[j][c]=i+1+1b
        ,j=sp[u=j]);
        if(v=sp[i+1]=j<0?0:tr[j][c]-(tr[j][c]>11+1)*1b){
            for(v=v-1==sp[u]?u:v-1;sp[u]!=sp[v];v=sp[v]);
            lrs[i+1]=min(lrs[u],lrs[v])+1;
        }
        if(sp[i+1]<=11)
            tm[sp[i+1]]=max(tm[sp[i+1]],lrs[i+1]);
    }
14  int run(vector<pair<int,T*> >s){
        swap(s[0],*min_element(s.begin(),s.end()));
        l1=s[k=1b=0].first;
        memset(mi,63,4*N+4);
        memset(tr,(lrs[0]=0,sp[0]=-1),4*M+4);
        for(i=0;i<l1;ins(*(s[0].second+i)-D),++i);
        for(k=1,ins(M);k<s.size();lb+=s[k++].first){
            memset(tm,0,4*N+4);
            for(i=l1+1;i-l1-1<s[k].first;ins(*(s[k].second+i-l1-1)-D),++i)
;
            for(i=l1;i;mi[i]=min(mi[i],tm[i]),tm[sp[i]]=max(tm[sp[i]],lrs[i]
24  ]*!!tm[i]),--i);
        }
        return min(*max_element(mi+1,mi+l1+1),l1);
    }
    int sp[2*N+2],lrs[2*N+2],tr[2*N+2][M+1],mi[N+1],tm[N+1],l1,lb,i,j,k,u,v
;
};

```

6.4 Palindromic Tree

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Palindromic Tree.hpp (1327 bytes, 50 lines)

```

#include<bits/stdc++.h>
2 using namespace std;
template<class T>struct PalindromicTree{
    struct node{
        node(int m,node*f,int l):
            nxt(m),fail(f),len(l){
        }
        vector<node*>nxt;
        node*fail;
        T val;
        int len;
12    }*root;
    int m;
    vector<int>str;
    vector<node*>all;
    PalindromicTree(int _m):
        m(_m){
            node*n0=new node(m,0,-2),*n1=new node(m,n0,-1),*n2=new node(m,n1,0)
        ;
            all.push_back(n0);
            all.push_back(n1);
            all.push_back(n2);
22        fill(n0->nxt.begin(),n0->nxt.end(),n2);
            root=n1;
        }
        ~PalindromicTree(){
            for(int i=0;i<all.size();++i)
                delete all[i];
        }
        node*find(node*x){
            while(x->fail&&str[str.size()-x->len-2]!=str[str.size()-1])
                x=x->fail;
32        return x;
    }
    node*insert(node*p,int c,T v){

```

```

    if(p==root)
        str=vector<int>(1,-1);
    str.push_back(c);
    p=find(p);
    if(!p->nxt[c]){
        node*np=(p->nxt[c]=new node(m,find(p->fail)->nxt[c],p->len+2))
    }
    all.push_back(np);
    p->nxt[c]->val+=v;
    return p->nxt[c];
}
void count(){
    for(int i=all.size()-1;i>=1;--i)
        all[i]->fail->val+=all[i]->val;
}
};
```

6.5 String Matching

Description

Find the occurrences of a pattern in a text.

Methods

template<class T>StringMatching<T>::StringMatching(T*p);	
Description	construct an object of SuffixMatching for a given pattern
Parameters	Description
T	type of character
p	pattern, indexed from one, ended by zero
Time complexity	$\Theta(p)$
Space complexity	$\Theta(p)$
Return value	an object of StringMatching

template<class T>int StringMatching<T>::run(T*t,int k=0);	
Description	given an occurrence of the pattern in a text, find the next occurrence
Parameters	Description
t	text, indexed from one, ended by zero
k	start index of the last occurrence of the pattern, use zero if there is none
Time complexity	$O(t)$
Space complexity	$\Theta(1)$
Return value	start index of the next occurrence of the pattern

Fields

Name	Description
------	-------------

Performance

Problem	Constraints	Time	Memory	Date
POJ P3461	$ p = 10^4, t = 10^6$	141 ms	1340 kB	2016-02-14

References

Title	Author
Fast pattern matching in strings	Donald E. Knuth, James H. Morris, Vaughan R. Pratt

Code

String Matching.hpp (682 bytes, 25 lines)

```
#include<bits/stdc++.h>
using namespace std;
template<class T>struct StringMatching{
    StringMatching(T*p):
        b(2,p[1]),f(2),l(2){
        for(int i=0;p[1]?1:(--l,0);b.push_back(p[1++])){
            for(;i&& p[i+1]!=p[1];i=f[i]);
            f.push_back(i+i+(p[i+1]==p[1]));
        }
        for(int i=2;i<l;++i)
            if(p[f[i]+1]==p[i+1])
```

10

```

        f[i]=f[f[i]];
    }
    int run(T*t,int k=0){
        for(int i=k?k+1:1,j=k?f[1]:0;t[i];++i){
            for(;j&&b[j+1]!=t[i];j=f[j]);
            if((j+=b[j+1]==t[i])==1)
                return i-l+1;
        }
20     return 0;
    }
    int l;
    vector<T>b;
    vector<int>f;
};
```

6.6 Suffix Array (DC3 Algorithm)

Description

Construct a suffix array and it's height array from a given string using DC3 algorithm.

Methods

template<class T,int M,T D>SuffixArray<T,M,D>::SuffixArray(T*s,int n);	
Description	construct an object of SuffixArray and in the mean time consturct the suffix array and height array
Parameters	
T	type of character, usually char
M	size of alphabet
D	offset of alphabet, use 'a' for lowercase letters
s	string from which to build a suffix array, indexed from one
n	length of s
Time complexity	$\Theta(n + M)$
Space complexity	$\Theta(10n + M)$
Return value	an object of SuffixArray

Fields

Name	Description
sa	suffix array, indexed from one
ht	height array, indexed from one

Performance

Problem	Constraints	Time	Memory	Date
UOJ P35	$N = 10^5, M = 26$	416 ms (18+ cases)	4248 kB	2016-02-14

References

Title	Author
后缀数组——处理字符串的有力工具	罗穗骞

Code

Suffix Array (DC3 Algorithm).hpp (2656 bytes, 82 lines)

```
#include<bits/stdc++.h>
using namespace std;
template<class T,int M,int D>struct SuffixArray{
    int*sa,*ht,*rk,*ts,*ct,*st;
5    SuffixArray(T*s,int n){
        crt(st,n),crt(sa,n),crt(ht,n);
        crt(rk,n),crt(ts,n),crt(ct,max(n,M));
        for(int i=1;i<=n;++i)st[i]=s[i]-D+1;
        dc3(st,n,M,sa,rk);
        for(int i=1;i<=n;++i){
            if(rk[i]==1){ht[1]=0;continue;}
            int&d=ht[rk[i]]=max(i==1?0:ht[rk[i-1]]-1,0);
            for(;i+d<=n&&sa[rk[i]-1]+d<=n
15                &&st[i+d]==st[sa[rk[i]-1]+d];++d);
        }
    }
    ~SuffixArray(){
        del(sa),del(ht),del(rk);
        del(ts),del(ct),del(st);
    }
}
```

```

void crt(int*&a,int n){
    a=new int[n+1];
}
void del(int*a){
25     delete a;
}
#define fc(i)(p0[i]+d>n||!p0[i]?0:s[p0[i]+d])
int cmp(int*p0,int i,int*s,int n){
    for(int d=0;d<3;++d)
        if(fc(i)!=fc(i-1))return 1;
    return 0;
}
void sot(int*p0,int n0,int*s,int n,int m,int d){
35     memset(ct,0,(m+1)*4);
    for(int i=1;i<=n0;++i)++ct[fc(i)];
    for(int i=1;i<=m;++i)ct[i]+=ct[i-1];
    for(int i=n0;i>=1;--i)ts[ct[fc(i)]=p0[i];
    memcpy(p0+1,ts+1,n0*4);
}
#define fc(d)\
    if(s[i+d]!=s[j+d])return s[i+d]<s[j+d];\
    if(i==n-d||j==n-d)return i==n-d;
bool cmp(int*s,int n,int*r,int i,int j){
    fc(0)
45     if(j%3==1)return r[i+1]<r[j+1];
    fc(1)
    return r[i+2]<r[j+2];
}
#undef fc
void dc3(int*s,int n,int m,int*a,int*r){
    int n0=n-(n/3)+1,*a0,*s0,i,j=0,k=n/3+bool(n%3)+1,1;
    crt(s0,n0),s0[k]=1,crt(a0,n0+1),a0[k]=0;
    for(i=1;i<=n;i+=3)a0[++j]=i,a0[j+k]=i+1;
    for(i=2;i>=0;--i)sot(a0,n0,s,n,m,i);
    for(r[a0[1]]=1,i=2;i<=n0;++i)
55         r[a0[i]]=r[a0[i-1]]+cmp(a0,i,s,n);
    for(i=1,j=0;i<=n;i+=3)
        s0[++j]=r[i],s0[j+k]=r[i+1];
    if(r[a0[n0]]==n0){
        memcpy(r+1,s0+1,n0*4);
        for(i=1;i<=n0;++i)a0[a[i]]=r[i];
    }
}

```

```

        }else
            dc3(s0,n0,r[a0[n0]],a0,a);
        for(i=1,j=0;i<=n;i+=3)
65         r[i]=a[++j],r[i+1]=a[j+k];
        if(j=0,n%3==0)
            s0[++j]=n;
        for(i=1;i<=n0;++i)
            if(a0[i]>=k)
                a0[i]=(a0[i]-k)*3-1;
            else
                if((a0[i]=3*a0[i]-2)!=1)s0[++j]=a0[i]-1;
        sot(s0,j,s,n,m,0);
        for(i=1,k=2,l=0;i<=j||k<=n0;)
75         if(k>n0||i<=j&&cmp(s,n,r,s0[i],a0[k]))
            a[++l]=s0[i++];
            else
                a[++l]=a0[k++];
        for(i=1;i<=n;++i)r[a[i]]=i;
        del(a0),del(s0);
    }
};

```

6.7 Suffix Array (Factor Oracle)

Description

Use a factor oracle to construct a suffix array and its height array from a given string. It is theoretically slow, but usually fast in practice. Object of it should be static since it has large data members.

Methods

template<class T,int N,int M,T D>SuffixArray<T,N,M,D>::SuffixArray();	
Description	construct an object of SuffixArray
Parameters	Description
T	type of character, usually char
N	maximum length of input string
M	size of alphabet
D	offset of alphabet, use 'a' for lowercase letters
Time complexity	$\Theta(1)$
Space complexity	$\Theta((M + 13)N)$
Return value	an object of SuffixArray
template<class T,int N,int M,T D>void SuffixArray<T,N,M,D>::build(T*s,int n);	
Description	build suffix array and height array
Parameters	Description
s	string from which to build a suffix array, indexed from zero
n	length of s
Time complexity	$O((M + n)n)$
Space complexity	$\Theta(n)$
Return value	none

Fields

Name	Description
sa	suffix array, indexed from one
ht	height array, indexed from one

Performance

Problem	Constraints	Time	Memory	Date
Tyvj P1860	$N = 2 \times 10^5, M = 26$	1154 ms (10 cases)	33012 kB	2016-02-14

References

Title	Author
Factor oracle, suffix oracle	Cyril Allauzen, Maxime Crochemore, Mathieu Raffinot
Computing repeated factors with a factor oracle	Arnaud Lefebvre, Thierry Lecroq

Code

Suffix Array (Factor Oracle).hpp (2640 bytes, 71 lines)

```

#include<bits/stdc++.h>
using namespace std;
template<class T,int N,int M,T D>struct SuffixArray{
    int val(int i,int d){
        return d<0?(d>-2?lrs[i]:n-1-lrs[i]):s[n-i+lrs[i]+d]-D;
    }
    void sort(int*a,int*b,int m,int d){
8        static int c[N];
        memset(c,0,4*(d>=0?M:n));
        for(i=1;i<=m;++c[val(a[i],d)],++i);
        for(i=1;i<(d>=0?M:n);c[i]+=c[i-1],++i);
        for(i=m;i>=1;b[c[val(a[i],d)]--]=a[i],--i);
    }
    void sort(int a,int b,int d,int l){
        sort(z+a-1,t,b-a+1,d);
        memcpy(z+a,t+1,(b-a+1)*4);
        for(i=a,j;i<=b;i=j+1){
18            for(j=i;j+1<=b&&val(z[j],d)==val(z[j+1],d);++j);
            if(j-i)
                sort(i,j,d+1,l);
        }
    }
    void add(int&b,int v){
        cv[++cp]=v,cn[cp]=b,b=cp;
    }
    void dfs(int u){
        #define m(p,q)\
28        for(int i=p##b[u],j;i){\
            for(*z=0,j=i;cn[j]&&lrs[cv[j]]==lrs[cv[cn[j]]];z[++z[0]]=cv[
j],j=cn[j]);\
            z[++z[0]]=cv[j],sort(1,*z,0,q);\
            for(z[0]=1;i!=cn[j];cv[i]=z[z[0]++],i=cn[i]);\
        }
        m(1,0)
        for(int i=lb[u];i;dfs(cv[i]),i=cn[i]);
        sa[++sa]=n+1-u,*sa-=!u;
        m(r,1)

```

```

    for(int i=rb[u];i;dfs(cv[i]),i=cn[i]);
38 }
void build(T*_s,int _n){
    n=_n,s=_s,memset(tr,(cp=*sa=*vl=*vr=*lb=*rb=*lrs=0,*z=-1),4*M);
    for(int i=0,c=s[n-1-i]-D,u,v;i<n;c=s[n-1-++i]-D){
        memset(tr+i+1,(lb[i+1]=rb[i+1]=lrs[i+1]=0)-1,4*M);
        for(j=i;j>-1&&tr[j][c]<0;tr[j][c]=i+1,j=z[u=j]);
        if(v=z[i+1]=j<0?0:tr[j][c]){
            for(v=v-1==z[u]?u:v-1;z[u]!=z[v];v=z[v]);
            lrs[i+1]=min(lrs[u],lrs[v])+1;
        }
48     for(j=0;n-(z[i+1]-lrs[i+1]-j)<n&&s[n-(z[i+1]-lrs[i+1]-j)]=s[
n-1-i+lrs[i+1]+j];++j);
        if(n-(z[i+1]-lrs[i+1]-j)<n&&s[n-(z[i+1]-lrs[i+1]-j)]>s[n-1-i
+lrs[i+1]+j])
            vl[++*vl]=i+1;
        else
            vr[++*vr]=i+1;
    }
    sort(vl,t,*vl,-1),sort(vr,vl,*vr,-2);
    for(i=*vl;i;add(lb[z[t[i]]],t[i]),--i);
    for(i=*vr;i;add(rb[z[vl[i]]],vl[i]),--i);
    dfs(0);
58     for(i=1;i<=n;++i)
        rk[sa[i]]=i;
    for(i=1;i<=n;++i){
        if(rk[i]==1){
            ht[1]=0;
            continue;
        }
        int&d=ht[rk[i]]=max(i==1?0:ht[rk[i-1]]-1,0);
        for(;i+d<=n&&sa[rk[i]-1]+d<=n&&s[i+d-1]==s[sa[rk[i]-1]+d-1];++
d);
    }
68 }
T*s;
int n,sa[N+1],ht[N+1],rk[N+1],lrs[N+1],tr[N+1][M],i,j,lb[N+1],rb[N+1],
cv[N+1],cn[N+1],cp,vl[N+1],vr[N+1],t[N+1],z[N+1];
};

```

6.8 Suffix Array (Prefix-Doubling Algorithm)

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Suffix Array (Prefix-Doubling Algorithm).hpp (1357 bytes, 55 lines)

```

#include<bits/stdc++.h>
using namespace std;
struct SuffixArray{
    int*a,*h,*r,*t,*c,n,m;
    #define lp(u,v)for(int i=u;i<=v;++i)
    #define rp(u,v)for(int i=u;i>=v;--i)
    void sort(){
9        memset(c+1,0,m*4);
        lp(1,n)
            ++c[r[t[i]]];
        lp(2,m)
            c[i]+=c[i-1];
        rp(n,1)
            a[c[r[t[i]]]--]=t[i];
    }
    SuffixArray(int*s){
        for(n=m=0;s[n+1];m=max(m,s[+n]));
        a=new int[4*n+max(n,m)+3];
19        h=a+n;
        r=h+n+1;
        t=r+n+1;
        c=t+n;
        lp(1,n)
            t[i]=i,r[i]=s[i];
        sort();
        for(int l=1;l<=n;l<=1,r[a[n]]==n?l=n+1:m=r[a[n]]){
            t[0]=0;
            lp(n-l+1,n)
                t[++t[0]]=i;
29        lp(1,n)
            if(a[i]>l)
                t[++t[0]]=a[i]-1;
        sort();
        swap(r,t);
        r[a[1]]=1;

```

```

        lp(2,n)
        r[a[i]]=r[a[i-1]]+(t[a[i]]!=t[a[i-1]]||a[i]+1>n||a[i-1]+1>n
||t[a[i]+1]!=t[a[i-1]+1]);
    }
39     int l=0;
    a[0]=n+1;
    lp(1,n){
        if(r[i]==1)
            l=0;
        l--=(l>0);
        int j=a[r[i]-1];
        for(;s[i+1]==s[j+1];++l);
        h[r[i]]=l;
49     }
    }
    #undef lp
    #undef rp
    ~SuffixArray(){
        delete a;
    }
};

```

6.9 Suffix Array (Suffix Tree)

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Suffix Array (Suffix Tree).hpp (2849 bytes, 115 lines)

```

#include<bits/stdc++.h>
using namespace std;
template<class T,int N,int M,T D>struct SuffixTree{
    struct node;
5    struct edge{
        edge():
            l(0),r(0),t(0){
        }
        int length(){
            return r-l;
        }
        T*l,*r;

```



```

        node*t;
    }pe[2*N],*ep=pe;
15  edge*newedge(T*l,T*r,node*t){
        ep->l=l;
        ep->r=r;
        ep->t=t;
        return ep++;
    }
    struct node{
        node():
            s(0),c({0}){
        }
25     node*s;
        edge*c[M+1];
    }pn[2*N+1],*np=pn;
    SuffixTree():
        root(np++),ct(0){
    }
    void extend(T*s){
        for(;ae&&al>=ae->length();){
            s+=ae->length();
            al-=ae->length();
35         an=ae->t;
            ae=al?an->c[*s-D]:0;
        }
    }
    bool extend(int c){
        if(ae){
            if(*(ae->l+al)-D-c)
                return true;
            ++al;
        }else{
45         if(!an->c[c])
            return true;
            ae=an->c[c];
            al=1;
            if(pr)
                pr->s=an;
        }
        extend(ae->l);
        return false;
    }

```

```

    }
55 void dfs(node*u,int d){
    int t=0,s=0;
    for(int i=0;i<M+1;++i)
        if(u->c[i]){
            if(!t)
                t=1;
            else if(!s){
                s=1;
                *sp++=d;
            }
65         dfs(u->c[i]->t,d+u->c[i]->length());
        }
    if(s)
        --sp;
    else if(!t&&sp!=sk){
        *hp++=(sp-1);
        *fp++=ct-d+1;
    }
}
void build(T*s,int n){
75 s[n++]=M+D;
    ct+=n;
    an=root;
    ae=al=0;
    for(T*p=s;p!=s+n;++p)
        for(pr=0;extend(*p-D);){
            edge*x=newedge(p,s+n,np++);
            if(!ae)
                an->c[*p-D]=x;
            else{
85         edge*&y=an->c[*ae->l-D];
                y=newedge(ae->l,ae->l+al,np++);
                y->t->c[(ae->l+al)-D]=ae;
                y->t->c[*p-D]=x;
                ae=y;
            }
            if(pr)
                pr->s=ae?ae->t:an;
            pr=ae?ae->t:an;
            int r=1;

```

```

95         if(an==root&&!a1)
            break;
        if(an==root)
            --a1;
        else{
            an=an->s?an->s:root;
            r=0;
        }
        if(a1){
105            T*t=ae->l+(an==root)*r;
            ae=an->c[*t-D];
            extend(t);
        }else
            ae=0;
    }
    dfs(root,0);
}
edge*ae;
node*root,*an,*pr;
int a1,ct,sk[N],*sp=sk,ht[N],*hp=ht,sa[N],*fp=sa;
115 };

```

6.10 Suffix Array (Treap)

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Suffix Array (Treap).hpp (3803 bytes, 147 lines)

```

#include<bits/stdc++.h>
using namespace std;
template<class T>struct SuffixArray{
    struct node{
5        node*c[2],*p;
        T v;
        int f,s,l,h,m;
        double t;
        node(node*_p,T _v,int _l):
            f(rand()*1.0/RAND_MAX*1e9),p(_p),v(_v),s(1),l(_l),h(0),m(0),t(5
e8){
            c[0]=c[1]=0;

```

```

    }
    }*root;
    vector<T>a;
15  SuffixArray():
        root(new node(0,0,0)),a(1){
    }
    ~SuffixArray(){
        clear(root);
    }
    void relabel(node*x,double l,double r){
        x->t=(l+r)/2;
        if(x->c[0])
            relabel(x->c[0],l,x->t);
25  if(x->c[1])
            relabel(x->c[1],x->t,r);
    }
    void update(node*x){
        x->s=1;
        x->m=x->h;
        for(int i=0;i<2;++i)
            if(x->c[i])
                x->s+=x->c[i]->s,x->m=min(x->m,x->c[i]->m);
    }
35  void rotate(node*&x,int d){
        node*y=x->c[d];
        x->c[d]=y->c[!d];
        y->c[!d]=x;
        y->s=x->s;
        y->m=x->m;
        update(x);
        x=y;
    }
    void clear(node*x){
45  if(!x)
        return;
        clear(x->c[0]);
        clear(x->c[1]);
        delete x;
    }
    node*insert(node*&x,node*p,T v,node*l,node*r){
        int d=x->v!=v?v?x->v<v:x->p->t<p->t;

```

```

    double tl=l?l->t:0,tr=r?r->t:1e9;
    node*y;
55  if(d)
        l=x;
    else
        r=x;
    if(!x->c[d]){
        y=new node(p,v,p->l+1);
        y->t=((l?l->t:0)+(r?r->t:1e9))/2;
        y->m=y->h=l->v==y->v?lcp(l->p,y->p)+1:0;
        if(r)
            r->h=r->v==y->v?lcp(r->p,y->p)+1:0;
65  x->c[d]=y;
    }else
        y=insert(x->c[d],p,v,l,r);
    update(x);
    if(x->c[d]->f>x->f)
        rotate(x,d),relabel(x,tl,tr);
    return y;
}
node*insert(node*p,T v){
    a.push_back(v);
75  return insert(root,p,v,0,0);
}
void erase(node*&x,node*y){
    if(x==y){
        if(!x->c[0]){
            x=x->c[1];
            delete y;
        }else if(!x->c[1]){
            x=x->c[0];
            delete y;
85  }else{
            int d=x->c[0]->f<x->c[1]->f;
            rotate(x,d);
            erase(x->c[!d],y);
            --x->s;
        }
    }else
        erase(x->c[x->t<y->t],y),update(x);
}

```

```

void erase(node*y){
95     erase(root,y);
        a.pop_back();
}
bool check(node*x,T*y,node*&p,int&l){
    if(p){
        int t=x->c[p->t>x->t]?x->c[p->t>x->t]->m:~0u>>1;
        if(p->t>x->t)
            t=min(t,p->h);
        else
            t=min(t,x->h);
105    if(t<l)
        return x->t<p->t;
    }
    for(p=x;l+1<=x->l&&y[l+1];++l)
        if(a[x->l-1]!=y[l+1])
            return a[x->l-1]<y[l+1];
    return y[l+1]!=0;
}
int count(node*x,T*y){
115    int r=0,l=0;
    for(node*p=0;x;){
        if(check(x,y,p,l))
            r+=(x->c[0]?x->c[0]->s:0)+1,x=x->c[1];
        else
            x=x->c[0];
        return r;
    }
}
int count(T*y){
125    T*t=y;
    while(*(t+1))
        ++t;
    int r=-count(root,y);
    ++*t;
    r+=count(root,y);
    --*t;
    return r;
}
int lcp(node*x,double u,double v,double l,double r){
    if(v<l||u>r||!x)
        return ~0u>>1;

```

```

135         if(u<l&&v>=r)
            return x->m;
        int t=u<x->t&&v>=x->t?x->h:~0u>>1;
        t=min(t,lcp(x->c[0],u,v,l,x->t));
        t=min(t,lcp(x->c[1],u,v,x->t,r));
        return t;
    }
    int lcp(node*x,node*y){
        if(x->t>y->t)
            swap(x,y);
145     return lcp(root,x->t,y->t,0,1e9);
    }
};

```

6.11 Suffix Automaton

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Suffix Automaton.hpp (1694 bytes, 59 lines)

```

#include<bits/stdc++.h>
using namespace std;
3  template<class T>struct SuffixAutomaton{
    struct node{
        node(vector<node*>&all,int m,node*_pr=0,int _ln=0,T _va=T()):
            pr(_pr),tr(m),ln(_ln),va(_va){
                all.push_back(this);
            }
        T va;
        int ln;
        node*pr;
        vector<node*>tr;
13 };
    SuffixAutomaton(int _m):
        root(new node(all,m)),m(_m){
    }
    ~SuffixAutomaton(){
        for(int i=0;i<all.size();++i)
            delete all[i];
    }
}

```

```

node*insert(node*lst,int c,T v){
    node*p=lst,*np=p->tr[c]?0:new node(all,m,0,lst->ln+1,v);
23   for(;p&&!p->tr[c];p=p->pr)
        p->tr[c]=np;
    if(!p)np->pr=root;
    else{
        node*q=p->tr[c];
        if(p==lst)
            np=q;
        if(q->ln==p->ln+1)
            p==lst?(q->va+=v):(np->pr=q,0);
        else{
33             node*nq=new node(all,m,q->pr,p->ln+1,p==lst?v:T());
            nq->tr=q->tr;
            q->pr=np->pr=nq;
            if(p==lst)
                np=nq;
            for(;p&&p->tr[c]==q;p=p->pr)
                p->tr[c]=nq;
        }
    }
    return np;
43 }
void count(){
    vector<int>cnt(all.size());
    vector<node*>tmp=all;
    for(int i=0;i<tmp.size();++i)
        ++cnt[tmp[i]->ln];
    for(int i=1;i<cnt.size();++i)
        cnt[i]+=cnt[i-1];
    for(int i=0;i<tmp.size();++i)
        all[--cnt[tmp[i]->ln]]=tmp[i];
53   for(int i=int(all.size())-1;i>0;--i)
        all[i]->pr->va+=all[i]->va;
}
int m;
node*root;
vector<node*>all;
};

```

6.12 Suffix Tree

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Suffix Tree.hpp (2296 bytes, 94 lines)

```

1  #include<bits/stdc++.h>
    using namespace std;
    template<class T,int N,int M,T D>struct SuffixTree{
        struct node;
        struct edge{
            edge():
                l(0),r(0),t(0){
            }
            int length(){
                return r-l;
11         }
            T*l,*r;
            node*t;
        }pe[2*N],*ep=pe;
        edge*newedge(T*l,T*r,node*t){
            ep->l=l;
            ep->r=r;
            ep->t=t;
            return ep++;
        }
21     struct node{
        node():
            s(0),c({0}){
        }
        node*s;
        edge*c[M];
        }pn[2*N+1],*np=pn;
        SuffixTree():
            root(np++),ct(0){
        }
31     void extend(T*s){
        for(;ae&&al>=ae->length();){
            s+=ae->length();
            al-=ae->length();
            an=ae->t;

```

```

        ae=al?an->c[*s-D]:0;
    }
}
bool extend(int c){
    if(ae){
41         if(*(ae->l+al)-D-c)
            return true;
        ++al;
    }else{
        if(!an->c[c])
            return true;
        ae=an->c[c];
        al=1;
        if(pr)
51         pr->s=an;
    }
    extend(ae->l);
    return false;
}
void insert(T*s,int n){
    ct+=n;
    an=root;
    ae=al=0;
    for(T*p=s;p!=s+n;++p)
        for(pr=0;extend(*p-D);){
61         edge*x=newedge(p,s+n,np++);
            if(!ae)
                an->c[*p-D]=x;
            else{
                edge*&y=an->c[*ae->l-D];
                y=newedge(ae->l,ae->l+al,np++);
                y->t->c[*ae->l+al-D]=ae;
                y->t->c[*p-D]=x;
                ae=y;
            }
71         if(pr)
            pr->s=ae?ae->t:an;
        pr=ae?ae->t:an;
        int r=1;
        if(an==root&&!al)
            break;
    }
}

```

```

        if(an==root)
            --al;
        else{
81         an=an->s?an->s:root;
            r=0;
        }
        if(al){
            T*t=ae->l+(an==root)*r;
            ae=an->c[*t-D];
            extend(t);
        }else
            ae=0;
    }
}
91 edge*ae;
    int al,ct;
    node*root,*an,*pr;
};
```

CHAPTER 7

Utility Tools

7.1 Checker

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Checker.bat (166 bytes, 7 lines)

```
:again
generator > input.txt
program1 < input.txt > output1.txt
program2 < input.txt > output2.txt
fc output1.txt output2.txt
6 if errorlevel 1 pause
goto again
```

7.2 Date

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Date.hpp (3596 bytes, 145 lines)

```
#include<bits/stdc++.h>
using namespace std;
3 struct Date{
    int y,m,d,w;
    Date&operator++(){
        return*this=*this+1;
    }
    bool leap(int a)const{
        return a%400==0|| (a%4==0&& a%100!=0);
    }
    int month_sum(int a,int b)const{
        if(b==0)
13         return 0;
        if(b==1)
            return 31;
        return 59+leap(a)+30*(b-2)+(b+1)/2-1+(b>=8&& b%2==0);
    }
    string month_name(int a)const{
        if(a==1)
            return"January";
```

```

    if(a==2)
        return"February";
23    if(a==3)
        return"March";
    if(a==4)
        return"April";
    if(a==5)
        return"May";
    if(a==6)
        return"June";
    if(a==7)
        return"July";
33    if(a==8)
        return"August";
    if(a==9)
        return"September";
    if(a==10)
        return"October";
    if(a==11)
        return"November";
    if(a==12)
        return"December";
43 }
string day_name(int a)const{
    if(a==0)
        return"Sunday";
    if(a==1)
        return"Monday";
    if(a==2)
        return"Tuesday";
    if(a==3)
        return"Wednesday";
53    if(a==4)
        return"Thursday";
    if(a==5)
        return"Friday";
    if(a==6)
        return"Saturday";
}
operator int()const{
    int t=(y-1)*365+(y-1)/4-(y-1)/100+(y-1)/400+month_sum(y,m-1)+d;

```

```

63         if(y==1752&&m>=9&&d>2 || y>1752)
            t-=11;
        t-=min(y-1,1700)/400-min(y-1,1700)/100;
        if(y<=1700&&y%400!=0&&y%100==0&&m>2)
            ++t;
        return t;
    }
    Date(int _y,int _m,int _d):
        y(_y),m(_m),d(_d),w((int(*this)+5)%7){
    }
    Date(int a){
73         int yl=0,yr=1e7;
        while(yl+1<yr){
            int ym=(yl+yr)/2;
            if(int(Date(ym,12,31))<a)
                yl=ym;
            else
                yr=ym;
        }
        y=yr;
        int ml=0,mr=12;
83         while(ml+1<mr){
            int mm=(ml+mr)/2,mt;
            if(mm==2){
                if(y<=1700)
                    mt=28+(y%4==0);
                else
                    mt=28+(y%4==0&&y%100!=0 || y%400==0);
            }else if(mm<=7)
                mt=30+mm%2;
            else
93                 mt=31-mm%2;
            if(int(Date(y,mm,mt))<a)
                ml=mm;
            else
                mr=mm;
        }
        m=mr;
        for(int i=1; ; ++i){
            if(y==1752&&m==9&&i>2&&i<14)
                continue;

```



```

103         if(int(Date(y,m,i))==a){
                d=i;
                break;
            }
        }
        w=(5+a)%7;
    }
    operator string()const{
        stringstream s;
        string t;
113        s<<day_name(w)+", "+month_name(m)+" "<<d<<"", "<<y;
        getline(s,t);
        return t;
    }
};
ostream&operator<<(ostream&s,const Date&a){
    return s<<string(a);
}
int operator-(const Date&a,const Date&b){
    return int(a)-int(b);
123 }
Date operator+(const Date&a,int b){
    return Date(int(a)+b);
}
Date operator-(const Date&a,int b){
    return Date(int(a)-b);
}
bool operator<(const Date&a,const Date&b){
    if(a.y==b.y&&a.m==b.m)
        return a.d<b.d;
133     if(a.y==b.y)
        return a.m<b.m;
    return a.y<b.y;
}
bool operator>(const Date&a,const Date&b){
    return b<a;
}
bool operator!=(const Date&a,const Date&b){
    return a.y!=b.y||a.m!=b.m||a.d!=b.d;
}
143 bool operator==(const Date&a,const Date&b){

```

```

    return !(a!=b);
}

```

7.3 Fast Reader

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Fast Reader.hpp (1251 bytes, 61 lines)

```

#include<bits/stdc++.h>
using namespace std;
struct FastReader{
    FILE*f;
5   char*p,*e;
    vector<char>v;
    void ipt(){
        for(int i=1,t;;i<=1){
            v.resize(v.size()+i);
            if(i!=(t=fread(&v[0]+v.size()-i,1,i,f))){
                p=&v[0],e=p+v.size()-i+t;
                break;
            }
        }
15  }
    void ign(){
        while(p!=e&&isspace(*p))
            ++p;
    }
    int isc(){
        return p!=e&&!isspace(*p);
    }
    int isd(){
        return p!=e&&isdigit(*p);
25  }
    FastReader(FILE*_f):
        f(_f){
            ipt();
        }
    FastReader(string _f):
        f(fopen(_f.c_str(),"r")){

```

```

        ipt();
    }
    ~FastReader(){
35         fclose(f);
    }
    template<class T>FastReader&operator>>(T&a){
        int n=1;
        ign();
        if(*p=='-')
            n=-1,++p;
        for(a=0;isd();)
            a=a*10+*p++-'0';
        a*=n;
45         return*this;
    }
    FastReader&operator>>(char&a){
        ign();
        a=*p++;
        return*this;
    }
    FastReader&operator>>(char*a){
        for(ign();isc();)
            *a++=*p++;
55         *a=0;
        return*this;
    }
    char get(){
        return*p++;
    }
};

```

7.4 Fast Writer

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Fast Writer.hpp (866 bytes, 39 lines)

```

#include<bits/stdc++.h>
using namespace std;
struct FastWriter{

```

```

FILE*f;
vector<char>p;
FastWriter(FILE*_f):
    f(_f){
}
9 FastWriter(string _f):
    f(fopen(_f.c_str(),"w")){
}
~FastWriter(){
    if(p.size())
        fwrite(&p[0],1,p.size(),f);
    fclose(f);
}
FastWriter&operator<<(char a){
19     p.push_back(a);
    return*this;
}
FastWriter&operator<<(const char*a){
    while(*a)
        p.push_back(*a++);
    return*this;
}
template<class T>FastWriter&operator<<(T a){
    if(a<0)
        p.push_back('-'),a=-a;
29     static char t[19];
    char*q=t;
    do{
        T b=a/10;
        *q++=a-b*10+'0',a=b;
    }while(a);
    while(q>t)
        p.push_back(*--q);
    return*this;
}
39 };

```

7.5 Number Speller

warning: old style will be replaced ... see Suffix Array (DC3) for new style

Number Speller.hpp (2143 bytes, 72 lines)

```
1  #include<bits/stdc++.h>
   using namespace std;
   namespace NumberSpeller{
       template<class T>string run(T a){
           map<T,string>m;
           m[0]="zero";
           m[1]="one";
           m[2]="two";
           m[3]="three";
           m[4]="four";
11          m[5]="five";
           m[6]="six";
           m[7]="seven";
           m[8]="eight";
           m[9]="nine";
           m[10]="ten";
           m[11]="eleven";
           m[12]="twelve";
           m[13]="thirteen";
           m[14]="fourteen";
           m[15]="fifteen";
21          m[16]="sixteen";
           m[17]="seventeen";
           m[18]="eighteen";
           m[19]="nineteen";
           m[20]="twenty";
           m[30]="thirty";
           m[40]="forty";
           m[50]="fifty";
           m[60]="sixty";
           m[70]="seventy";
31          m[80]="eighty";
           m[90]="ninety";
           if(a<0)
               return"minus "+run(-a);
```

```

    if(m.count(a))
        return m[a];
    if(a<100)
        return run(a/10*10)+"-"+run(a%10);
    if(a<1000&&a%100==0)
41      return run(a/100)+" hundred";
    if(a<1000)
        return run(a/100*100)+" and "+run(a%100);
    vector<string>t;
    t.push_back("thousand");
    t.push_back("million");
    t.push_back("billion");
    t.push_back("trillion");
    t.push_back("quadrillion");
    t.push_back("quintillion");
51    t.push_back("sextillion");
    t.push_back("septillion");
    t.push_back("octillion");
    t.push_back("nonillion");
    t.push_back("decillion");
    t.push_back("undecillion");
    t.push_back("duodecillion");
    t.push_back("tredecillion");
    t.push_back("quattuordecillion");
    t.push_back("quindecillion");
61    string r=a%1000?run(a%1000):"";
    a/=1000;
    for(int i=0;a;++i,a/=1000)
        if(a%1000){
            if(!i&&r.find("and")==string::npos&&r.find("hundred")==
string::npos&&r.size())
                r=run(a%1000)+" "+t[i]+" and "+r;
            else
                r=run(a%1000)+" "+t[i]+(r.size()?"," : "")+r;
        }
    return r;
71 }
}

```
