





## Bill of Materials <a href="#">Parameter Title not found></a>

Source Data From: 智能车\_电磁PCB.PrjPcb

智能车\_电磁PCB.PrjPcb Project:

Variant: None

Creation Date: 2018/5/4 21:05:21 Print Date: 43224 43224.87927

ootprint	Comment	LibRef	Designator	Description	Quantity
I.44LCD	1.44LCD	1.44LCD	1.44LCD		1
0603C	100nF	0603_Cap	C1, C6, C16, C19, C20, C22, C23, C25,	Capacitor	15
			C26, C28, C29, C31, C32, C33, C35	· ·	
0805	10uF	Cap	C2, C10	Capacitor	2
AEC_D6.3	220uF	Cap Pol1	C3, C4, C13, C41	Polarized Capacitor (Radial)	4
0805	100nF	Cap	C5, C9, C15, C45	Capacitor	4
0603C	10nF	0603_Cap	C21, C24, C27, C30, C34, C36	Capacitor	6
1206C	10uF	Cap Pol1	C37, C40, C42, C44, C47, C49	Polarized Capacitor (Radial)	6
0805(2012)	1.5uF	Cap	C38, C43, C46, C48	Capacitor	4
0805(2012)	470PF	Cap	C39	Capacitor	1
SOD-	In4148	Diode	D1, D2, D3, D4, D5, D6, D7, D8, D9, D10,	Typical INFRARED GaAs doide	12
523(0603)			D11, D12		
Diode-1206	IN5819	Diode	D13, D17, D21, D24	Default Diode	4
SMB	IN5819	Diode		Default Diode	9
			D27		
0805(2012)	U	Res Varistor	D18, D25	Varistor (Voltage-Sensitive Resistor)	2
1206	1A	Fuse	F1, F2	Fuse	2
HDR1X4	陀螺仪	Header 4	GYRO	Header, 4-Pin	1
山外KEA核心 -	U*	KEA128-Core	KEA128-Core		1
反 to=to+o o		la di sata	10	l- d d	
电感8*8_0	Inductor	Inductor	L2	Inductor	1
BELL	Bell	Bell	LS1	Bell Hondor 3 Bin Dual row	1
HDR2X3	Header 3X2	Header 3X2	P1, P3	Header, 3-Pin, Dual row	2 1
(T30-垂直	XT30-公-pcb	XT30-公头	D4 D6	Hooder 4 Din Duel row	1 2
HDR2X4	Header 4X2	Header 4X2	P4, P6 P5	Header, 4-Pin, Dual row	1
HDR1X4 HDR1X12	起跑检测 电磁传感器	Header 4 Header 12	P8	Header, 4-Pin Header, 12-Pin	
			P9, P10	neader, 12-Pin	1 2
KT30-垂直 HDR1X4	XT30-母-pcb 预留AD	XT30-母头 Header 4	P11	Header, 4-Pin	1
HDR1X4	预留IO	Header 4	P12	Header, 4-Pin	1
SOT-23	外面IO   S8050	NPN	03	NPN Transistor	1
_R7843_0	IR7843	NMOS-2	Q4, Q5, Q6, Q7, Q8, Q9, Q10, Q11	N-Channel Power MOSFET	8
0603R	1K	0603_Res	R6, R7, R8, R9, R15, R19, R25, R26,	Resistor	23
00031	IIX	0005_1\es	R31, R32, R40, R41, R47, R48, R53, R54,	ivesistoi	23
			R60, R65, R67, R68, R73, R76, R80		
0603R	10K	0603_Res	R10, R11, R13, R14, R16, R17, R18, R20,	Resistor	29
			R21, R23, R24, R33, R34, R36, R37, R42,		
			R43, R45, R46, R55, R56, R61, R62, R63,		
			R64, R70, R71, R78, R79		
0603R	10R	0603 Res	R12	Resistor	1
0603R	37.4K	0603 Res	R22, R30, R44, R52, R66, R69	Resistor	6
3362P	100K	RPot	R27, R35, R49, R57, R72, R77	Potentiometer	6
0603R	330R	0603_Res	R28, R29, R38, R39, R50, R51, R58, R59,	Resistor	12
			R74, R75, R81, R82		
0805	0.22R	Res	R83	Resistor	1
0805	180R	Res	R84	Resistor	1
0805	20R	Res	R85, R86, R89, R90, R95, R96, R97, R98	Resistor	8
0805	10K	Res	R87, R91, R92, R93, R94	Resistor	5
0805	1.2K	Res	R88	Resistor	1
双排两档6脚	SWITCH	SWITCH	S1		1
发码开关4-	贴片拨码开关	SW DIP-4	S2, S5	DIP Switch, 4 Position, SPST	2
2.54间距	1	1			
SMT_BUTTO	SW-PB	SW-PB	S3, S4, S6, S7	Switch	4
N					
SWICH_2	SW-SPDT	SW-SPDT	S8	SPDT Subminiature Toggle Switch, Right	1
				Angle Mounting, Vertical Actuation	
_R7843_0	AMS1085-5	U22	U1		1
_R7843_0	AMS1085-3.3	U22	U3		1
rssop14	74HC74	74HC74	U4		1
rssop14	INA2332	INA2332_1	U5, U6, U7		3
R2104	IR2104S	Component_1_1 74HC00	U8, U10, U12, U13 U9	4	4
MC34063 74lvc245	MC34063 74lvc245		U11	9/05/4443 9/4中亚维格共正	1
	7 4IVUZ4O	74lvc245	011	8位5伏转3.3伏电平转换芯片	1
rssop	I	1	l .	l .	209
Approved		Notes			209
-ppi o reu					
		1			
		<u> </u>			
		-			