Unit 3 Exercises

4SC000 Optimal Control and Reinforcement Learning

Duarte Antunes

A runnable Python companion to these exercises – Dijkstra's algorithm, A*, and the DP algorithm applied to graphs – is available in `code/unit3/` (see its `README.md`).

Core exercises

Problem 3.1 Consider a weighted graph characterized by the following matrix

$$W = \begin{bmatrix} 0 & 0 & \infty & \infty & 1 \\ 3 & 0 & 5 & 3 & 1 \\ \infty & 5 & 0 & 1 & 3 \\ \infty & \infty & 1 & 0 & 1 \\ 1 & 1 & 3 & 1 & 0 \end{bmatrix}$$

where each component W_{ij} of row i and column j denotes the cost of the link from node i to node j ($W_{ij} = \infty$ indicates that there is no link from node i to node j).

(i) Compute a shortest path from node 1 to node 3 using the dynamic programming algorithm.
(ii) Compute a shortest path from node 1 to node 3 using Dijkstra's algorithm.
(iii) For each node $i \in \{1, \dots, 5\}$, indicate the first node (immediately after i) of the optimal path from node i to node 3.

Solution

(i) Running the dynamic programming algorithm on the transition diagram associated with the graph (the graph repeated at each stage, working backward from node 3) gives the costs-to-go and optimal decisions shown below. Reading off the boxed decisions from node 1 traces out a shortest path of cost 3.




Fig. 1: DP algorithm applied to the transition diagram associated with the graph




Fig. 2: Shortest path from node 1 to node 3

(ii) Running Dijkstra's algorithm from node 1:

Iteration	Open list (node, estimated distance to node 1)	Previous node
0	$\{1, 0\}$	
1	$\{2, 0\}, \{5, 1\}$	$\beta(2) = 1$, $\beta(5) = 1$
2	$\{5, 1\}, \{3, 5\}, \{4, 3\}$	$\beta(3) = 2$, $\beta(4) = 2$
3	$\{3, 4\}, \{4, 2\}$	$\beta(3) = 5$, $\beta(4) = 5$
4	$\{3, 3\}$	$\beta(3) = 4$

A shortest path can be read off from this table: $1 \to 5 \to 4 \to 3$, matching (i) (cost 3).
(iii) Combining the answers above (the first node of the optimal path to node 3, for every possible starting node):

State	First node of the optimal path to 3
1	5
2	5
3	3
4	3
5	4

Problem 3.2 Consider the weighted graph depicted below. Compute the shortest path from node 1 to node 11 using:

(i) Dijkstra's algorithm.
(ii) the A* algorithm with the following heuristic h

node i	1	2	3	4	5	6	7	8	9	10	11
$h(i)$	0	25	50	15	16	50	9	7	50	0	0




Fig. 3: Directed graph

Solution

(i) Dijkstra's algorithm:

Iteration	List of open nodes (node, estimate of the distance from node to node 1)
0	$\{1, 0\}$
1	$\{3, 1\}, \{4, 10\}, \{2, 10\}$
2	$\{6, 2\}, \{4, 10\}, \{2, 10\}$
3	$\{9, 3\}, \{4, 10\}, \{2, 10\}$
4	$\{11, 103\}, \{4, 10\}, \{2, 10\}$
5	$\{11, 103\}, \{7, 20\}, \{2, 10\}$
6	$\{11, 103\}, \{7, 20\}, \{5, 20\}$

7	$\{11, 103\}, \{10, 30\}, \{5, 20\}$
8	$\{11, 103\}, \{10, 30\}, \{8, 30\}$
9	$\{11, 31\}, \{8, 30\}$
10	$\{11, 31\}$

(ii) A* algorithm: first apply the transformation $\bar{c}_{ij} = c_{ij} + h(j) - h(i)$ (valid here because the transformed costs $\bar{c}_{ij}$ remain non-negative), giving the transformed graph below.




Fig. 4: New graph after the transformation $\bar{c}_{ij} = c_{ij} + h(j) - h(i)$

Iteration	List of open nodes (node, estimate of the distance from node to node 1)
0	$\{1, 0\}$
1	$\{4, 25\}, \{1, 51\}, \{2, 35\}$
2	$\{7, 29\}, \{1, 51\}, \{2, 35\}$
3	$\{10, 30\}, \{1, 51\}, \{2, 35\}$
4	$\{11, 31\}$

Both algorithms find the same shortest path (A* reaches the answer in far fewer iterations, thanks to the heuristic).

Additional exercises

Problem 3.3 Consider the transition diagram depicted below. For each initial state at stage 0 compute one optimal path minimizing the cost incurred from stage 0 to stage 4, using Dijkstra's algorithm.




Fig. 5: Transition diagram

Solution

We start by relabeling the nodes as depicted below (this makes it easier to run Dijkstra's algorithm on a single graph rather than tracking stages explicitly).




Fig. 6: Graph with nodes relabeled

There are two possible initial states (nodes 1 and 2) and two possible final states (nodes 13 and 14); the optimal path from each initial state is obtained by running Dijkstra's algorithm to both final nodes and keeping the cheaper one.

From node 1. Computing the optimal path from node 1 to node 13:

Iteration	List of open nodes (node i, estimate of the distance from i to 1)
0	$\{1,0\}$
1	$\{3,1\},\{4,2\}$
2	$\{4,2\},\{6,5\},\{7,4\}$
3	$\{6,5\},\{7,2\},\{8,3\}$
4	$\{6,5\},\{8,3\},\{10,5\},\{11,4\}$
5	$\{6,5\},\{10,5\},\{11,3\},\{12,4\}$
6	$\{6,5\},\{10,5\},\{12,4\},\{13,5\},\{14,7\}$
7	$\{6,5\},\{13,5\},\{14,7\}$

The distance to node 13 is 5. Computing the optimal path from node 1 to node 14 (same procedure, table omitted) gives a distance of 7. Since $5 < 7$, the optimal path from node 1 has cost 5 and is

Stage	0	1	2	3	4
Node	1	2	3	2	1

(node numbers here refer to the *original* diagram's stage-labels along the path, recovered from the relabeled graph).

From node 2. Computing the optimal path from node 2 to node 13:

Iteration	List of open nodes (node i, estimate of the distance from i to 2)
0	$\{2,0\}$
1	$\{4,4\},\{5,4\}$
2	$\{5,4\},\{7,4\},\{8,5\}$
3	$\{7,4\},\{8,5\},\{9,5\}$
4	$\{8,5\},\{9,5\},\{10,7\},\{11,6\}$
5	$\{9,5\},\{10,7\},\{11,5\},\{12,6\}$
6	$\{10,7\},\{11,5\},\{12,5\}$
7	$\{10,7\},\{12,5\},\{13,7\},\{14,9\}$
8	$\{10,7\},\{13,7\},\{14,9\}$
9	$\{13,7\},\{14,9\}$


The distance to node 13 is 7. Computing the optimal path from node 2 to node 14 gives a distance of 9. Since $7 < 9$, the optimal path from node 2 has cost 7 and is

Stage	0	1	2	3	4
Node	2	2	3	2	1

Problem 3.4 A cost-minded traveler visiting Hawaii wants to fly from Kauai to Maui and checks the prices of the flights for the next day, summarized in the table below. A direct flight costs 300 money units, and the traveler believes that there should be a cheaper non-direct flight. He estimates that he can do trips with at most 4 hops and he is interested in knowing what is the best price with at most 2, 3 and 4 hops to compare the options.

(i) Provide the answers that the traveler is looking for using the dynamic programming algorithm.
(ii) Would there be a better option if 5 hops were allowed?
(iii) Solve (i) with Dijkstra's algorithm.

Arrival \ Departure	Oahu	Hawaii	Kauai	Lanai	Maui	Molok
Oahu	–	90	70	105	130	95
Hawaii	95	–	80	55	100	115
Kauai	75	105	–	135	250	85
Lanai	105	35	120	–	40	100
Maui	130	95	300	45	–	140
Molokai	90	120	80	95	95	–



Solution

(i)-(ii) Running the DP algorithm on the transition diagram associated with the graph gives the costs-to-go and decisions shown below. Rather than building the full transition diagram directly (tedious, since every node at one stage connects to every node at the next), it is easier to start from the cost-to-go associated with the last step (stage 4, simply the cost of the direct link from each city to Maui, or ∞ if none) and then, at each earlier stage k, compute for every state i

$$\min_j c_{ij} + J_{k+1}(j),$$

where c_{ij} is the cost of the link from i to j and $J_{k+1}(j)$ is the cost-to-go already found for j at the next stage.




Fig. 7: DP algorithm applied to the transition diagram associated with the graph

At each iteration ℓ of the algorithm, the cost-to-go for a given node corresponds to the optimal cost to reach the destination with ℓ hops. Reading the row for Kauai:


- With 2 hops, the optimal cost is 165, via Kauai → Lanai → Maui.
- With 3 hops, the optimal cost is 160, via Kauai → Hawaii → Lanai → Maui.
- With 4 hops, the optimal cost is still 160 (same path).
- With 5 hops, the optimal cost is also still 160 (same path) – allowing a fifth hop does not help.

(iii) Running Dijkstra's algorithm from Kauai:


Iteration	List of open nodes (node, estimate of the distance from node to Kauai)
0	{Kauai, 0}
1	{Oahu, 70}, {Hawaii, 80}, {Lanai, 120}, {Maui, 300}, {Molokai, 80}
2	{Hawaii, 80}, {Lanai, 120}, {Maui, 200}, {Molokai, 80}
3	{Lanai, 115}, {Maui, 175}, {Molokai, 80}
4	{Lanai, 115}, {Maui, 175}
5	{Maui, 160}

confirming the optimal path Kauai → Hawaii → Lanai → Maui, cost 160.


Problem 3.5 Although we have only considered so far graphs with non-negative weights, it is possible to apply the dynamic programming algorithm to find the shortest path in graphs with negative weights, under a certain condition. The aim of this exercise is to find such a condition. Consider the following three graphs.



(a) (a)



(a) (b)



(a) (c)

(i) Apply the dynamic programming algorithm to obtain the shortest path from the initial node 2 to the final node 1 for graphs (a), (b) and (c).
(ii) Compare the shortest path that you have found for graph (c) with the cost of the following path $2 \to 4 \to 3 \to 2 \to 4 \to 3 \to 1$. Is the path found in (i) optimal?
(iii) Can you find a path with a smaller cost for graph (b) than the one found in (i)?
(iv) Can you find a condition under which the dynamic programming algorithm finds the shortest path for graphs with negative weights?
(v) Would it be possible to apply Dijkstra's algorithm?

i Solution

(i) Running the DP algorithm (with 3 stages, since the shortest path here never needs more than 3 hops) for each graph gives the costs-to-go and shortest path shown below; in all three cases DP reports the same path $2 \to 4 \to 3 \to 1$.




Fig. 11: DP applied to graphs (a), (b), (c)

(ii) For graph (c), the path $2 \to 4 \to 3 \to 1$ found in (i) has length 3, whereas the longer path $2 \to 4 \to 3 \to 2 \to 4 \to 3 \to 1$ has length 1. So the path found by DP in (i) is *not* optimal for graph (c) – DP fails here because graph (c) contains a negative-cost cycle ($3 \to 2 \to 4 \to 3$ has cost $-4+1+1=-2<0$), so the cost can be driven arbitrarily low by cycling and DP (which only searches out to a fixed number of hops) misses this.
(iii) No, it is not possible: for graph (b) the DP path from (i) is already optimal.
(iv) DP finds the shortest path for a graph with negative weights provided there are no negative-cost cycles reachable from the initial node and reaching the final node – with such a cycle, as seen in (ii), the cost can be decreased without bound and no shortest path exists.
(v) Dijkstra's algorithm only works for graphs with non-negative weights; of the three graphs above, it could only be applied to (a).