

Lily Hsiao

March 20, 2017

[1]. [2]. [3]. [4]. [5].

## References

- [1] J. Wright, A. Y. Yang, A. Ganesh, S. S. Sastry, and Y. Ma, “Robust face recognition via sparse representation,” *IEEE transactions on pattern analysis and machine intelligence*, vol. 31, no. 2, pp. 210–227, 2009.
- [2] I. Kemelmacher-Shlizerman and R. Basri, “3d face reconstruction from a single image using a single reference face shape,” *IEEE transactions on pattern analysis and machine intelligence*, vol. 33, no. 2, pp. 394–405, 2011.
- [3] A. R. Rivera, J. R. Castillo, and O. O. Chae, “Local directional number pattern for face analysis: Face and expression recognition,” *IEEE transactions on image processing*, vol. 22, no. 5, pp. 1740–1752, 2013.
- [4] S. Ren, X. Cao, Y. Wei, and J. Sun, “Face alignment at 3000 fps via regressing local binary features,” in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2014, pp. 1685–1692.
- [5] S. Zhu, C. Li, C.-C. Loy, and X. Tang, “Unconstrained face alignment via cascaded compositional learning,” in *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, 2016, pp. 3409–3417.