CPAO Sharing session

Liquibase

Capgemini AIRBUS

CPAO Sharing session - Liquibase What is it? Why to use it?




Liquidbase, Liquidbased Liquibase

What is it?

- DevOps environment
- **Database Management**
- Flexible database change: define changes in SQL, XML, JSON, or YAML
- Version control for your database
- Order changes and standardize development
- Automatic Deployment
- Control when, where, and how database changes are deployed.

Why to use it?

- Auto-generate SQL scripts
- Repeatable migrations
- Integrations and extensions (Maven, Spring boot...)
- Rollbacks
- Context-dependent logic
- Use contexts and preconditions to fine-tune script execution



CPAO Sharing session - Liquibase Installation 1/2



- Liquibase standalone jar
 - Download from https://download.liquibase.org/
 - No database configuration needed, information are given as parameters

```
liquibase --driver=oracle.idbc.OracleDriver --classpath=\path\to\classes:idbcdriver.jar
--changeLogFile=com/example/db.changelog.xml
--url="jdbc:oracle:thin:@localhost:1521:XE" --username=scott --password=tiger generateChangeLog
```

- non-spring project such as ACMM could use this method
- Maven plugin integration

```
<plugin>
   <groupId>org.liquibase</groupId>
   <artifactId>liquibase-maven-plugin</artifactId>
   <configuration>
       cpropertyFile>src/main/resources/liquibase.properties
   </configuration>
</plugin>
```

```
driver: oracle.jdbc.OracleDriver
url: jdbc:oracle:thin:@//192.168.99.100:1521/xe
username: 0470 CMPM
password: cmpm
verbose: true
dropFirst: false
outputChangeLogFile=src/main/resources/liquibase-outputChangeLog.xml
changeLogFile=src/main/resources/db/changelog/liquibase-changeLog.xml
```

CPAO Sharing session - Liquibase Installation 2/2



- Spring (Boot) integration:
- ACP, ICC-CUSTO
 - Configuration in application.properties

```
<dependency>
   <groupId>org.liquibase
   <artifactId>liquibase-core</artifactId>
</dependency>
```

```
#LiquiBase
liquibase.enabled=true
liquibase.change-log=classpath:/db/changelog/liquibase-changeLog.xml
liquibase.drop-first=false
liquibase.contexts=@liquibase.context@
```

- MODMGT
 - Double datasource Oracle/DB2: configuration with Spring beans

```
@Primary
Bean
   liquibase.setDataSource(dataSource);
   liquibase.setChangeLog (ConfigurationConstants.LIQUIBASE ORACLE CHANGELOG CLASSPATH);
   LOGGER.info( message: "oracleLiquibase() > context={}", liquibaseContext);
   liquibase.setContexts(liquibaseContext);
   return liquibase;
```

```
public SpringLiquibase ibmLiquibase(@Qualifier("Db2DataSourceNOMENCLATURE")DataSource dataSource) {
   SpringLiquibase liquibase = new SpringLiquibase();
   liquibase.setChangeLog(ConfigurationConstants.LIQUIBASE DB2 CHANGELOG CLASSPATH);
   String liquibaseContext = env.getProperty(ConfigurationConstants.ENV PROPERTY KEY LIQUIBASE CONTEXT)
   liquibase.setDatabaseChangeLogTable(ConfigurationConstants.LIQUIBASE DB2 CHANGELOG TABLE);
   return liquibase;
```

CPAO Sharing session - Liquibase Configuration and architecture



- Tree configuration
 - liquibase-changeLog.xml

```
<?xml version="1.1" encoding="UTF-8" standalone="no"?>
<databaseChangeLog xmlns="http://www.liquibase.org/xml/ns/dbchangelog"</pre>
    <includeAll path="classpath:/db/changelog/install/sequences/" />
    <includeAll path="classpath:/db/changelog/install/tables/" />
    <includeAll path="classpath:/db/changelog/install/index/" />
    <includeAll path="classpath:/db/changelog/install/constants/" />
    <includeAll path="classpath:/db/changelog/latest/synonyms/" />
    <includeAll path="classpath:/db/changelog/latest/triggers/" />
    <includeAll path="classpath:/db/changelog/latest/views/" />
    <includeAll path="classpath:/db/changelog/data/"/>
    <includeAll path="classpath:/db/changelog/latest/updates"/>
</databaseChangeLog>
```

- Liquibase tree example
 - XML naming convention
 - AAAAMMJJ name.xml

```
v 🔄 db

∨ Changelog

     > 🗁 data
     > install

✓ ☐ latest
        > @ grants
        > in synonyms
        triggers
             20180302 cr_trigger.xml
             20180302_publish_trigger.xml
        > 🗁 updates
        > iews
     > a sql
        1/2 liquibase-changeLog.xml
```

```
✓ ■ db.changelog
     > data
           4 20200420_init_nom_tables_db2_dev.xml
    > sql

✓ ■ oracle

✓ install

               🚜 20200102_init_sequences.xml
               a 20200220_uac_init_sequences.xml
               🚜 20200313_scheduler_init_sequences.xml
      db2-liquibase-changeLog.xml
      🏭 oracle-liquibase-changeLog.xml
   application properties
```

CPAO Sharing session - Liquibase ChangeLog Initialization



- For existing tables, indexes, PK/FK...
- ChangeLog generation threw commands
 - Standalone Liquibase

liquibase --driver=oracle.jdbc.OracleDriver --classpath=\path\to\classes:jdbcdriver.jar --changeLogFile=com/example/db.changelog.xml --url="jdbc:oracle:thin:@localhost:1521:XE" --username=scott --password=tiger generateChangeLog

https://www.liquibase.org/documentation/generating_changelogs.html

Maven plugin:

mvn liquibase:generateChangeLog

http://www.liquibase.org/documentation/maven/maven_generateChangeLog.html

- Views, synonyms have to be done manually
- Context have to be set manually

CPAO Sharing session - Liquibase What is a changeset



- Description of a Database Change
- Contains Metadata of information
 - id (required),
 - author (required),
 - dbms,
 - failOnError (default value: true),
 - runAlways (default value: false),
 - runOnChange (default value: false), ...
- Specific changes, sql, ...

<changeSet author="cmpm" id="CMPM-DEV-ACPROGRAM" context="dev" runOnChange="true">

<sqlFile path="classpath:/db/changelog/sql/acprogram.sql" />

</changeSet>

CPAO Sharing session - Liquibase What is a changeset - configuration



- Precondition
 - primaryKeyExists,
 - indexExists.
 - tableExists, ...

```
<changeSet author="cmpm" id="CMPM-INDEX-CR-CREATOR NEW">
    <preConditions onFail="MARK RAN">
        <sglCheck expectedResult="0">SELECT COUNT(1) FROM USER INDEXES WHERE TABLE NAME = 'CHANGEREQUEST' AND INDEX NAME = 'IDX CR CREATOR'</sglCheck>
   </preConditions>
    <createIndex indexName="idx_cr_creator" tableName="CHANGEREQUEST">
        <column name="CREATOR" type="varchar(128)"/>
    </createIndex>
    <rollback>
    </rollback>
```

- Rollback
 - Tag,
 - Date,
 - Changeset count, ...
- Profile (context="dev", context="prod", no context)

</changeSet>

```
<changeSet author="cmpm" id="CMPM-DEV-ACPROGRAM" context="dev" runOnChange="true">
    <sqlFile path="classpath:/db/changelog/sql/acprogram.sql" />
</changeSet>
```

CPAO Sharing session - Liquibase What is a changeset - some examples



Create Table

```
<changeSet author="liquibase-docs" id="createTable-example">
    <createTable catalogName="cat"</pre>
            remarks="A String"
            schemaName="public"
            tableName="person"
            tablespace="A String">
        <column name="address" type="varchar(255)"/>
    </createTable>
</changeSet>
```

Drop Table

```
<changeSet author="liquibase-docs" id="dropTable-example">
    <dropTable cascadeConstraints="true"</pre>
            catalogName="cat"
            schemaName="public"
            tableName="person"/>
</changeSet>
```

CPAO Sharing session - Liquibase What is a changeset - some examples



Insert

```
<changeSet author="liquibase-docs" id="insert-example">
    <insert catalogName="cat"</pre>
            dbms="!h2, mysql"
            schemaName="public"
            tableName="person">
        <column name="address" value="address value"/>
   </insert>
</changeSet>
```

Delete

```
<changeSet author="liquibase-docs" id="delete-example">
    <delete catalogName="cat"
           schemaName="public"
           tableName="person">
       <where>name='Bob'</where>
    </delete>
</changeSet>
```

CPAO Sharing session - Liquibase What is a changeset - some examples



SQL

```
<changeSet author="liquibase-docs" id="sql-example">
 <sql dbms="!h2, oracle, mysql"
  endDelimiter="\nGO"
  splitStatements="true"
  stripComments="true">insert into person (name) values ('Bob')
<comment>What about Bob?</comment>
  </sql>
</changeSet>
```

SQL File

```
<changeSet author="liquibase-docs" id="sqlFile-example">
     <sqlFile dbms="!h2, oracle, mysql"
        encoding="UTF-8"
        endDelimiter="\nGO"
       path="my/path/file.sql"
        relativeToChangelogFile="true"
        splitStatements="true"
        stripComments="true"/>
</changeSet>
```

• More commands on <u>liquibase doc</u>.

CPAO Sharing session - Liquibase **Database Changelog**




- Changes logs
 - ID
 - Author
 - Filename
 - Date executed
 - Order executed
 - Exec type (Executed, reran...)
 - MD5SUM
 - Description
 - Comments
 - Tag
 - Liquibase (Version)
 - Contexts
 - Labels
 - Deployment id


⊕ ID	♦ AUTHOR	∯ FILENAME		ORDEREXEC ♦ EXECTY
CMPM-DEV-METADATA	cmpm	db/changelog/data/20180302_metadata.xml	03-JUL-18 14.59.01.783751000	392 RERAN
CMPM-MP-METADATA	cmpm	db/changelog/install/tables/20180703_metadata_mp.xml	03-JUL-18 14.22.51.393987000	391 EXECUTE
CMPM-TABLE-CHANGEREQUEST_AUD-FFA-CHANGETY	. cmpm	db/changelog/install/tables/20180605_onepagerMigrate.xml	02-JUL-18 14.17.59.452672000	390 EXECUTE
CMPM-UPDATE-CRSTATUSCLEANUP	cmpm	db/changelog/latest/updates/20180302_crStatusCleanUp.xml	25-JUN-18 13.09.06.200737000	389 EXECUTE
CMPM-UPDATE-AGENDACLEANUP	cmpm	db/changelog/latest/updates/20180302_agendaCleanUp.xml	25-JUN-18 13.09.05.734329000	388 EXECUTE
CMPM-DEV-INDUSCHOICE	cmpm	db/changelog/data/20180525_industrialChoice.xml	25-JUN-18 13.09.05.010041000	387 EXECUTE
CMPM-DEV-DECISIONTYPE	cmpm	db/changelog/data/20180309_decisionType.xml	25-JUN-18 13.09.04.979688000	386 EXECUTE
CMPM-DEV-VERSIONRANK	cmpm	db/changelog/data/20180302_versionrank.xml	25-JUN-18 13.09.04.569885000	385 EXECUTE
CMPM-DEV-VERSION	cmpm	db/changelog/data/20180302_version.xml	25-JUN-18 13.08.51.739442000	384 EXECUTE
CMPM-DEV-TECHPUBMANUAL	cmpm	db/changelog/data/20180302_techPubManual.xml	25-JUN-18 13.08.50.195848000	383 EXECUTE
CMPM-INSERT-SURVEY	cmpm	db/changelog/data/20180302_survey.xml	25-JUN-18 13.08.50.035559000	382 EXECUTE
CMPM-DEV-SUPPLIER	cmpm	db/changelog/data/20180302_supplier.xml	25-JUN-18 13.08.49.338768000	381 EXECUTE
CMPM-DEV-STD	cmpm	db/changelog/data/20180302_standard.xml	25-JUN-18 13.08.49.144266000	380 EXECUTE
CMPM-DEV-ROLE	cmpm	db/changelog/data/20180302_role.xml	25-JUN-18 13.08.48.999521000	379 EXECUTE
CMPM-DEV-REASONS	cmpm	db/changelog/data/20180302_reasons.xml	25-JUN-18 13.08.48.966492000	378 EXECUTE
CMPM-DEV-POLICY	cmpm	db/changelog/data/20180302_policy.xml	25-JUN-18 13.08.48.839532000	377 EXECUTE
CMPM-DEV-MSN	cmpm	db/changelog/data/20180302_msn.xml	25-JUN-18 13.08.48.501232000	376 EXECUTE
CMPM-DEV-MP	cmpm	db/changelog/data/20180302_mp.xml	25-JUN-18 13.08.42.323214000	375 EXECUTE
CMPM-DEV-MODEL	cmpm	db/changelog/data/20180302_model.xml	25-JUN-18 13.08.38.103286000	374 EXECUTE
CMPM-DEV-MOD	cmpm	db/changelog/data/20180302_mod.xml	25-JUN-18 13.08.37.623145000	373 EXECUTE
CMPM-DEV-INDUSSID	cmpm	db/changelog/data/20180302 industrialstandard.xml	25-JUN-18 13.08.33.098707000	371 EXECUTE

CPAO Sharing session - Liquibase Database Changelog lock



- Handle parallel execution
 - ID
 - Locked
 - LockGranted
 - LockedBy





About Capgemini

A global leader in consulting, technology services and digital transformation, Capgemini is at the forefront of innovation to address the entire breadth of clients' opportunities in the evolving world of cloud, digital and platforms. Building on its strong 50-year heritage and deep industry-specific expertise, Capgemini enables organizations to realize their business ambitions through an array of services from strategy to operations. Capgemini is driven by the conviction that the business value of technology comes from and through people. It is a multicultural company of 200,000 team members in over 40 countries. The Group reported 2016 global revenues of EUR 12.5 billion.

Learn more about us at

www.capgemini.com

This message contains information that may be privileged or confidential and is the property of the Capgemini Group.

Copyright © 2017 Capgemini. All rights reserved.