

C.2.2 Exam Practice 2: Security

Date: 5/3/2026, 10:15:55 PM

Time Spent: 14:06

Score: 88%

Passing Score: 80%



Question 1

✓ Correct

What is a type of device that must meet the profile that the company requires, and the employee will have to agree on the installation of corporate apps and to some level of oversight and auditing, even though the device belongs to the employee and not the company?

☐ COBO☐ CYOD☐ COPE☒ BYOD ✓ Correct

Explanation

Bring your own device (BYOD) is a mobile device owned by the employee. The mobile is usually the most popular with employees but poses the most difficulties for security and network managers.

A corporate-owned business only (COBO) device is the company's property and may only be used for company business.

Corporate-owned, personally enabled (COPE) is when the company chooses and supplies the device, and it remains the company's property. The employee may use it to access personal email, social media accounts, and personal web browsing.

Choose your own device (CYOD) is like COPE, but the employee can choose the device they want from a list.

Related Content

[20.1.4 Mobile Device Management](#)[resources\questions\pt_core2_220_1202_2_8_005.question.xml](#)

Question 2

✕ Incorrect

A company's IT support specialist is ready to start recommissioning a system as part of the malware removal process. What is the last step before removing the computer from quarantine?

☒ Create a fresh restore point. ✕ Incorrect

☐ Antivirus scan ✓ Correct

☐ Re-enable System Restore.

☐ Verify DNS configuration.

Explanation

Before removing a computer system from quarantine, the final step is to run another antivirus scan to make sure the system is clean.

Creating a new restore point (or system image) is one component of recommissioning and is done after re-enabling the System Restore but before running a final antivirus scan.

Re-enabling the System Restore is the beginning of the recommissioning process, along with re-enabling any disabled automatic backups.

Verifying Domain Name System (DNS) configuration to prevent reinfection is part of recommissioning, but it comes before the final antivirus scan.

Related Content

19.4.8 Best Practices for Malware Removal

resources\questions\pt_core2_220_1202_2_6_008.question.xml

Question 3

✔ Correct

Which of the following uses a security shield icon for tasks that are protected under them?

- ☐ Fingerprint
- ☐ SSO
- ☐ PIN

☒ UAC ✔ Correct

Explanation

User account control (UAC) is a Windows security feature designed to protect the system against malicious scripts and attacks that could exploit the powerful privileges assigned to members of the Administrators group.

A personal identification number (PIN) can contain letters and symbols. It is a passcode used to process the authentication of a user accessing a system.

A fingerprint is a type of bio gesture authentication that uses a sensor to scan the unique features of the user's fingerprint.

Single sign-on (SSO) means that a user authenticates once to a device or network to access multiple applications or services.

Related Content

15.1.7 User Account Control

resources\questions\pt_core2_220_1202_2_2_003.question.xml

Question 4

✔ Correct

A user calls the help desk with issues consistent with a malware infection, although the user received no alert. The technician confirms that there was no malware alert. Which of the following options would be an appropriate next step? (Select two.)

- ☒ Update the antivirus software. ✔ Correct
- ☐ Remove the malware.
- ☐ Log on to the system as an administrator.
- ☒ Scan the system using different antivirus software. ✔ Correct

Explanation

Since the installed antivirus software did not pick up the malware infection, scanning the system with a different antivirus product is a good option since some products pick up what others do not.

The antivirus software may not have detected the malware infection because it was not updated. Updating antivirus software before running scans is a best practice.

Logging on to a malware-infected system as an administrator exposes their privileged account access credentials for the malware to exploit.

Removing the malware is a few steps ahead of the current scenario.

Related Content

resources\questions\pt_core2_220_1202_2_6_005.question.xml

Question 5

✕ Incorrect

A lawyer opens an email attachment that appears to be a court summons, but it is malware. The law firm's IT consultant quarantines the lawyer's system and then disables System Restore. Which of the following should IT disable?

- ☐ RADIUS
- ☐ Nearby Share
- ☐ File History ✓ Correct
- ☒ File sharing ✕ Incorrect

Explanation

File History is a Windows feature for automatically backing up user data. Any automated backup systems (like File History) should be disabled, and any backup copies should be scanned for malware since they could also be infected.

File sharing is a Windows firewall configuration that opens the network ports required to operate as a file/print server.

Remote Authentication Dial-in User Service (RADIUS) is a protocol used to manage remote and wireless authentication infrastructures.

Nearby Share is an Android feature for file sharing between a PC and smartphone or other devices over Bluetooth in a personal area network (PAN).

Related Content

resources\questions\pt_core2_220_1202_2_6_004.question.xml

Question 6

✔ Correct

A company uses a method that restricts its employees from changing or adjusting their computer settings. What is this method called?

☒ BIOS password ✔ Correct

- ☐ Expiration requirements
- ☐ Disable guest accounts
- ☐ Secure PII and passwords

Explanation

Basic input/output (BIOS) password is a piece of authentication information that may sometimes require logging into a computer's basic input/output system (BIOS) before the machine can boot up.

Expiration requirement means that the user must change the password after a set period.

Secure personal identifiable information (PII) and passwords are when paper copies of personal and confidential data must not leave where they could be read or stolen. This type of information should not be entered into unprotected plain text files, word processing documents, or spreadsheets.

Disabling guest accounts allows unauthorized access to the computer and may provide some network access. It is only enabled to facilitate passwordless file sharing in a Windows workgroup.

Related Content

19.1.1 Password Best Practices

resources\questions\pt_core2_220_1202_2_7_001.question.xml

Question 7

✔ Correct

What method uses the process of exposing the device to a high-intensity magnetic field that leaves the object magnetically impartial?

- ☐ Incinerating
- ☐ Certificate of destruction
- ☐ Erasing/wiping

☒ Degaussing ✓ Correct

Explanation

Degaussing is when a hard disk is exposed to a powerful electromagnet that disrupts the magnetic pattern that stores the data on the disk surface.

Incinerating is when the disk is exposed to high heat to melt its components. This should be performed in a furnace designed for media sanitization. Municipal incinerators may leave remnants.

Erasing/wiping software ensures that old data is removed using zeroes or random patterns, leaving the disk in a “clean” state, ready to be passed to the new owner.

A certificate of destruction shows the make, model, and serial number of each drive that was handled, plus the date of destruction and how it was destroyed.

Related Content

21.2.6 Disposal and Recycling Outsourcing Concepts

resources\questions\pt_core2_220_1202_2_9_004.question.xml

Question 8

✔ Correct

A user requests a site's certificate, but an evil twin intercepts the request and presents a spoofed certificate, which the user's browser accepts. What has just happened? (Select three.)

☒ An on-path attack ✔ Correct☐ A rootkit attack☒ The user thinks they have a secure connection. ✔ Correct☒ Malware is in the middle of the session. ✔ Correct**Explanation**

An on-path attack is when a threat actor, such as an evil twin, intercepts traffic between two hosts. In this case, it was via a spoofed digital certificate.

In the middle of the session, the evil twin intercepts traffic between two hosts; this was known as a "Man-in-the-Middle" attack in a former time.

Since the user's browser has accepted the spoofed digital certificate, the user believes they have a secure session, even though they do not.

A rootkit is malware that modifies system files, often at the kernel (root) level.

Related Content

18.1.4 Phishing and Evil Twins

resources\questions\pt_core2_220_1202_3_4_012.question.xml

Question 9

✓ Correct

Which of the following accounts can users set up profile settings to synchronize between devices via the online portal?

☒ Microsoft account ✓ Correct

☐ Guest user

☐ Local account

☐ Administrator

Explanation

Microsoft accounts are managed via an online portal and identified by an email address. Configuring access to an account creates a profile associated with a local account.

A local account is defined on that computer only and stored in a database known as the security account manager (SAM). A local account cannot log on to a different computer or access a file over the network.

A user account from the administrators group can perform all management tasks and generally has very high access to all files and other objects in the system.

A guest user is a group only present for a legacy reason. It has the same default permissions and rights as the user group.

Related Content

15.1.6 User and Group Accounts

resources\questions\pt_core2_220_1202_2_2_001.question.xml

Question 10

✓ Correct

Users perform a technique that tends to select C, M, N, O, and S shapes. Which of the following is this?

- ☐ PIN
- ☐ Swipe
- ☐ Facial recognition
- ☒ Pattern ✓ Correct

Explanation

Pattern requires the user to swipe a “join-the-dots” pattern. The pattern method has numerous weaknesses.

Swipe is a gesture that means that access to the device is unauthenticated. Simply swiping across the screen will unlock the device.

Facial recognition is a method that creates a template computer from a 3-D image of the user’s face. A facial bio gesture has the advantage of using the camera rather than a special sensor.

Personal identification numbers (PINs) are used on most devices to enable screen lock authentication and generate an encryption key. The PIN can act as a primary or backup authentication method.

Related Content[20.1.1 Screen Locks](#)[resources\questions\pt_core2_220_1202_2_8_002.question.xml](#)

Question 11

✔ Correct

An administrator uses a method that assigns permissions and rights to a collection of user accounts. What is this called?

- ☐ MFA
- ☐ Least privilege
- ☒ Security group ✔ Correct
- ☐ ACL

Explanation

A security group is a collection of user accounts, as it is more efficient to assign permissions to a group than to assign them individually to each user.

Access control list (ACL) allows each access control entry (ACE) to identify a subject and its permissions for the resource. A subject could be a human user, a computer, or a software service.

Least privilege means that a user should be granted the minimum possible rights necessary to perform that job, which can be complex to apply in practice.

Multifactor authentication (MFA) means that the user must submit at least two different credentials.

Related Content

13.1.6 Local Users and Groups Console

resources\questions\pt_core2_220_1202_2_1_001.question.xml

Question 12

✔ Correct

What technique is used on hard drives that reset them to factory condition?

- ☐ Erasing/wiping
- ☐ Certificate of destruction
- ☒ Low-level formatting ✓ Correct
- ☐ Third-party vendor

Explanation

A low-level formatting tool resets a disk to its factory condition. Most of these tools will now incorporate some sanitize function. Secure erase (SE), and instant secure erase (ISE) are two functions of this tool.

Third-party vendors may use overwriting or crypto-erase and issue a certificate of recycling rather than destruction.

A certificate of destruction shows the make, model, and serial number of each drive that was handled, plus the date of destruction and how it was destroyed.

Erasing/wiping software ensures that old data is removed using zeroes or random patterns, leaving the disk in a “clean” state, ready to be passed to the new owner.

Related Content

21.2.5 Data Destruction Methods

resources\questions\pt_core2_220_1202_2_9_006.question.xml

Question 13

✓ Correct

What kind of software is often inadvertently installed by users, leading to recommendations for its removal due to potential security risks?

- ☒ Potentially Unwanted Application (PUA) ✓ Correct
- ☐ Productivity tools
- ☐ Operating system update
- ☐ Antivirus software

Explanation

A Potentially Unwanted Application (PUA) is a program that, while not necessarily malicious, may perform unwanted actions on a system. These can range from displaying intrusive advertising, tracking the user's internet usage for sale to advertisers, or using premium SMS services. For these reasons, PUAs are often recommended for removal from computers. Operating system updates are important for maintaining the security and performance of a system. Trusted vendors typically issue these and are crucial for patching vulnerabilities. Antivirus software prevents, detects, and removes malware from computers. They are an essential part of a system's security strategy. Productivity tools are applications used to produce information, such as documents, presentations, worksheets, databases, charts, graphs, digital paintings, electronic music, and digital video. While it's important to download these tools from trusted sources, they are generally not classified as unwanted applications.

Related Content

19.3.1 Browser Selection and Installation

resources\questions\pt_core2_220_1202_2_11_002.question.xml

Question 14

✔ Correct

An administrator uses an access control system to shuttle authentication and authorization traffic between the supplicant and the authentication server that encrypts an entire authentication rather than just the password. What is this method?

- ☐ Kerberos
- ☐ RADIUS
- ☒ TACACS+ ✔ Correct
- ☐ AES

Explanation

Terminal Access Control System Plus (TACACS+) is one way of implementing authentication, authorization, and accounting (AAA). TACACS+ is often used in authenticating administrative access to routers, switches, and access points.

Remote Authentication Dial-In User Service (RADIUS) is implementing the AAA server when configuring enterprise authentication. Rather than storing and validating user credentials directly, it forwards data between the RADIUS server and the supplicant without reading it.

Kerberos allows a user account to authenticate to a domain controller (DC) over a trusted local cabled segment. Kerberos facilitates single sign-on (SSO).

Advanced Encryption Standard (AES) is the standard encryption used by WPA2 and the strongest encryption standard to use by Wi-Fi.

Related Content

18.2.5 RADIUS, TACACS+, and Kerberos

resources\questions\pt_core2_220_1202_2_3_004.question.xml

Question 15

✓ Correct

Which of the following should generate an alert when the account is disabled or altered?

- ☐ Restrict login times.
- ☐ Restrict user permission.
- ☒ Change the default administrator account. ✓ Correct
- ☐ Disable guest account.

Explanation

These default accounts have practical limitations and, consequently, are the ultimate target for threat actors. Any use of the default administrator account must be logged and accounted for.

Disabling guest accounts allows unauthorized access to the computer and may provide some sort of network access. It is only enabled to facilitate password-less file sharing in a Windows workgroup.

Restrict user permission means some networks have complex requirements for assigning rights. However, the basic principle is that the number of accounts with administrator privileges should be as few as possible.

Restrict login times are typically used to prevent an account from logging in at an unusual time of the day or night or during the weekend.

Related Content

19.1.5 Change Default Administrator Account and Password

resources\questions\pt_core2_220_1202_2_7_003.question.xml

Question 16

✓ Correct

A technician destroys disks by putting holes through them and smashing them with a hammer. What is this method?

- ☐ Incinerating
- ☐ Degaussing
- ☐ Erasing/wiping

☒ Drilling ✓ Correct

Explanation

Drilling is when a disk needs to be destroyed; IT uses a drill or hammer. The goal is to make the drive unusable.

Degaussing is when a hard disk is exposed to a powerful electromagnet that disrupts the magnetic pattern that stores the data on the disk surface.

Incinerating is when the disk is exposed to high heat to melt its components. It is performed in a furnace designed for media sanitization. Municipal incinerators may leave remnants.

Erasing/wiping software ensures that old data is removed using zeroes or random patterns, leaving the disk in a “clean” state, ready to be passed to the new owner.

Related Content

21.2.6 Disposal and Recycling Outsourcing Concepts

resources\questions\pt_core2_220_1202_2_9_005.question.xml

Question 17

— Partial

What type of encryption does WPA2 use? (Select two.)

☐ TKIP ✓ Correct

☐ WPA3

☐ MFA

☒ AES ✓ Correct

Explanation

Advanced encryption standard (AES) is the standard encryption used by WPA2 and the strongest encryption standard to use by Wi-Fi.

Temporal key integrity protocol (TKIP) tries to mitigate the various attacks against WEP developed by producing a new 128-bit encryption key for every packet sent on the network.

Wi-Fi Protected Access (WPA3) uses passphrase-based group authentication of stations in private mode, and it changes the method by which this secret is used to agree with session keys. The simultaneous authentication of equals (SAE) protocol replaces the 4-way handshake.

Multifactor authentication (MFA) allows the machine to establish a trust relationship and create a secure tunnel to transmit the user credentials or perform smart card authentication without a user password.

Related Content

18.2.1 Wi-Fi Protected Access

resources\questions\pt_core2_220_1202_2_3_002.question.xml

Question 18

✔ Correct

A user has lost several corporate laptops in the past. Each device had a basic password, which put company data at risk. The user has a new laptop and uses which method of increased security to log in to the corporate owned system?

- ☐ Corporate application
- ☐ Location services
- ☐ Device pairing
- ☒ Two-factor authentication ✓ Correct

Explanation

Two-factor or multifactor authentication means that the user must submit at least two different kinds of credentials. This would be used to authenticate access to a system with a higher level of security than a single method.

Corporate applications refer to applications running on the device. This does not pertain to gaining access to the device.

To connect a peripheral device via Bluetooth, the Bluetooth radio on each device must be put into discoverable mode, which is also known as pairing mode. This would not increase security.

Using location services is not related to being connected to a cellular network. Location services use Wi-Fi and GPS to determine a device's location.

Related Content

-  15.1.9 Authentication Methods
-  18.2.2 Wi-Fi Authentication Methods
-  18.2.4 Authentication Methods
-  20.1.5 Two-factor Authentication

resources\questions\pt_core2_220_1202_2_1_007.question.xml

Question 19

✔ Correct

A technician is using a tool with a secure erase function that performs a zero-filling on HDDs and marks all blocks as empty on SSDs. The SSD firmware's automatic garbage collectors then perform the actual erase of each block over time. What is this tool?

- ☒ Low-level formatting ✓ Correct
- ☐ Standard formatting
- ☐ Shredding
- ☐ Erasing/wiping

Explanation

A low-level formatting tool resets a disk to its factory condition. Most of these tools will incorporate a sanitize function.

The standard formatting tool deletes partitions and writes a new file system that will only remove references to files and mark all sectors as usable.

Erasing/wiping software ensures that old data is removed using zeroes or random patterns, leaving the disk in a "clean" state, ready to be passed to the new owner. This overwriting method is suitable for all but the most confidential data.

Shredding is when the disk is ground into little pieces. A mechanical shredder works in much the same way as a paper shredder.

Related Content

21.2.5 Data Destruction Methods

resources\questions\pt_core2_220_1202_2_9_001.question.xml

Question 20

✔ Correct

A technician needs to set up a method that blocks URLs or search terms using keywords and phrases. What is this method?

- ☐ Changing channels
- ☐ Encryption setting
- ☒ Content filtering ✓ Correct
- ☐ Disable guest access

Explanation

Content filtering means that the firewall downloads curated reputation databases that associate IP address ranges, Fully Qualified Domain Names (FQDNs), and URL web addresses with sites known to host various categories of content.

Changing channels can be accessed by using a Wi-Fi analyzer to identify which channel within the access point's range is least congested.

Disable guest access when a user does not want a guest network. The guest network is usually isolated from the other local devices.

Guests can connect to this network and access the internet without a password. Encryption settings allow users to set the authentication mode.

Related Content

18.3.5 Home Router Firewall Configuration

resources\questions\pt_core2_220_1202_2_10_003.question.xml