

**Season:**

Fall 2021

**Style #:**

LW4BF8S

**Style Desc:**

Hooded Define Jacket Nulu LW4BF8S

**Product Size Definition:**

W Tops--W Ext Sizes:0-26

**Grade Rule Template:**

W Tops 0-18

**Brand:**

lululemon

**Division:**

lulu Womens

**Class:**

Womens 2nd Layers

**Pod:**

W No Sweat

**Style Status:**

Active

**Generated Date:**



Jan 06, 2021



## BOM Comments

## fabric




	Standard Placement	Placement	Supplier Article #	Material Status	Material	Supplier	Total Leadtime	Bulk Production Lead Time - Days	Usage	BOM UOM	Price Per Unit	Total	023012 - HBLK/W HT/BLK
	self		RT1803238	Approved	Mini Space Dye Herringbone Jacquard Nulu	Eclat Textiles Co. Ltd.	85	0	1.8230	Yard	\$12.3600	\$22.5323	Mini Space Dye Herringbone Jacquard Heathe red Black White/B lack
	lining1		R20403099	Approved	Coolmax	Eclat Textiles Co. Ltd.	63	0	0.0610	Yard	\$2.8900	\$0.1763	Black
	lining2		DB18-4A	Approved	Lightweight Power Mesh 105gsm	Yu Yuang Textile Co., Ltd	55	0	0.1040	Yard	\$3.0000	\$0.3120	Black
	lining3		DN92-DA-1	Approved	Power mesh wider width 146gsm	Yu Yuang Textile Co., Ltd	55	0	0.0130	Yard	\$3.1300	\$0.0407	Black

trim													
	Standard Placement	Placement	Supplier Article #	Material Status	Material	Supplier	Total Leadtime	Bulk Production Lead Time - Days	Usage	BOM UOM	Price Per Unit	Total	023012 - HBLK/W HT/BLK
	seeQAManual		F785140	Approved	Seamsoft Tex 24, Ticket 140	Coats Plc	0	45	1.0000	Yard	\$0.0011	\$0.0011	DTM
	seeQAManual		5643140	Approved	Gramax Tex 21, Ticket 140 Thread	Coats Plc	0	45	1.0000	Yard	\$0.0007	\$0.0007	DTM
	seeQAManual		2994180	Approved	Epic Tex 18, Ticket 180 Thread	Coats Plc	0	45	1.0000	Yard	\$0.0007	\$0.0007	DTM
 Matt Black VYMJ	seeTechnicalSketch		Z#5YKK_5VY-VYMJOR	Approved	#5 Vislon Metaluxe Matte Black - Open-End Right-Insert	YKK Taiwan	0	40	1.0000	Inch	\$0.2644	\$0.1844	Black
	seeTechnicalSketch	CF ZIPPER PULL	P#5YKK_5VS-DA8LLM64	Approved	#5 Vislon Autolock X-Out Grosgrain Pull	YKK Taiwan	0	45	1.0000	Each	\$0.4070	\$0.4070	Matte Black - EHA
Modified Date: Jan 06, 2021				Page 2 of 10				Confidential and Proprietary					

A close-up photograph of a metal zipper pull. The pull is silver-toned and features a series of horizontal ridges. In the center, there is a circular logo containing a stylized Greek letter Omega (Ω). The zipper teeth are visible on either side of the pull.


Confidential and Proprietary




## trim

	Standard Placement	Placement	Supplier Article #	Material Status	Material	Supplier	Total Leadtime	Bulk Production Lead Time - Days	Usage	BOM UOM	Price Per Unit	Total	023012 - HBLK/WH/BLK
	seeTechnicalSketch	CF ZIPPER INSIDE	ESSLU10MM	Approved	DESSLU - Stretch single - sided satin - 10mm	Shanghai JML Apparel Co. Ltd.	0	50	1.9000	Yard	\$0.1030	\$0.1957	Black - DTM
	seeTechnicalSketch		DR41312/8P-DPM	Approved	DC00038 - Non-Stretch Solid Drawcord With Silicone Dip Tip - 8mm	Shanghai JML Apparel Co. Ltd.	0	60	1.1000	Each	\$0.8450	\$0.9295	Black/Black
	seeTechnicalSketch	Logo	LUF201408067	Approved with Limitations	T00185N - Silver Reflective Lulu Logo, Hero Quality - 13mm (Effective SU15 and Onwards)	E. Textint	0	40	1.0000	Each	\$0.0670	\$0.0670	Silver

## labels

	Standard Placement	Placement	Supplier Article #	Material Status	Material	Supplier	Total Leadtime	Bulk Production Lead Time - Days	Usage	BOM UOM	Price Per Unit	Total	023012 - HBLK/WH/BLK
	seeQAManual	CB	CC00001	Approved	CC00001-LLL-GARMENT	Shanghai JML Apparel Co. Ltd.	0	15	1.0000	Each	\$0.0320	\$0.0320	White

labels													
	Standard Placement	Placement	Supplier Article #	Material Status	Material	Supplier	Total Leadtime	Bulk Production Lead Time - Days	Usage	BOM UOM	Price Per Unit	Total	023012 - HBLK/HT/BLK
	seeTechnicalSketch		TRACE00001	Approved	TRACE00001 - Size and Traceability Label	Avery/Paxar	0	14	1.0000	Each	\$0.0300	\$0.0300	White/Grey



packaging													
	Standard Placement	Placement	Supplier Article #	Material Status	Material	Supplier	Total Leadtime	Bulk Production Lead Time - Days	Usage	BOM UOM	Price Per Unit	Total	023012 - HBLK/HT/BLK
	seeQAManual		HTT1002-ST-2IN	Approved	Hangtag Trim - Swiftach Fastener - 2inch	Factory Sourced	0	0	1.0000	Each	\$0.0000	\$0.0000	White
	seeQAManual		LHT-WWMT-001	Approved	LHT - lululemon WWMT Hangtag - White	Avery/Paxar	0	14	1.0000	Each	\$0.0369	\$0.0369	White
	seeQAManual		LWWMT Barcode	Approved	WWMT Barcode Sticker	Avery/Paxar	0	0	1.0000	Each	\$0.0300	\$0.0300	White

Modified Date:Jan 06, 2021

Page 5 of 10

Confidential and Proprietary

**packaging**

	Standard Placement	Placement	Supplier Article #	Material Status	Material	Supplier	Total Leadtime	Bulk Production Lead Time - Days	Usage	BOM UOM	Price Per Unit	Total	023012 - HBLK/W HT/BLK
	seeQAManual		MJ70-H	Approved	HMJ70-H - Source Tag - Silver Pin ** Please Also Spec Tag Hzlamt7200-B**	Tyco	0	0	1.0000	Each	\$0.0227	\$0.0227	Silver
	seeQAManual		ZLAMT7200-B	Approved	HZLAMT7200-B - Source Tag - Black Tag ** Please Also Spec Pin Hmj70-H**	Tyco	0	0	1.0000	Each	\$0.0803	\$0.0803	Black

**finishing**

	Standard Placement	Placement	Supplier Article #	Material Status	Material	Supplier	Total Leadtime	Bulk Production Lead Time - Days	Usage	BOM UOM	Price Per Unit	Total	023012 - HBLK/W HT/BLK
	seeTechnicalSketch				Embroidered Eyelet		0	0	1.0000		\$0.0000	\$0.0000	DTM

Total = \$26.235



<b>Season:</b>	Fall 2021	<b>Brand:</b>	lululemon	<b>Style Status:</b>	Active
<b>Style #:</b>	LW4BF8S	<b>Division:</b>	lulu Womens	<b>Generated Date:</b>	Jan 06, 2021
<b>Style Desc:</b>	Hooded Define Jacket Nulu LW4BF8S	<b>Class:</b>	Womens 2nd Layers	<b>Measurement Template:</b>	MT - Ws Basic Top - Raglan LS & SS
<b>Product Size Definition:</b>	W Tops--W Ext Sizes:0-26	<b>Pod:</b>	W No Sweat		
<b>Grade Rule Template:</b>	W Tops 0-18				

#	Name	Criticality	Tol (-)	Tol (+)	HTM Instruction	0	2	4	6	8
87	REF-HPS LENGTH at FRONT	Reference Only	1/2	1/2	Measure at CF from imaginary line connecting high point shoulder straight down to finished edge of hem. Note: This measurement is for the base size and for detail only.					25 1/4
1	CF LENGTH		3/8	3/8	Measure from CF top finished edge/neck seam straight down to bottom finished hem.	19 1/2	20	20 1/2	21	21 1/2
59	ZIPPER LENGTH at CF	Critical	1/4	1/4	Measure with zipper closed from top stopper straight down to bottom stopper.	22 1/2	23	23 1/2	24	24 1/2
5	CB LENGTH	Critical	1/2	1/2	Measure from CB top finished edge/neck seam straight down to bottom finished hem.	21 1/2	22 1/8	22 3/4	23 3/8	24
97	NECK WIDTH at HPS SEAM	Critical	1/8	1/8	Measure straight across at HPS/seam.	5 3/4	6	6 1/4	6 1/2	6 3/4
142	NECK DROP at CB fr HPS		1/8	1/8	Measure from an imaginary line connecting high point shoulder straight down to CB neck opening edge.	3/4	3/4	3/4	3/4	3/4
141	NECK DROP at CF fr HPS		1/8	1/8	Measure from an imaginary line connecting high point shoulder straight down to CF neck opening edge.	2 3/4	2 7/8	3	3 1/8	3 1/4
279	ACROSS SHOULDER at SEAM	Critical	3/8	3/8	Measure straight across back of garment from armhole seam to armhole seam at shoulder.	12 5/8	13	13 1/2	14	14 1/2
116	ACROSS FRONT 5" fr HPS		1/4	1/4	Measure 5" down from front high point shoulder straight across from armhole seam to armhole seam.	11 1/8	11 1/2	12	12 1/2	13
115	ACROSS BACK 5" fr HPS		1/4	1/4	Measure 5" down from back high point shoulder straight across from armhole seam to armhole seam.	11 5/8	12	12 1/2	13	13 1/2
183	YOKE HEIGHT at CB		1/8	1/8	Measure from CB top finished edge/neck seam straight down to yoke seam.	7 1/4	7 1/2	7 3/4	8	8 1/4
4081	Armhole Drop from HPS	Reference Only	1/4	1/4	Measure from an imaginary line connecting high point shoulder straight down to Underarm seam/position	7 3/4	8	8 1/4	8 1/2	8 3/4
6	CHEST CIRC 1" down ARMHOLE	Critical	1/2	1/2	Measure 1" below armhole from fold edge of garment straight across to fold edge of garment, multiply by 2.	26 1/2	28	30	32	34
172	WAIST POS fr HPS		0	0	Measure from high point shoulder straight down to natural waist level.	14 1/2	14 7/8	15 1/4	15 5/8	16
509	WAIST CIRCUMFERENCE TOPS	Critical	1/2	1/2	Measure from left fold to right fold with garment flat, multiply by 2.	22	23 1/2	25 1/2	27 1/2	29 1/2
9	HEM SWEEP CIRC	Critical	1/2	1/2	Measure from left fold edge to right fold edge straight across bottom edge of finished hem, multiply by 2.	30	31 1/2	33 1/2	35 1/2	37 1/2
Modified Date: Sep 16, 2020		Page 7 of 10					Confidential and Proprietary			

Measurement Set: Calculated			Fall 2021			Hooded Define Jacket Nulu LW4BF8S			lululemon			Jan 06, 2021		
#	Name	Criticality	Tol (-)	Tol (+)	HTM Instruction	0	2	4	6	8				
62	REF-SLEEVE LENGTH fr CB - THUMBHOLE	Reference Only	5/8	5/8	Measure straight across from CB neck seam/edge straight across to shoulder point and straight down to bottom edge of sleeve opening.	30 1/4	31 1/8	31 3/4	32 3/8	33				
63	SLEEVE LENGTH-LONG	Critical	3/8	3/8	Measure from top of armhole straight down to bottom edge of sleeve opening.	23 15/16	24 5/8	25	25 3/8	25 3/4				
71	BICEP CIRC 1" down ARMHOLE	Critical	1/4	1/4	Measure at 1"" below armhole from inner sleeve fold edge straight across to outer sleeve fold edge, multiply by 2.	8 7/8	9 1/2	10 1/4	11	11 3/4				
151	FOREARM CIRC 10" up fr HEM (32" slv length: cb)		1/4	1/4	Measure 10" up from finished hem straight across from inner sleeve fold edge to outer sleeve fold edge, multiply by 2.	7 1/2	7 7/8	8 1/4	8 5/8	9				
65	CUFF CIRC RELAXED		1/4	1/4	Measure from inner fold edge to outer fold edge straight across bottom edge of cuff, multiply by 2.	7	7 1/4	7 1/2	7 3/4	8				
69	CUFF HEIGHT		1/8	1/8	Measure from cuff seam straight down to bottom edge of cuff.	3	3	3	3	3				
73	PKT1 OPENING		1/8	1/8	Measure from finished edge to finished edge along pocket opening.	5 1/2	5 1/2	5 1/2	6	6				
76	HOOD HEIGHT	Critical	1/4	1/4	Measure from front neck seam straight to top fold with front opening of hood aligned.	12 3/4	12 7/8	13	13 1/8	13 1/4				
77	HOOD WIDTH	Critical	1/4	1/4	Measure 6" up from CB neck seam straight across from front opening edge of hood to back fold edge of hood, multiply by 2.	20	20 3/8	20 3/4	21 1/8	21 1/2				
106	HOOD CHIN HEIGHT at CF		1/8	1/8	Measure from edge of hood opening at CF straight down to CF neck seam.	3	3	3	3	3				
316	DRAWCORD LENGTH at HOOD		1/2	1/2	Measure from aligned drawcord tips to top fold edge of hood along hood casing seam, multiply by 2.	45 1/2	45 1/2	45 1/2	46	46				
Modified Date:Sep 16, 2020		Page 8 of 10						Confidential and Proprietary						



Modified Date: Sep 16, 2020	Page 9 of 10	Confidential and Proprietary
-----------------------------	--------------	------------------------------

#	Name	Criticality	Tol (-)	Tol (+)	HTM Instruction	8	10	12	14	16	18	20
63	SLEEVE LENGTH-LONG	Critical	3/8	3/8	Measure from top of armhole straight down to bottom edge of sleeve opening.	25 3/4	26 1/8	26 1/2	26 3/8	26 1/4	26 1/8	26
71	BICEP CIRC 1" down ARMHOLE	Critical	1/4	1/4	Measure at 1" below armhole from inner sleeve fold edge straight across to outer sleeve fold edge, multiply by 2.	11 3/4	12 1/2	13 1/4	14	14 3/4	15 1/2	16 1/4
151	FOREARM CIRC 10" up fr HEM (32" slv length: cb)		1/4	1/4	Measure 10" up from finished hem straight across from inner sleeve fold edge to outer sleeve fold edge, multiply by 2.	9	9 3/8	9 3/4	10 1/8	10 1/2	10 7/8	11 1/4
65	CUFF CIRC RELAXED		1/4	1/4	Measure from inner fold edge to outer fold edge straight across bottom edge of cuff, multiply by 2.	8	8 1/4	8 1/2	8 3/4	8 3/4	8 3/4	8 3/4
69	CUFF HEIGHT		1/8	1/8	Measure from cuff seam straight down to bottom edge of cuff.	3	3	3	3	3	3	3
73	PKT1 OPENING		1/8	1/8	Measure from finished edge to finished edge along pocket opening.	6	6	6 1/2	6 1/2	6 1/2	6 1/2	6 1/2
76	HOOD HEIGHT	Critical	1/4	1/4	Measure from front neck seam straight to top fold with front opening of hood aligned.	13 1/4	13 3/8	13 1/2	13 5/8	13 5/8	13 5/8	13 5/8
77	HOOD WIDTH	Critical	1/4	1/4	Measure 6" up from CB neck seam straight across from front opening edge of hood to back fold edge of hood, multiply by 2.	21 1/2	21 7/8	22 1/4	22 5/8	23	23 3/8	23 3/4
106	HOOD CHIN HEIGHT at CF		1/8	1/8	Measure from edge of hood opening at CF straight down to CF neck seam.	3	3	3	3	3	3	3
316	DRAWCORD LENGTH at HOOD		1/2	1/2	Measure from aligned drawcord tips to top fold edge of hood along hood casing seam, multiply by 2.	46	46	46 1/2	46 1/2	46 1/2	46 1/2	46 1/2