

DEPARTMENT OF COMPUTER SCIENCE AND ENGINEERING

Title: Simulating the MFT and MVT Memory Management Techniques.

OPERATING SYSTEM LAB
CSE 310



GREEN UNIVERSITY OF BANGLADESH

1 Objective(s)

- To gather knowledge of different memory management techniques.
- To implement Multiprogramming with a Fixed number of Tasks (MFT) and Multiprogramming with a Variable number of Tasks (MVT).

2 Problem analysis

In this section, Multiprogramming with a Fixed number of Tasks (MFT) memory management technique is discussed.

2.1 MFT Memory Management Technique

MFT (Multiprogramming with a Fixed number of Tasks) is one of the old memory management techniques in which the memory is partitioned into fixed-size partitions and each job is assigned to a partition. The memory assigned to a partition does not change.

3 Implementation in C

```
1
   /* MFT Memory Management Technique code */
2
   #include<stdio.h>
   #include<conio.h>
3
4
5
   main()
6
7
       int ms, bs, nob, ef,n, mp[10],tif=0;
8
       int i,p=0;
9
10
       printf(" Enter the total memory available (in Bytes) -- ");
       scanf("%d", &ms);
11
12
       printf(" Enter the block size (in Bytes) -- ");
13
       scanf("%d", &bs);
14
15
16
       nob=ms/bs;
17
       ef=ms - nob*bs;
18
       printf("\n Enter the number of processes -- ");
19
20
       scanf("%d", &n);
21
       printf("\n");
22
       for (i=0; i<n; i++)</pre>
23
24
            printf(" Enter memory required for process %d (in Bytes) -- ",i+1);
25
            scanf("%d", &mp[i]);
26
27
28
29
       printf("\n No. of Blocks available in memory -- %d", nob);
       printf("\n\n PROCESS\tMEMORY REQUIRED\t ALLOCATED\tINTERNAL FRAGMENTATION")
30
31
       for (i=0; i<n && p<nob; i++)</pre>
32
33
            printf("\n %d\t\t%d",i+1,mp[i]);
34
35
36
            if(mp[i] > bs)
```

```
37
                printf("\t\t NO\t\t---");
38
            else
39
            {
                printf("\t\t YES\t\t%d",bs-mp[i]);
40
41
                tif = tif + bs-mp[i];
42
                p++;
43
            }
44
       }
45
46
       if(i<n)
           printf("\n\n Memory is Full, Remaining Processes cannot be accomodated"
47
               );
48
49
       printf("\n\n Total Internal Fragmentation is %d",tif);
       printf("\n Total External Fragmentation is %d",ef);
50
51
52
       getch();
53
```

4 Input/Output

Output of the MFT Memory Management Technique program is given below.

```
Enter the total memory available (in Bytes) -- 1000
Enter the block size (in Bytes) -- 300
Enter the number of processes -- 5
Enter memory required for process 1 (in Bytes) -- 275
Enter memory required for process 2 (in Bytes) -- 400
Enter memory required for process 3 (in Bytes) -- 290
Enter memory required for process 4 (in Bytes) -- 293
Enter memory required for process 5 (in Bytes) -- 100
No. of Blocks available in memory -- 3
PROCESS
              MEMORY REQUIRED ALLOCATED
                                              INTERNAL FRAGMENTATION
1
              275
                                YES
2
              400
                                NO
3
              290
                                YES
                                               10
1
              293
                                YES
                                               7
Memory is Full, Remaining Processes cannot be accomodated
Total Internal Fragmentation is 42
Total External Fragmentation is 100
```

5 Discussion & Conclusion

Based on the focused objective(s) to understand about MFT Memory Management Technique, the additional lab exercises made me more confident towards the fulfilment of the objectives(s).

Lab Task (Please implement yourself and show the output to the 6 instructor)

1. Implement MVT Memory Management Technique.

6.1 Problem analysis

MVT (Multiprogramming with a Variable number of Tasks) is the memory management technique in which each job gets just the amount of memory it needs. That is, the partitioning of memory is dynamic and changes as jobs enter and leave the system. MVT is a more "efficient" user of resources. MFT suffers from the problem of internal fragmentation and MVT suffers from external fragmentation.

Sample Input/Output 6.2

INPUT:

Enter the total memory available (in Bytes) – 1000 Enter memory required for process 1 (in Bytes) – 400 Memory is allocated for Process 1 Do you want to continue(y/n):y Enter memory required for process 2 (in Bytes) – 275 Memory is allocated for Process 2 Do you want to continue(y/n):yEnter memory required for process 3 (in Bytes) – 550

OUTPUT:

Memory is Full Total Memory Available – 1000 PROCESS ——MEMORY-ALLOCATED -400Total Memory Allocated is 675

Total External Fragmentation is 325

7 Lab Exercise (Submit as a report)

• Implement a code to solve the Memory Management technique problem.

Input:

Enter the number of Blocks-4

Block 1 size: 280 Block 2 size: 350 Block 3 size: 300 Block 4 size: 320

Enter the number of processes – 4

Enter memory required for process 1-275Enter memory required for process 2 – 400 Enter memory required for process 3 – 290

Enter memory required for process 4 – 293

Output:

Table 1: Sample Output

Processes	Processes size	Blocks	Blocks size	Allocated	Int. Frag.
1	275	1	280	YES	5
2	400	2	350	NO	_
3	290	3	350	YES	60
4	293	4	300	YES	7

8 Policy

Copying from the Internet, classmate, seniors, or from any other source is strongly prohibited. 100% marks will be deducted if any such copying is detected.