

Question 1

Bubble Sort is the simplest sorting algorithm that works by repeatedly swapping the adjacent elements if they are in the wrong order.

Example:

First Example:

(5 1 4 2 8) \rightarrow (1 5 4 2 8), Here, algorithm compares the first two elements, and swaps since $5 > 1$.

(1 5 4 2 8) \rightarrow (1 4 5 2 8), Swap since $5 > 4$

(1 4 5 2 8) \rightarrow (1 4 2 5 8), Swap since $5 > 2$

(1 4 2 5 8) \rightarrow (1 4 2 5 8), Now, since these elements are already in order ($8 > 5$), the algorithm does not swap them.

Second Example:

(1 4 2 5 8) \rightarrow (1 4 2 5 8)

(1 4 2 5 8) \rightarrow (1 2 4 5 8), Swap since $4 > 2$

(1 2 4 5 8) \rightarrow (1 2 4 5 8)

(1 2 4 5 8) \rightarrow (1 2 4 5 8)

Now, the array is already sorted, but our algorithm does not know if it is completed. The algorithm needs one whole pass without any swap to know it is sorted.

Third Example:

(1 2 4 5 8) \rightarrow (1 2 4 5 8)

(1 2 4 5 8) \rightarrow (1 2 4 5 8)

(1 2 4 5 8) \rightarrow (1 2 4 5 8)

(1 2 4 5 8) \rightarrow (1 2 4 5 8)

Question 2

Create **Clock** that include two struct; **Date, Time**.

Date

- int day
- int month
- int year

Time

- int seconds
- int mins
- int hours

Question 3

Create a function that adds .txt to the given string.

Question 4

Write a program that reads all the text within the text file

Hint:

```
while(fgets('add something here' ) != NULL){  
    'Add something here'  
}
```