```
To run a command as administrator (user "root"), use "sudo <command>".

See "man sudo_root" for details.

| Idolce@DESKTOP-T9SASNL:-$ cat

stuff

stuff

stuff

ara[

par

par

ldolce@DESKTOP-T9SASNL:-$ _

| Idolce@DESKTOP-T9SASNL:-$ _

| Idolce@DESKTOP-T9SASNL:-$ _

| Idolce@DESKTOP-T9SASNL:-$ cat > list1

pear

banana

apple

| Idolce@DESKTOP-T9SASNL:-$ cat | list2

pear

banana

apple

| Idolce@DESKTOP-T9SASNL:-$ cat > list2

pear

banana

apple

| Idolce@DESKTOP-T9SASNL:-$ cat > list2

pear

banana

apple

| Idolce@DESKTOP-T9SASNL:-$ cat > list2

pear

banana

| Idolce@DESKTOP-T9SASNL:-$ cat > list2

pear

| Idolce@DESKTOP-T9SASNL:-$ cat | list3

| Idolce@DESKTOP-T9SASNL:-$ cat | lis
```

```
Idolce@DESKTOP-T9SASNL:-$
Idolce@DESKTOP-T9SASNL:-$ cat >> list1
peach
grape
orange
Idolce@DESKTOP-T9SASNL:-$
Idolce@DESKTOP-TPSASNL:-$
Idolce@DESKTOP-TPSASNL:-$
Idolce@DESKTOP-TPSASNL:-$
Idolc
```