Final Assignment

Dulshika Dassanayake

2026-04-06

Contents

1. Notes on the recap material **1**

Data subsetting 1

without subset function 2

With subset function 3

2. Extra optional materials provided, the code and how it works. **4**

3. Introduction to renv. **4**

Follow the coding demonstration in class. Turn in notes 4

GitHub link: https://github.com/Dulshikamadushani/R-Practice/tree/main/Bonus%20material **5**

1. Notes on the recap material

Data subsetting

example dataset: mtcars

```
mtcars
```

```
##                     mpg cyl  disp  hp drat    wt  qsec vs am gear carb
## Mazda RX4          21.0   6 160.0 110 3.90 2.620 16.46  0  1    4    4
## Mazda RX4 Wag      21.0   6 160.0 110 3.90 2.875 17.02  0  1    4    4
## Datsun 710         22.8   4 108.0  93 3.85 2.320 18.61  1  1    4    1
## Hornet 4 Drive     21.4   6 258.0 110 3.08 3.215 19.44  1  0    3    1
## Hornet Sportabout  18.7   8 360.0 175 3.15 3.440 17.02  0  0    3    2
## Valiant            18.1   6 225.0 105 2.76 3.460 20.22  1  0    3    1
## Duster 360         14.3   8 360.0 245 3.21 3.570 15.84  0  0    3    4
## Merc 240D          24.4   4 146.7  62 3.69 3.190 20.00  1  0    4    2
## Merc 230           22.8   4 140.8  95 3.92 3.150 22.90  1  0    4    2
## Merc 280           19.2   6 167.6 123 3.92 3.440 18.30  1  0    4    4
## Merc 280C          17.8   6 167.6 123 3.92 3.440 18.90  1  0    4    4
```

```
## Merc 450SE          16.4   8 275.8 180 3.07 4.070 17.40  0  0    3    3
## Merc 450SL          17.3   8 275.8 180 3.07 3.730 17.60  0  0    3    3
## Merc 450SLC         15.2   8 275.8 180 3.07 3.780 18.00  0  0    3    3
## Cadillac Fleetwood  10.4   8 472.0 205 2.93 5.250 17.98  0  0    3    4
## Lincoln Continental 10.4   8 460.0 215 3.00 5.424 17.82  0  0    3    4
## Chrysler Imperial   14.7   8 440.0 230 3.23 5.345 17.42  0  0    3    4
## Fiat 128            32.4   4  78.7  66 4.08 2.200 19.47  1  1    4    1
## Honda Civic         30.4   4  75.7  52 4.93 1.615 18.52  1  1    4    2
## Toyota Corolla      33.9   4  71.1  65 4.22 1.835 19.90  1  1    4    1
## Toyota Corona       21.5   4 120.1  97 3.70 2.465 20.01  1  0    3    1
## Dodge Challenger    15.5   8 318.0 150 2.76 3.520 16.87  0  0    3    2
## AMC Javelin         15.2   8 304.0 150 3.15 3.435 17.30  0  0    3    2
## Camaro Z28          13.3   8 350.0 245 3.73 3.840 15.41  0  0    3    4
## Pontiac Firebird    19.2   8 400.0 175 3.08 3.845 17.05  0  0    3    2
## Fiat X1-9           27.3   4  79.0  66 4.08 1.935 18.90  1  1    4    1
## Porsche 914-2       26.0   4 120.3  91 4.43 2.140 16.70  0  1    5    2
## Lotus Europa        30.4   4  95.1 113 3.77 1.513 16.90  1  1    5    2
## Ford Pantera L      15.8   8 351.0 264 4.22 3.170 14.50  0  1    5    4
## Ferrari Dino        19.7   6 145.0 175 3.62 2.770 15.50  0  1    5    6
## Maserati Bora       15.0   8 301.0 335 3.54 3.570 14.60  0  1    5    8
## Volvo 142E          21.4   4 121.0 109 4.11 2.780 18.60  1  1    4    2
```

without subset function

Give the name of the data set then open square bracket[raw,]column

```r
mtcars [1,] # raw one only
```

```
##           mpg cyl disp  hp drat   wt  qsec vs am gear carb
## Mazda RX4  21   6  160 110  3.9 2.62 16.46  0  1    4    4
```

```r
mtcars [1,3] # raw one column 3
```

```
## [1] 160
```

find all rows such that vs=1 data frame $ sign vs == 1 and need to put a comma

```r
mtcars [mtcars$vs == 1,]
```

```
##                 mpg cyl  disp  hp drat    wt  qsec vs am gear carb
## Datsun 710     22.8   4 108.0  93 3.85 2.320 18.61  1  1    4    1
## Hornet 4 Drive 21.4   6 258.0 110 3.08 3.215 19.44  1  0    3    1
## Valiant        18.1   6 225.0 105 2.76 3.460 20.22  1  0    3    1
## Merc 240D      24.4   4 146.7  62 3.69 3.190 20.00  1  0    4    2
## Merc 230       22.8   4 140.8  95 3.92 3.150 22.90  1  0    4    2
## Merc 280       19.2   6 167.6 123 3.92 3.440 18.30  1  0    4    4
## Merc 280C      17.8   6 167.6 123 3.92 3.440 18.90  1  0    4    4
## Fiat 128       32.4   4  78.7  66 4.08 2.200 19.47  1  1    4    1
```

```
## Honda Civic    30.4   4  75.7  52 4.93 1.615 18.52  1  1    4    2
## Toyota Corolla 33.9   4  71.1  65 4.22 1.835 19.90  1  1    4    1
## Toyota Corona  21.5   4 120.1  97 3.70 2.465 20.01  1  0    3    1
## Fiat X1-9      27.3   4  79.0  66 4.08 1.935 18.90  1  1    4    1
## Lotus Europa   30.4   4  95.1 113 3.77 1.513 16.90  1  1    5    2
## Volvo 142E     21.4   4 121.0 109 4.11 2.780 18.60  1  1    4    2
```

```r
mtcars $hp[mtcars$vs == 1] # no comma allows to access all row and column
```

```
##  [1]  93 110 105  62  95 123 123  66  52  65  97  66 113 109
```

```r
mtcars $hp[mtcars$vs == 1][1] # get the first number there
```

```
## [1] 93
```

```r
mtcars $hp[mtcars$vs == 1 & mtcars$gear == 4] # and function
```

```
##  [1]  93  62  95 123 123  66  52  65  66 109
```

```r
max (mtcars$hp) # get the maximum value of the mtcars hp row
```

```
## [1] 335
```

With subset function

```r
subset(mtcars, vs==1)
```

```
##                 mpg cyl  disp  hp drat    wt  qsec vs am gear carb
## Datsun 710     22.8   4 108.0  93 3.85 2.320 18.61  1  1    4    1
## Hornet 4 Drive 21.4   6 258.0 110 3.08 3.215 19.44  1  0    3    1
## Valiant        18.1   6 225.0 105 2.76 3.460 20.22  1  0    3    1
## Merc 240D      24.4   4 146.7  62 3.69 3.190 20.00  1  0    4    2
## Merc 230       22.8   4 140.8  95 3.92 3.150 22.90  1  0    4    2
## Merc 280       19.2   6 167.6 123 3.92 3.440 18.30  1  0    4    4
## Merc 280C      17.8   6 167.6 123 3.92 3.440 18.90  1  0    4    4
## Fiat 128       32.4   4  78.7  66 4.08 2.200 19.47  1  1    4    1
## Honda Civic    30.4   4  75.7  52 4.93 1.615 18.52  1  1    4    2
## Toyota Corolla 33.9   4  71.1  65 4.22 1.835 19.90  1  1    4    1
## Toyota Corona  21.5   4 120.1  97 3.70 2.465 20.01  1  0    3    1
## Fiat X1-9      27.3   4  79.0  66 4.08 1.935 18.90  1  1    4    1
## Lotus Europa   30.4   4  95.1 113 3.77 1.513 16.90  1  1    5    2
## Volvo 142E     21.4   4 121.0 109 4.11 2.780 18.60  1  1    4    2
```

```r
subset(mtcars, vs==1 & gear == 4) # and
```

```
##                 mpg cyl  disp  hp drat    wt  qsec vs am gear carb
## Datsun 710     22.8   4 108.0  93 3.85 2.320 18.61  1  1    4    1
## Merc 240D      24.4   4 146.7  62 3.69 3.190 20.00  1  0    4    2
```

```
## Merc 230       22.8   4 140.8  95 3.92 3.150 22.90  1  0    4    2
## Merc 280       19.2   6 167.6 123 3.92 3.440 18.30  1  0    4    4
## Merc 280C      17.8   6 167.6 123 3.92 3.440 18.90  1  0    4    4
## Fiat 128       32.4   4  78.7  66 4.08 2.200 19.47  1  1    4    1
## Honda Civic    30.4   4  75.7  52 4.93 1.615 18.52  1  1    4    2
## Toyota Corolla 33.9   4  71.1  65 4.22 1.835 19.90  1  1    4    1
## Fiat X1-9      27.3   4  79.0  66 4.08 1.935 18.90  1  1    4    1
## Volvo 142E     21.4   4 121.0 109 4.11 2.780 18.60  1  1    4    2
```

```r
subset(mtcars, vs==1 | gear == 4) # or
```

```
##                 mpg cyl  disp  hp drat    wt  qsec vs am gear carb
## Mazda RX4      21.0   6 160.0 110 3.90 2.620 16.46  0  1    4    4
## Mazda RX4 Wag  21.0   6 160.0 110 3.90 2.875 17.02  0  1    4    4
## Datsun 710     22.8   4 108.0  93 3.85 2.320 18.61  1  1    4    1
## Hornet 4 Drive 21.4   6 258.0 110 3.08 3.215 19.44  1  0    3    1
## Valiant        18.1   6 225.0 105 2.76 3.460 20.22  1  0    3    1
## Merc 240D      24.4   4 146.7  62 3.69 3.190 20.00  1  0    4    2
## Merc 230       22.8   4 140.8  95 3.92 3.150 22.90  1  0    4    2
## Merc 280       19.2   6 167.6 123 3.92 3.440 18.30  1  0    4    4
## Merc 280C      17.8   6 167.6 123 3.92 3.440 18.90  1  0    4    4
## Fiat 128       32.4   4  78.7  66 4.08 2.200 19.47  1  1    4    1
## Honda Civic    30.4   4  75.7  52 4.93 1.615 18.52  1  1    4    2
## Toyota Corolla 33.9   4  71.1  65 4.22 1.835 19.90  1  1    4    1
## Toyota Corona  21.5   4 120.1  97 3.70 2.465 20.01  1  0    3    1
## Fiat X1-9      27.3   4  79.0  66 4.08 1.935 18.90  1  1    4    1
## Lotus Europa   30.4   4  95.1 113 3.77 1.513 16.90  1  1    5    2
## Volvo 142E     21.4   4 121.0 109 4.11 2.780 18.60  1  1    4    2
```

2. Extra optional materials provided, the code and how it works.

Short justification for choosing this and what want to learn

I chose the "Putting points on a map" module because spatial visualization is important for my research on 'phosphorus internal loading in lakes', where identifying geographic hotspots is essential. In this module, I explored how ggplot2 uses longitude and latitude variables to create maps by layering polygons for geographic boundaries and plotting data points using geom_point(). Learning how these functions work helps me understand how to visualize spatial environmental data clearly on maps.

3. Introduction to renv.

Follow the coding demonstration in class. Turn in notes

renv package

In R, packages are normally installed in a global library, meaning the same packages are shared across all projects. Because package versions may differ between computers, this can cause code to break when a project is moved to another machine.

This creates problems for reproducibility, since the same code may not produce the same results if package versions are different.

The renv package solves this problem by creating a project-specific library that records the exact versions of packages used in the project.

This ensures that the project environment can be recreated on other computers, improving reproducibility and portability of the code.

Steps followed:

Create a GitHub repository First, a GitHub repository was created to store the project files. For this demonstration, I used the already created class repository.

Load the necessary packages The required packages were loaded in R to demonstrate how renv manages package versions.

```
library(ggplot2)
library(dplyr)
```

Initialize the renv project environment A project-specific library and lock file were created using renv.

- Run the code in the console: renv::init()
- Record the package versions used in the project: renv::snapshot()
- These commands create a project-specific library and a lock file '(renv.lock)' that records the exact versions of all packages used.

Commit the renv files to GitHub The renv.lock file and related project files were committed and pushed to GitHub so that the project environment can be reproduced elsewhere.

Recreate the environment on another computer To run the project on a different computer:

- Download the repository from GitHub.
- Open the project in RStudio.
- Install renv if it is not already installed with: install.packages("renv")
- Restore the project environment using: renv::restore()

This installs the exact package versions listed in the renv.lock file, ensuring the project runs the same way on different machines.

GitHub link: https://github.com/Dulshikamadushani/R-Practice/tree/main/Bonus%20material